

Specifications



Photo is representative



Eaton 210072

Eaton Moeller® series Z5 Overload relay, $I_r = 95 - 125$ A, 1 N/O, 1 N/C, For use with: DILM250

General specifications

PRODUCT NAME	Eaton Moeller® series Z5 Thermal overload relay
---------------------	---

CATALOG NUMBER	210072
-----------------------	--------

MODEL CODE	Z5-125/FF250
-------------------	--------------

EAN	4015082100728
------------	---------------

PRODUCT LENGTH/DEPTH	146 mm
-----------------------------	--------

PRODUCT HEIGHT	167 mm
-----------------------	--------

PRODUCT WIDTH	128 mm
----------------------	--------

PRODUCT WEIGHT	1.731 kg
-----------------------	----------

CERTIFICATIONS

IEC/EN 60947
IEC/EN 60947-4-1
CE
UL
CSA File No.: 012528
CSA Class No.: 3211-03
CSA-C22.2 No. 60947-4-1-14
UL File No.: E29184
CSA
UL 60947-4-1
UL Category Control No.: NKCR
VDE 0660

Features & Functions

FEATURES

Phase-failure sensitivity
(according to IEC/EN
60947, VDE 0660 Part 102)
Reset pushbutton
manual/auto
Test/off button
Trip-free release

General

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
CLASS	CLASS 10 A
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
DEGREE OF PROTECTION	IP00
MOUNTING METHOD	Direct attachment Direct mounting Separate mounting
OVERLOAD RELEASE CURRENT SETTING - MIN	95 A
OVERLOAD RELEASE CURRENT SETTING - MAX	125 A
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Overload relay Z5
PROTECTION	With terminal cover, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	8000 V AC 4000 V (auxiliary and control circuits)
SHOCK RESISTANCE	10 g, Mechanical, Sinusoidal, Shock duration 10 ms
SUITABLE FOR	Branch circuits, (UL/CSA)
TEMPERATURE COMPENSATION	≤ 0.25 %/K, residual error for T > 40° Continuous

Terminal capacities

TERMINAL CAPACITY (BUSBAR)	25 mm width, Main connection
TERMINAL CAPACITY (FLEXIBLE WITH CABLE LUG)	185 mm ²
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 4) mm ² , Control circuit cables 2 x (0.75 - 4) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	2/0 - 500 MCM, Main cables 2 x (18 - 14), Control circuit cables
TERMINAL CAPACITY (STRANDED WITH CABLE LUG)	185 mm ²
WIDTH ACROSS FLATS	16 mm (Hexagon head spanner SW)
STRIPPING LENGTH (CONTROL CIRCUIT CABLE)	8 mm
SCREW SIZE	M3.5, Terminal screw, Control circuit cables M10 x 35, Terminal screw, Main connections
SCREWDRIVER SIZE	1 x 6 mm, Terminal screw, Control circuit cables, Standard screwdriver 2, Terminal screw, Control circuit cables, Pozidriv screwdriver
TIGHTENING TORQUE	1.2 Nm, Screw terminals, Control circuit cables 18 Nm, Main cable connection screw/bolt

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	0.9 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.4 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.2 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	0.9 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	0.75 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	1000 V
SAFE ISOLATION	440 V, Between auxiliary contacts and main contacts, According to EN 61140 500 V AC, Between main circuits, According to EN 61140 240 V AC, Between auxiliary contacts, According to EN 61140
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	B600 at opposite polarity, AC operated (UL/CSA) R300, DC operated (UL/CSA) B300 at opposite polarity, AC operated (UL/CSA)
VOLTAGE RATING - MAX	600 VAC
VOLTAGE RATING - MAX	600 VAC

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (BASIC RATING)	10 kA, SCCR (UL/CSA) 500 A, max. CB, SCCR (UL/CSA)
	500 A Class J, max. Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT PROTECTION RATING	315 A gG/gL, Fuse, Type "1" coordination
	250 A gG/gL, Fuse, Type "2" coordination
	Max. 6 A gG/gL, fuse, Without welding, Auxiliary and control circuits

Contacts

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
--	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
--	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
--	---

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
--	---

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
--	---

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	25.5 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	8.5 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	125 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

Resources

CATALOGUES	Product Range Catalog Switching and protecting motors eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-tripping-z5-overload-relay-characteristic-curve.eps eaton-tripping-z5-overload-relay-characteristic-curve-004.eps
DECLARATIONS OF CONFORMITY	eaton-thermal-overload-relay-declaration-of-conformity-uk251268en.pdf eaton-thermal-overload-relay-declaration-of-conformity-eu250785en.pdf
DRAWINGS	eaton-tripping-devices-overload-relay-z5-overload-relay-dimensions-002.eps eaton-tripping-devices-overload-relay-z5-overload-relay-3d-drawing.eps
ECAD MODEL	ETN.210072.edz IL03407081Z
INSTALLATION INSTRUCTIONS	IL03407140Z2010_10 eaton-overload-relays-z5-zb150-il03407006z.pdf
MANUALS AND USER GUIDES	DA-MN-h1476dgb
MCAD MODEL	DA-CS-z5_ff250 DA-CD-z5_ff250
WIRING DIAGRAMS	eaton-tripping-devices-overload-relay-zeb-overload-relay-wiring-diagram.eps eaton-general-release-zeb-overload-relay-wiring-diagram.eps

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

