Specifications



Photo is representative

Eaton 215643

Eaton Moeller series xPole - Busbar. Phase busbar, 4-phases, 10qmm, fork connector, 12SU

| General specifications | |
|-------------------------|--------------------------------|
| PRODUCT NAME | Eaton Moeller series busbar |
| CATALOG NUMBER | 215643 |
| MODEL CODE | EVG-4PHAS/12MODUL |
| EAN | 9010238140325 |
| PRODUCT LENGTH/DEPTH | 210 mm |
| PRODUCT HEIGHT | 30 mm |
| PRODUCT WIDTH | 10 mm |
| PRODUCT WEIGHT | 0.095 kg |
| COMPLIANCES | RoHS conform |
| GLOBAL CATALOG | 215643 |



| Product specification | S |
|--|--|
| USED WITH | Busbar EVG |
| ТҮРЕ | • Busbar • EVG |
| FEATURES | Insulated |
| ACCESSORY/SPARE PART TYPE | Busbar for residual current circuit breakers Busbar for miniature circuit breaker Busbar for combined residual current/power circuit breaker |
| ELECTRIC CONNECTION TYPE | Fork |
| RATED SURGE VOLTAGE | 4 KV |
| RATED UNINTERRUPTED CURRENT (IU) | 63 A |
| SUITABLE FOR NUMBER OF DEVICES | 3 |
| NUMBER OF POLES | Four-pole |
| COLOR | Other |
| RATED SHORT-TIME WITHSTAND CURRENT (ICW) | 0 kA |
| CROSS SECTION | 10 mm ² |
| NUMBER OF MODULAR SPACINGS | 12 |
| NUMBER OF PHASES | 4 |
| PITCH DIMENSIONS | 0 mm |
| RATED OPERATIONAL VOLTAGE (UE) - MAX | 500 V |
| RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ) | 25 kA |
| FUNCTIONS | Busbar |
| SUITABLE FOR | Devices with N-busbar 3 devices |

| Resources | |
|----------------------------|---|
| DECLARATIONS OF CONFORMITY | DA-DC-03 EVG |
| DRAWINGS | eaton-busbar-3d- drawing.jpg |
| | eaton-mcb-busbar-3d- drawing-006.eps |

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









