

# Specifications

## Eaton 216380

Eaton Moeller® series M22 Contact element, Make contact, Bottom, Screw terminals, Base fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series M22 Accessory Contact element
<b>CATALOG NUMBER</b>	216380
<b>MODEL CODE</b>	M22-KC10
<b>EAN</b>	4015082163808
<b>PRODUCT LENGTH/DEPTH</b>	38 mm
<b>PRODUCT HEIGHT</b>	10 mm
<b>PRODUCT WIDTH</b>	32 mm
<b>PRODUCT WEIGHT</b>	0.01 kg
<b>COMPLIANCES</b>	CE Marked
<b>CERTIFICATIONS</b>	EN 60947-5 UL 508 CSA Std. C22.2 No. 14-05 IEC 60947-5 CSA Std. C22.2 No. 94-91 VDE IEC/EN 60947-5 UL Category Control No.: NKCR CSA UL CSA Class No.: 3211-03 CSA File No.: 012528 UL File No.: E29184 CSA-C22.2 No. 14-05 CE CSA-C22.2 No. 94-91 IEC 60947-5-1
<b>GLOBAL CATALOG</b>	216380

## Product specifications

<b>AMPERAGE RATING</b>	6A
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF</b>	Does not apply, since the entire switchgear needs to

## Resources

<b>CATALOGS</b>	<a href="#">eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-us-us.pdf</a> <a href="#">Flip catalog - Product Range Catalog - Command and indication</a> <a href="#">eaton-rmq-titan-brochure-br047004en-en-us.pdf</a>
<b>CERTIFICATION REPORTS</b>	<a href="#">000Z425</a>
<b>CONTROL TRAVEL DIAGRAM</b>	<a href="#">eaton-operating-diagram-m22-contact-element-contact-travel-diagram-007.eps</a> <a href="#">DA-DC-00004176.pdf</a> <a href="#">DA-DC-00004975.pdf</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00004135.pdf</a> <a href="#">DA-DC-00004134.pdf</a> <a href="#">DA-DC-00004971.pdf</a> <a href="#">DA-DC-00004157.pdf</a>
<b>DRAWINGS</b>	<a href="#">eaton-operating-pushbutton-m22-dimensions-003.eps</a> <a href="#">eaton-general-standards-000Z425.jpg</a> <a href="#">eaton-operating-contact-m22-contact-element-3d-drawing-003.eps</a> <a href="#">eaton-operating-adapter-m22-contact-element-flow-diagram-003.eps</a>
<b>ECAD MODEL</b>	<a href="#">ETN.216380.edz</a>
<b>FLYERS</b>	<a href="#">eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf</a> <a href="#">IL04716002Z</a>
<b>INSTALLATION VIDEOS</b>	<a href="#">RMQ Flat Design</a>
<b>MCAD MODEL</b>	<a href="#">DA-CD-kontaktelement_schraube_boden</a>

<b>ASSEMBLIES</b>	be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>ELECTRIC CONNECTION TYPE</b>	Screw connection
<b>OPERATING FREQUENCY</b>	3600 Operations/h
<b>POLLUTION DEGREE</b>	3
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>ACTUATING FORCE - MAX</b>	5 N
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	85 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	-25 °C
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>FORCE FOR POSITIVE OPENING - MIN</b>	0 N
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-</b>	0.11 W

	<a href="#">DA-CS-kontaktelement_schraube_boden</a>
	<a href="#">MCI Multicolor Light Indicator M22 with SmartWire-DT</a>
	<a href="#">easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator</a>
<b>MULTIMEDIA</b>	<a href="#">RMQ small E-Stop emergency-stop button</a>
	<a href="#">MCI MultiColor Light Indicator RMQ compact solution</a>
	<a href="#">eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf</a>
	<a href="#">eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf</a>
<b>SALES NOTES</b>	<a href="#">eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf</a>
	<a href="#">eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf</a>
	<a href="#">eaton-operating-contact-m22-contact-element-wiring-diagram-002.eps</a>
<b>WIRING DIAGRAMS</b>	

<b>DEPENDENT PVID</b>	
<b>NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	1
<b>NUMBER OF SWITCHES (FAULT SIGNAL)</b>	0
<b>CONNECTION TO SMARTWIRE-DT</b>	No
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	6000 V AC
<b>CONTACT CONFIGURATION</b>	1 NO
<b>COLOR</b>	Green
<b>CONNECTION TYPE</b>	Base fixing Single contact Screw connection
<b>MOUNTING METHOD</b>	Floor fastening
<b>OVERVOLTAGE CATEGORY</b>	III
<b>CONTROL CIRCUIT RELIABILITY</b>	1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA) 1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)
<b>DEGREE OF PROTECTION</b>	IP20
<b>MODEL</b>	Top mounting
<b>LAMP HOLDER</b>	None
<b>LIFESPAN, ELECTRICAL</b>	1,200,000 Operations (at 12 V, DC-13, 2.8 A) 1,000,000 Operations (at 230 V, AC-15, 1 A) 1,600,000 Operations (at 230 V, 0.5 A) 700,000 Operations (at 230 V, AC-15, 3 A)
<b>TERMINAL CAPACITY (STRANDED)</b>	0.5 - 2.5 mm <sup>2</sup>
<b>LIFESPAN, MECHANICAL</b>	5,000,000 Operations
<b>SHORT-CIRCUIT</b>	PKZM0-10/FAZ-B6/1,

<b>PROTECTION</b>	Contacts, Max. short-circuit protective device, Fuseless
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 500 V</b>	0.1 A
<b>SHORT-CIRCUIT PROTECTION RATING</b>	Max. 10 A gG/gL, Fuse, Contacts
<b>OPERATING TORQUE</b>	0.8 Nm
<b>RATED INSULATION VOLTAGE (UI)</b>	500 V
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 115 V</b>	6 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V</b>	6 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V</b>	4 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V</b>	2 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V</b>	0.6 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V</b>	0.3 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V</b>	3 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 42 V</b>	1.7 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V</b>	1.2 A
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	6 A
<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	0.5 - 1.5 mm <sup>2</sup>
<b>TERMINAL CAPACITY (SOLID)</b>	0.75 - 2.5 mm <sup>2</sup>

**SHOCK RESISTANCE**

30 g, Mechanical,  
According to IEC/EN  
60068-2-27, Sinusoidal  
shock 11 ms

**PROJECT NAME:****PROJECT NUMBER:****PREPARED BY:****DATE:****Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

