

Specifications



Photo is representative



Eaton 216383

Eaton Moeller® series M22 Contact element, Screw terminals, Base fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A M22-KC01-GVP

General specifications

PRODUCT NAME	Eaton Moeller® series M22 Accessory Contact element
CATALOG NUMBER	216383
MODEL CODE	M22-KC01-GVP
EAN	4015082163839
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	32 mm
PRODUCT WIDTH	10 mm
PRODUCT WEIGHT	0.01 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Std. C22.2 No. 94-91 IEC 60947-5 CSA Std. C22.2 No. 14-05 UL 508 EN 60947-5
CATALOG NOTES	1 N/O contact box mounting
GLOBAL CATALOG	216383



Powering Business Worldwide

Product specifications

ELECTRIC CONNECTION TYPE	Screw connection
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT STORAGE TEMPERATURE - MIN	-25 °C
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF SWITCHES (FAULT SIGNAL)	0
CONTACT CONFIGURATION	1 NC
COLOR	Red
MOUNTING METHOD	Floor fastening
MODEL	Top mounting
LAMP HOLDER	None
RATED OPERATIONAL CURRENT (IE) AT DC-13, 500 V	0.1 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	6 A

Resources

	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
CATALOGS	Flip catalog - Product Range Catalog - Command and indication eaton-rmq-titan-brochure-br047004en-en-us.pdf
CERTIFICATION REPORTS	000Z425
CONTROL TRAVEL DIAGRAM	eaton-operating-diagram-m22-contact-element-contact-travel-diagram-008.eps
DECLARATIONS OF CONFORMITY	eaton-accessory-declaration-of-conformity-eu250868en.pdf eaton-operating-pushbutton-m22-dimensions-003.eps eaton-operating-contact-m22-contact-element-3d-drawing-003.eps eaton-general-standards-000Z425.jpg eaton-operating-devices-adapter-flow-diagram-004.eps
DRAWINGS	
ECAD MODEL	ETN.216383.edz
FLYERS	eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf
INSTALLATION INSTRUCTIONS	IL04716002Z
INSTALLATION VIDEOS	RMQ Flat Design
MCAD MODEL	DA-CS-kontaktelement_schraube_boden DA-CD-kontaktelement_schraube_boden
	easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator
MULTIMEDIA	RMQ small E-Stop emergency-stop button MCI MultiColor Light Indicator RMQ compact solution

	MCI Multicolor Light Indicator M22 with SmartWire-DT
SALES NOTES	eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf
	eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf
	eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf
	eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf
WIRING DIAGRAMS	eaton-operating-contact-m22-contact-element-wiring-diagram-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

