

Specifications



Eaton 216386

Eaton Moeller® series M22 Contact element, Cage Clamp, Base fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A

General specifications

PRODUCT NAME	Eaton Moeller® series M22 Accessory Contact element
CATALOG NUMBER	216386
MODEL CODE	M22-CKC10
EAN	4015082163860
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	32 mm
PRODUCT WEIGHT	0.01 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Std. C22.2 No. 14-05 EN 60947-5 IEC 60947-5 CSA Std. C22.2 No. 94-91 UL 508 CE CSA File No.: 012528 CSA-C22.2 No. 94-91 UL File No.: E29184 CSA Class No.: 3211-03 UL IEC 60947-5-1 CSA-C22.2 No. 14-05 UL Category Control No.: NKCR CSA IEC/EN 60947-5
GLOBAL CATALOG	216386



Powering Business Worldwide

Product specifications

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.

Resources

CATALOGS	Flip catalog - Product Range Catalog - Command and indication eaton-rmq-titan-brochure-br047004en-en-us.pdf eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
CERTIFICATION REPORTS	000Z425
CONTROL TRAVEL DIAGRAM	eaton-operating-diagram-m22-contact-element-contact-travel-diagram-007.eps
DECLARATIONS OF CONFORMITY	DA-DC-00004975.pdf DA-DC-00004176.pdf DA-DC-00004135.pdf DA-DC-00004157.pdf DA-DC-00004971.pdf DA-DC-00004134.pdf
DRAWINGS	eaton-operating-contact-m22-contact-element-3d-drawing-005.eps eaton-general-standards-000Z425.jpg eaton-operating-adapter-m22-contact-element-flow-diagram-003.eps
ECAD MODEL	ETN.216386.edz
FLYERS	eaton-rmq-titan-selection-aid-brochure-fl047002-en-us.pdf
INSTALLATION INSTRUCTIONS	IL04716002Z eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf
INSTALLATION VIDEOS	RMQ Flat Design
MCAD MODEL	kontaktelelement_cage_boden.stp kontaktelelement_cage_boden
MULTIMEDIA	MCI Multicolor Light Indicator M22 with SmartWire-DT

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
ELECTRIC CONNECTION TYPE	Spring clamp connection
OPERATING FREQUENCY	3600 Operations/h
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
ACTUATING FORCE - MAX	5 N
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT STORAGE TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
FORCE FOR POSITIVE OPENING - MIN	0 N
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.11 W

	easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator MCI MultiColor Light Indicator RMQ compact solution RMQ small E-Stop emergency-stop button
PEP ECO-PASSPORT	eaton-accessory-declaration-of-conformity-eu250868en.pdf
	eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf
SALES NOTES	
WIRING DIAGRAMS	eaton-operating-contact-m22-contact-element-wiring-diagram-002.eps

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
NUMBER OF SWITCHES (FAULT SIGNAL)	0
CONNECTION TO SMARTWIRE-DT	No
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
CONTACT CONFIGURATION	1 NO
COLOR	Green
CONNECTION TYPE	Base fixing Single contact Cage Clamp
MOUNTING METHOD	Floor fastening
OVERVOLTAGE CATEGORY	III
CONTROL CIRCUIT RELIABILITY	1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA) 1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)
DEGREE OF PROTECTION	IP20
MODEL	Top mounting
LAMP HOLDER	None
LIFESPAN, ELECTRICAL	1,000,000 Operations (at 230 V, AC-15, 1 A) 1,600,000 Operations (at 230 V, 0.5 A) 1,200,000 Operations (at 12 V, DC-13, 2.8 A) 700,000 Operations (at 230 V, AC-15, 3 A)
TERMINAL CAPACITY (STRANDED)	0.5 - 2.5 mm ²
LIFESPAN, MECHANICAL	5,000,000 Operations
SHORT-CIRCUIT PROTECTION	PKZM0-10/FAZ-B6/1, Contacts, Max. short-

	circuit protective device, Fuseless
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
RATED OPERATIONAL CURRENT (IE) AT DC-13, 500 V	0.1 A
SHORT-CIRCUIT PROTECTION RATING	Max. 10 A gG/gL, Fuse, Contacts
RATED INSULATION VOLTAGE (UI)	500 V
RATED OPERATIONAL CURRENT (IE) AT AC-15, 115 V	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	4 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V	2 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.6 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.3 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	3 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 42 V	1.7 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	1.2 A
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	6 A
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	0.5 - 1.5 mm ²
TERMINAL CAPACITY (SOLID)	0.75 - 2.5 mm ²
SHOCK RESISTANCE	30 g, Mechanical, according to IEC/EN

60068-2-27, Shock
duration 11 ms

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

