



Button plate, flat, with inscription

Part no.

M22-XD-R-X0

Article no.

218153



Delivery programme

Range			RMQ-Titan (drilling dimensions 22.5 mm)
Basic function			Button plates Accessories
Single unit/Complete unit			Single unit
Description			 5 characters: letter height 5 mm > 5 characters: letter height 3 mm
Design			Flush
Name			STOP
For use with			M22(S)-D-X M22(S)-DR-X M22-DG-X M22-DZ-X
Colour, symbol			
Front ring			Front ring: titanium
Connection to SmartWire-DT			no
Accessories			General accessories
Basic function accessories			Button plates
			For enclosed overload relays Mounting diameter: 22.3 mm
Product range			Accessories
Accessories			Pushbuttons
Description			Mounting diameter: 22.3 mm
Function			For enclosed overload relays
Button plate			red with white circle
Notes			
Red button plate with white circle			
Information relevant for export to North America			
Product Standards IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking			
UL File No. E29184			
UL CCN NKCR			
CSA File No. 012528			
CSA Class No. 3211-03			
NA Certification UL Listed, CSA certified			

Approbationen

Product Standards
UL File No.
UL CCN
CSA File No.
CSA Class No.
NA Certification
Specially designed for NA

UL 508; CSA-C22.2 No. 14; IEC/EN 60947; CE marking
E29184
NKCR
12528
3211-03
UL Listed, CSA certified
No

Technische Daten nach ETIM 4.0

Inscription			-
Suitable for selector switch			No
ISO symbol inscription			Symbol "0"
Color			red
Mushroom head pushbutton			No
Suitable for signalling lamp			No
Suitable for pushbuttons			YES
External diameter		mm	22
Suitable for illuminated pushbutton actuator			No
Width		mm	0
Program diameter		mm	22
Form			Round
Height		mm	0
Design			flush
Suitable for engraving			No
Suitable for indicator light			No

CAD-Daten

Product standards CAD data:

<http://eaton-moeller.partcommunity.com>

Additional product information (links)

AWA1160-1745 (IL04716002Z) The RMQ-Titan system	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/17450510.pdf
---	---