
Specifications



Eaton 218178

Eaton Moeller® series M22 Button plate, flat black, unlock symbol

General specifications	
PRODUCT NAME	Eaton Moeller® series M22 Accessory Button plate
CATALOG NUMBER	218178
MODEL CODE	M22-XD-S-X12
EAN	4015082181789
PRODUCT LENGTH/DEPTH	24 mm
PRODUCT HEIGHT	3 mm
PRODUCT WIDTH	24 mm
PRODUCT WEIGHT	0.002 kg
CERTIFICATIONS	UL/CSA certification not required
GLOBAL CATALOG	218178



e ded ne
e e ded
e e ded ne
ded ne
ents.
ents.
ents.
ents.
e the eds to
e the eds to
ents.
e the eds to
ents.
e the eds to

Resources	
CATALOGS	eaton-rmq-titan-brochure- br047004en-en-us.pdf
	eaton-pushbuttons-signal- towers-sensors- assortment-overview- catalog-ca047003en-en- us.pdf
	Flip catalog - Product Range Catalog - Command and indication
DRAWINGS	<u>116C153</u>
ECAD MODEL	ETN.218178.edz
FLYERS	eaton-rmq-titan-selection- aid-brochure-fl047002-en- us.pdf
INSTALLATION INSTRUCTIONS	<u>IL04716002Z</u>
INSTALLATION VIDEOS	RMQ Flat Design
MCAD MODEL	DA-CD- tastenplattenlinse flach
	DA-CS- tastenplattenlinse_flach
MULTIMEDIA	MCI Multicolor Light Indicator M22 with SmartWire-DT
	MCI MultiColor Light Indicator RMQ compact solution
	RMQ small E-Stop emergency-stop button
	easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator
SALES NOTES	eaton-rmq-mci-multi- color-light-indicator-flyer- fl047005en-en-us.pdf
	eaton-control circuit- devices rmq-titan- fl144090en-en-us.pdf
	eaton-rmq-small-e-stop- flyer-fl047006en-en-us.pdf
	eaton-rmq-flat-enclosure- flyer-fl047003en-en-us.pdf

SHOCK	be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.
CONSTRUCTION TYPE	Flat
CONNECTION TO SMARTWIRE-DT	No
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	0 W
OUTSIDE DIAMETER	22.5 mm
PROGRAM DIAMETER	22 mm
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
COLOR	Black
SHAPE	Round
DESIGN	Flush
LANGUAGE	Other
INSCRIPTION	Other
INSCRIPTION TYPE	Symbol

IMPRINT	Other
IMPRINT ISO SYMBOLS	Symbol "unlock"
SUITABLE FOR	Push button

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









