Specifications



Eaton 218404

Eaton Moeller® series M22 Lens, indicator light white, flush, UP M22-XL-W-D3

General specifications	
PRODUCT NAME	Eaton Moeller® series M22 Accessory Lens
CATALOG NUMBER	218404
MODEL CODE	M22-XL-W-D3
EAN	4015082184049
PRODUCT LENGTH/DEPTH	29 mm
PRODUCT HEIGHT	9 mm
PRODUCT WIDTH	29 mm
PRODUCT WEIGHT	0.002 kg
CERTIFICATIONS	UL/CSA certification not required
GLOBAL CATALOG	218404



Product specification	S
ТҮРЕ	Lenses for indicator lights
FEATURES	Labelled
10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.

	Resources	
lights		eaton-pushbuttons-signal- towers-sensors- assortment-overview- catalog-ca047003en-en- us.pdf
e	CATALOGS	eaton-rmq-titan-brochure- br047004en-en-us.pdf
S		Flip catalog - Product Range Catalog - Command and indication
e	DRAWINGS	eaton-operating-button- symbol-007.eps
	ECAD MODEL	ETN.218404.edz
ie ided he L) is	FLYERS	eaton-rmq-titan-selection- aid-brochure-fl047002-en- us.pdf
	INSTALLATION INSTRUCTIONS	<u>IL04716002Z</u>
nents.	INSTALLATION VIDEOS	RMQ Flat Design
	MCAD MODEL	DA-CD-linse flach
nents.	MCAD MODEL	DA-CS-linse flach
nents.	nts.	MCI Multicolor Light Indicator M22 with SmartWire-DT
		RMQ small E-Stop emergency-stop button
nents.		easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator
te the		MCI MultiColor Light Indicator RMQ compact solution
eeds to		eaton-rmq-small-e-stop- flyer-fl047006en-en-us.pdf
ee the eeds to	SALES MOTES	eaton-rmq-mci-multi- color-light-indicator-flyer- fl047005en-en-us.pdf
nents.	SALES NOTES	eaton-rmq-flat-enclosure- flyer-fl047003en-en-us.pdf
ee the eeds to		eaton-control circuit- devices rmq-titan- fl144090en-en-us.pdf
nents		

10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.
CONNECTION TO SMARTWIRE-DT	No
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
BUILT-IN DIAMETER	22.5 mm
EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
PRODUCT CATEGORY	Accessories
DIAMETER	29.6 mm
LENS COLOR	White
DESIGN	Flat Flush
INSCRIPTION	Individual inscription possible: ≤ 5 characters:

	letter height 5 mm Individual inscription possible: > 5 characters: letter height 3 mm " AUF "
INSCRIPTION TYPE	Text
LENS SHAPE	Round

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

 $\hbox{@ 2025 Eaton.}$ All Rights Reserved.

Follow us on social media to get the latest product and support information.









