Specifications



Eaton 218419

Eaton Moeller® series M22 Lens, indicator light white, flush, TEST

General specifications	
PRODUCT NAME	Eaton Moeller® series M22 Accessory Lens
CATALOG NUMBER	218419
MODEL CODE	M22-XL-W-GB9
EAN	4015082184193
PRODUCT LENGTH/DEPTH	29 mm
PRODUCT HEIGHT	9 mm
PRODUCT WIDTH	29 mm
PRODUCT WEIGHT	0.002 kg
CERTIFICATIONS	UL/CSA certification not required



Features & Function	าร
DESIGN	Flat Flush
FEATURES	Labelled
INSCRIPTION	Individual inscription possible: ≤ 5 characters: letter height 5 mm Individual inscription possible: > 5 characters: letter height 3 mm " TEST "
INSCRIPTION TYPE	Text
LENS COLOR	White

PRODUCT CATEGORY	Accessories
ТҮРЕ	Lenses for indicator lights

Climatic environmental conditions	
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	70 °C

Communication	
CONNECTION TO SMARTWIRE-DT	No

EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID HEAT DISSIPATION CAPACITY PDISS HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS 10.2.2 CORROSION RESISTANCE Meets the product standard's requirements. Meets the product
CAPACITY PDISS HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS 10.2.2 CORROSION RESISTANCE Meets the product standard's requirements. Meets the product
POLE, CURRENT-DEPENDENT PVID RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS 10.2.2 CORROSION RESISTANCE Meets the product standard's requirements. Meets the product
CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS 10.2.2 CORROSION RESISTANCE Meets the product standard's requirements. Meets the product
DISSIPATION, NON- CURRENT-DEPENDENT PVS 10.2.2 CORROSION RESISTANCE Meets the product standard's requirements. 10.2.3.1 VERIFICATION OF Meets the product
RESISTANCE standard's requirements. 10.2.3.1 VERIFICATION OF Meets the product
Meets the product
THERMAL STABILITY OF standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF Meets the product INSULATING MATERIALS TO NORMAL HEAT Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) Please enquire RADIATION
Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS Meets the product standard's requirements.
10.3 DEGREE OFDoes not apply, since thePROTECTION OFentire switchgear needs toASSEMBLIESbe evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES Meets the product standard's requirements.

Resources	
CATALOGUES	Flip catalog - Product Range Catalog - Command and indication
	eaton-pushbuttons-signal- towers-sensors- assortment-overview- catalog-ca047003en-en- us.pdf
	eaton-rmq-titan-brochure- br047004en-en-us.pdf
DRAWINGS	eaton-operating-button- symbol-007.eps
ECAD MODEL	ETN.218419.edz
FLYERS	eaton-rmq-titan-selection- aid-brochure-fl047002-en- us.pdf
INSTALLATION INSTRUCTIONS	<u>IL04716002Z</u>
INSTALLATION VIDEOS	RMQ Flat Design
MCAD MODEL	DA-CD-linse flach
MCAD MODEL	DA-CS-linse flach
MULTIMEDIA	RMQ small E-Stop emergency-stop button
	easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator
	MCI MultiColor Light Indicator RMQ compact solution
	MCI Multicolor Light Indicator M22 with SmartWire-DT
SALES NOTES	eaton-rmq-small-e-stop- flyer-fl047006en-en-us.pdf
	eaton-control circuit- devices rmq-titan- fl144090en-en-us.pdf
	eaton-rmq-flat-enclosure- flyer-fl047003en-en-us.pdf
	eaton-rmq-mci-multi- color-light-indicator-flyer- fl047005en-en-us.pdf

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	ls the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









