

RPI-BC 107,6 DEV-KIT KMGY - Electronics housing



2202874

<https://www.phoenixcontact.com/pc/products/2202874>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail housing for Raspberry Pi computers (suitable for Raspberry Pi A+, B+, B2, B3, B4); set consisting of lower part, upper part, cover, and PCB retainer; housing according to DIN 43880

Your advantages

- Tool-free mounting
- Plenty of space for additional circuits on matrix or additional boards
- GPIO strip can be used with PTSM series connection technology
- Easy module-to-module connection, thanks to bus connection via DIN rails

Commercial data


Item number	2202874
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	ACHBAE
GTIN	4055626257211
Weight per piece (including packing)	119.4 g
Weight per piece (excluding packing)	119.4 g
Customs tariff number	85472000
Country of origin	DE

Technical data

Product properties

Product type	Stackable housing set
Housing series	BC
Type	Housing set
Housing type	DIN rail housing for use in distribution boards in accordance with DIN 43880
Ventilation openings present	yes

Dimensions

Dimensional drawing	
Width	107.6 mm
Height	89.7 mm
Depth	62.2 mm

Material specifications

Color (Upper housing part)	light grey (RAL 7035)
Color (Lower housing part)	light grey (RAL 7035)
Flammability rating according to UL 94	V0
Housing material	Polycarbonate

Environmental and real-life conditions

Power dissipation single housing for 20 °C

Ambient temperature	20 °C
Reduction factor	1

Power dissipation single housing for 30 °C

Ambient temperature	30 °C
Reduction factor	0.84

Power dissipation single housing for 40 °C

Ambient temperature	40 °C
Reduction factor	0.72

Power dissipation single housing for 50 °C

Ambient temperature	50 °C
Reduction factor	0.6

2202874

<https://www.phoenixcontact.com/pc/products/2202874>

Power dissipation single housing for 60 °C

Ambient temperature	60 °C
Reduction factor	0.48

Power dissipation single housing for 70 °C

Ambient temperature	70 °C
Reduction factor	0.38

Ambient conditions

Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C

PCB data

Type of PCB mount	Latching
-------------------	----------

Mounting

Mounting type	Snap in
---------------	---------

Packaging specifications

Type of packaging	packed in cardboard
Outer packaging type	Carton

Drawings

Dimensional drawing



Schematic figure for illustrating the item dimensions. The figure is not of the desired product. For further details, refer to the product drawings in the "Downloads" tab.

RPI-BC 107,6 DEV-KIT KMGY - Electronics housing



2202874

<https://www.phoenixcontact.com/pc/products/2202874>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2202874>



UL Recognized

Approval ID: FILE E 240868

2202874

<https://www.phoenixcontact.com/pc/products/2202874>

Classifications

ECLASS

ECLASS-11.0	27182702
ECLASS-13.0	27190201

ETIM

ETIM 9.0	EC001031
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com