

2203157
<https://www.phoenixcontact.com/no/products/2203157>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Handheld housing, C-Mini-Plus, light gray, consisting of two half shells, screws. Front 1.1 mm recessed, with window and keypad slot, battery compartment cover and battery contacts for 2 AA batteries

Your advantages

- Suitable for handheld devices
- Easy integration of LCD displays and membrane keypads
- Ergonomic straight or staggered housing design
- Fast mounting, thanks to the modular design

Commercial data

Item number	2203157
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	31BAC
Product key	ACFACA
GTIN	4055626377094
Weight per piece (including packing)	152 g
Weight per piece (excluding packing)	93 g
Customs tariff number	84879090
Country of origin	DE

HCS-C MINI-P 1W 2AA C C 7035 - Electronics housing

2203157

<https://www.phoenixcontact.com/no/products/2203157>

Technical data


Product properties

Product type	Complete housing
Housing series	HCS
Type	straight
Housing type	Handheld housing
Ventilation openings present	no
Battery compartment	2 x AA

Display

Diagonal	2.8 in. / 7 cm (Window for display)
----------	-------------------------------------

Dimensions

Dimensional drawing	
Width	80 mm
Height	135 mm
Depth	29 mm
Dimensions	70.4 mm x 69.2 mm x 1.1 mm (Recessed area on front)
	70.4 mm x 8.2 mm x 1.1 mm (Recessed area on front)
	63 mm x 34 mm (Window for display)
	70.4 mm x 43 mm x 2.5 mm (Holder for cover lens)

PCB design

PCB thickness	1.4 mm ... 1.8 mm
---------------	-------------------

Material specifications

Color (Housing)	light grey (RAL 7035)
Flammability rating according to UL 94	V0
CTI according to IEC 60112	$400 \leq \text{CTI} < 600$
Insulating material	II
Surface characteristics	untreated
Housing material	ABS

Environmental and real-life conditions

Glow-wire test

Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s

HCS-C MINI-P 1W 2AA C C 7035 - Electronics housing



2203157

<https://www.phoenixcontact.com/no/products/2203157>

Thermal stability / ball thrust test

Specification	IEC 60695-10-2:2014-02
Temperature	80 °C
Test duration	1 h
Force	20

Ambient conditions

Max. IP code to attain	IP40
Ambient temperature (operation)	-40 °C ... 80 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C ... 55 °C
Ambient temperature (assembly)	-5 °C ... 80 °C
Relative humidity (storage/transport)	95 %

PCB data

Number of PCB holders	2
Thickness of the PCB	1.4 mm ... 1.8 mm

Mounting

Tightening torque / speed	Screw connection between housing halves: 0.25 Nm-0.3 Nm / 500 rpm-1000 rpm
---------------------------	--


HCS-C MINI-P 1W 2AA C C 7035 - Electronics housing

2203157

<https://www.phoenixcontact.com/no/products/2203157>

Drawings

Dimensional drawing



Schematic representation – for additional information, see product range drawing in the Download Center

HCS-C MINI-P 1W 2AA C C 7035 - Electronics housing



2203157

<https://www.phoenixcontact.com/no/products/2203157>

Classifications

ECLASS

ECLASS-11.0	27182702
ECLASS-13.0	27190102

ETIM

ETIM 9.0	EC001031
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT AS
Strømsveien 344
N-1081 Oslo
+47 22 07 68 00
norge@phoenixcontact.com