

# UCS CC 7035 - Corner inlay

2203395

<https://www.phoenixcontact.com/pc/products/2203395>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Corner inlay for UCS housings, material: polyamide, color: light gray, similar to RAL 7035



## Your advantages

- Flexible mounting options for the control cabinet and use in the field
- Can be adapted to suit the application, thanks to identical receptacles in the housing
- Different colors for high recognition value inside and outside the control cabinet

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2203395       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Product key                          | ACFCAA        |
| GTIN                                 | 4055626427928 |
| Weight per piece (including packing) | 10.6 g        |
| Weight per piece (excluding packing) | 10.6 g        |
| Customs tariff number                | 84879090      |
| Country of origin                    | DE            |

# UCS CC 7035 - Corner inlay

2203395

<https://www.phoenixcontact.com/pc/products/2203395>



## Technical data

### Notes

|         |                                                             |
|---------|-------------------------------------------------------------|
| General | Refer to the data sheet for the range in the download area. |
|---------|-------------------------------------------------------------|

### Product properties

|                              |                        |
|------------------------------|------------------------|
| Product type                 | Select corner          |
| Product family               | UCS                    |
| Housing series               | UCS                    |
| Type                         | including screws, flat |
| Housing type                 | Universal housings     |
| Ventilation openings present | no                     |

### Dimensions

|        |         |
|--------|---------|
| Width  | 16.2 mm |
| Height | 16.2 mm |
| Depth  | 13.5 mm |

### PCB design

|               |                 |
|---------------|-----------------|
| PCB thickness | 0.8 mm ... 3 mm |
|---------------|-----------------|

### Material specifications

|                                        |                       |
|----------------------------------------|-----------------------|
| Color (Housing)                        | light grey (RAL 7035) |
| Flammability rating according to UL 94 | V0                    |
| CTI according to IEC 60112             | 600                   |
| Insulating material                    | PA                    |
| Housing material                       | Polyamide             |
| Surface characteristics                | untreated             |

### Environmental and real-life conditions

#### Vibration test

|                        |                             |
|------------------------|-----------------------------|
| Specification          | IEC 60068-2-6:2007-12       |
| Frequency              | 10 - 150 - 10 Hz            |
| Sweep speed            | 1 octave/min                |
| Amplitude              | 0.15 mm (10 Hz ... 58.1 Hz) |
| Acceleration           | 2g (58.1 Hz ... 150 Hz)     |
| Test duration per axis | 2.5 h                       |
| Test directions        | X-, Y- and Z-axis           |

#### Glow-wire test

|                  |                        |
|------------------|------------------------|
| Specification    | IEC 60695-2-11:2014-02 |
| Temperature      | 850 °C                 |
| Time of exposure | 30 s                   |

#### Thermal stability / ball thrust test

# UCS CC 7035 - Corner inlay

2203395

<https://www.phoenixcontact.com/pc/products/2203395>



|               |                        |
|---------------|------------------------|
| Specification | IEC 60695-10-2:2014-02 |
| Temperature   | 125 °C                 |
| Test duration | 1 h                    |
| Force         | 20 N                   |

## Mechanical strength / tumbling barrel

|                |                        |
|----------------|------------------------|
| Specification  | IEC 60068-2-31:2008-05 |
| Height of fall | 50 cm                  |
| Frequency      | 50                     |

## Shocks

|                                |                                   |
|--------------------------------|-----------------------------------|
| Specification                  | IEC 60068-2-27:2008-02            |
| Pulse shape                    | Half-sine                         |
| Acceleration                   | 15g                               |
| Shock duration                 | 11 ms                             |
| Number of shocks per direction | 3                                 |
| Test directions                | X-, Y- and Z-axis (pos. and neg.) |

## Test for substances that would hinder coating with paint or varnish

|               |                      |
|---------------|----------------------|
| Specification | VW PV 3.10.7:2005-02 |
| Result        | Test passed          |

## Degree of protection (IP code)

|                                       |                                                   |
|---------------------------------------|---------------------------------------------------|
| Specification                         | IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08 |
| Result, degree of protection, IP code | IP40                                              |

## Ambient conditions

|                                         |                                                    |
|-----------------------------------------|----------------------------------------------------|
| Max. IP code to attain                  | IP40                                               |
| Ambient temperature (operation)         | -40 °C ... 105 °C (depending on power dissipation) |
| Ambient temperature (storage/transport) | -40 °C ... 55 °C                                   |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                   |
| Relative humidity (storage/transport)   | 80 %                                               |

## PCB data

|                      |                 |
|----------------------|-----------------|
| Type of PCB mount    | Bolt mounting   |
| Thickness of the PCB | 0.8 mm ... 3 mm |

## Mounting

|                           |                                                                           |
|---------------------------|---------------------------------------------------------------------------|
| Mounting type             | Screw mounting                                                            |
| Mounting position         | any                                                                       |
| Tightening torque / speed | Screw connection between housing halves: 1.2 Nm-1.4 Nm / 500 rpm-1000 rpm |
|                           | Mounting of PCB on corner feeder: 0.4 Nm-0.5 Nm / 500 rpm-1000 rpm        |

## Packaging specifications

|                   |        |
|-------------------|--------|
| Type of packaging | PE bag |
|-------------------|--------|

# UCS CC 7035 - Corner inlay

2203395

<https://www.phoenixcontact.com/pc/products/2203395>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27182702 |
| ECLASS-13.0 | 27190605 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001031 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

# UCS CC 7035 - Corner inlay

2203395

<https://www.phoenixcontact.com/pc/products/2203395>



## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)