

# Specifications

## Eaton 221516

Eaton Moeller® series STN Control transformer, 0.5 kVA, Rated input voltage 400± 5 % V, Rated output voltage 24 V

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series STN Control transformer
<b>CATALOG NUMBER</b>	221516
<b>EAN</b>	4015082215163
<b>PRODUCT LENGTH/DEPTH</b>	120 mm
<b>PRODUCT HEIGHT</b>	133 mm
<b>PRODUCT WIDTH</b>	121 mm
<b>PRODUCT WEIGHT</b>	5.139 kg
<b>CERTIFICATIONS</b>	CE VDE 0570 Part 2-2 UL 506 CSA-C22.2 No. 66.1-06 CSA-C22.2 No. 66.2-06 IEC/EN 61558-2-2 UL Category Control No.: XPTQ2, XPTQ8 UL File No.: E167225 UL Recognized IEC/EN 60204-1, ÖVE-EN 13 VDE 0113, VDE 0100 Part 410 CSA-C22.2 No. 66 UL report applies to both US and Canada Certified by UL for use in Canada UL5085-1 UL 5085-2
<b>CATALOG NOTES</b>	Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 °C
<b>MODEL CODE</b>	STN0,5(400/24)



Powering Business Worldwide

## Product specifications

<b>TYPE</b>	Single-phase STN control transformers
<b>FEATURES</b>	Separate windings Fully Vacuum-impregnated
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product

## Resources

<b>APPLICATION NOTES</b>	<a href="#">eaton-transformer-stz-sti-stn-dtz-uti-ap009002-en-us.pdf</a>
<b>BROCHURES</b>	<a href="#">eaton-transformers-brochure-br009002en-en-us.pdf</a>
<b>CATALOGUES</b>	<a href="#">eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00004448.pdf</a> <a href="#">DA-DC-00004420.pdf</a>
<b>ECAD MODEL</b>	<a href="#">ETN.221516.edz</a>
<b>MCAD MODEL</b>	<a href="#">DA-CS-stn0_5_24</a> <a href="#">DA-CD-stn0_5_24</a>
<b>SYSTEM OVERVIEW</b>	<a href="#">eaton-general-diagram-sti-control-transformer-explosion-drawing.eps</a>

	standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>APPARENT POWER</b>	500 VA
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
<b>NO-LOAD LOSSES</b>	15 W
<b>PRIMARY VOLTAGE 1 - MAX</b>	400 V
<b>PRIMARY VOLTAGE 1 - MIN</b>	400 V
<b>PRIMARY VOLTAGE 10 - MAX</b>	0 V
<b>PRIMARY VOLTAGE 10 - MIN</b>	0 V
<b>PRIMARY VOLTAGE 2 -</b>	0 V

<b>MAX</b>	
<b>PRIMARY VOLTAGE 2 - MIN</b>	0 V
<b>PRIMARY VOLTAGE 3 - MAX</b>	0 V
<b>PRIMARY VOLTAGE 3 - MIN</b>	0 V
<b>PRIMARY VOLTAGE 4 - MAX</b>	0 V
<b>PRIMARY VOLTAGE 4 - MIN</b>	0 V
<b>PRIMARY VOLTAGE 5 - MAX</b>	0 V
<b>PRIMARY VOLTAGE 5 - MIN</b>	0 V
<b>PRIMARY VOLTAGE 6 - MAX</b>	0 V
<b>CONDUCTOR MATERIAL</b>	Copper
<b>DEGREE OF PROTECTION</b>	IP00
<b>CONNECTION LUG</b>	Yes for > 115 A
<b>CONNECTION TYPE</b>	Terminations, < 115 A
<b>DUTY FACTOR</b>	100 %
<b>INSULATION MATERIAL TYPE (IEC 85)</b>	B
<b>EFFICIENCY</b>	93 %
<b>RELATIVE SHORT-CIRCUIT VOLTAGE</b>	4.1 %
<b>SUITABLE FOR</b>	Branch circuits, (UL/CSA)
<b>INSULATION CLASS</b>	B
<b>PRIMARY TAPPING</b>	± 5 %
<b>PRIMARY VOLTAGE 6 - MIN</b>	0 V
<b>PRIMARY VOLTAGE 7 - MAX</b>	0 V
<b>PRIMARY VOLTAGE 7 - MIN</b>	0 V
<b>PRIMARY VOLTAGE 8 - MAX</b>	0 V
<b>PRIMARY VOLTAGE 8 - MIN</b>	0 V
<b>PRIMARY VOLTAGE 9 - MAX</b>	0 V
<b>PRIMARY VOLTAGE 9 - MIN</b>	0 V
<b>RATED FREQUENCY - MAX</b>	60 Hz

<b>RATED FREQUENCY - MIN</b>	50 Hz
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
<b>RATED POWER</b>	0.5 VA
<b>SECONDARY VOLTAGE 1 - MAX</b>	24 V
<b>SECONDARY VOLTAGE 1 - MIN</b>	24 V
<b>SECONDARY VOLTAGE 10 - MAX</b>	0 V
<b>SECONDARY VOLTAGE 10 - MIN</b>	0 V
<b>SECONDARY VOLTAGE 2 - MAX</b>	0 V
<b>SECONDARY VOLTAGE 2 - MIN</b>	0 V
<b>SECONDARY VOLTAGE 3 - MAX</b>	0 V
<b>SECONDARY VOLTAGE 3 - MIN</b>	0 V
<b>SECONDARY VOLTAGE 4 - MAX</b>	0 V
<b>PRODUCT CATEGORY</b>	Single-phase control transformers ST
<b>SECONDARY VOLTAGE 4 - MIN</b>	0 V
<b>SECONDARY VOLTAGE 5 - MAX</b>	0 V
<b>SECONDARY VOLTAGE 5 - MIN</b>	0 V
<b>SECONDARY VOLTAGE 6 - MAX</b>	0 V
<b>SECONDARY VOLTAGE 6 - MIN</b>	0 V
<b>SECONDARY VOLTAGE 7 - MAX</b>	0 V
<b>SECONDARY VOLTAGE 7 - MIN</b>	0 V
<b>SECONDARY VOLTAGE 8 - MAX</b>	0 V
<b>SECONDARY VOLTAGE 8 - MIN</b>	0 V
<b>SECONDARY VOLTAGE 9 - MAX</b>	0 V
<b>SECONDARY VOLTAGE 9 - MIN</b>	0 V

<b>SHORT-CIRCUIT LOSSES</b>	27 W
<b>SHORT-TIME RATING</b>	0.88 kVA
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	42 W
<b>VOLTAGE RATING - MAX</b>	600 V
<b>POWER CONSUMPTION IN STANDBY MODE</b>	7 W

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

