

# Specifications

Photo is representative

## Eaton 222867

Eaton Moeller® series T3 Main switch, T3, 32 A, surface mounting, 3 contact unit(s), 3 pole, 2 N/O, Emergency switching off function, With red rotary handle and yellow locking ring

### General specifications

|                             |                                                                                                                                                                                                                                                           |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series T3 Main switch                                                                                                                                                                                                                      |
| <b>CATALOG NUMBER</b>       | 222867                                                                                                                                                                                                                                                    |
| <b>EAN</b>                  | 4015082228675                                                                                                                                                                                                                                             |
| <b>PRODUCT LENGTH/DEPTH</b> | 206 mm                                                                                                                                                                                                                                                    |
| <b>PRODUCT HEIGHT</b>       | 135 mm                                                                                                                                                                                                                                                    |
| <b>PRODUCT WIDTH</b>        | 187 mm                                                                                                                                                                                                                                                    |
| <b>PRODUCT WEIGHT</b>       | 0.585 kg                                                                                                                                                                                                                                                  |
| <b>CERTIFICATIONS</b>       | IEC/EN 60947<br>CE<br>UL<br>CSA-C22.2 No. 60947-4-1-14<br>CSA-C22.2 No. 94<br>IEC/EN 60947-3<br>UL Category Control No.: NLRV<br>CSA Class No.: 3211-07<br>CSA File No.: 012528<br>UL 60947-4-1<br>VDE 0660<br>IEC/EN 60204<br>CSA<br>UL File No.: E36332 |
| <b>CATALOG NOTES</b>        | Rated Short-time<br>Withstand Current (Icw)<br>for a time of 1 second                                                                                                                                                                                     |
| <b>MODEL CODE</b>           | T3-3-15259/I2/SVB                                                                                                                                                                                                                                         |

## Features & Functions

|                        |                                                      |
|------------------------|------------------------------------------------------|
| <b>FEATURES</b>        | Version as maintenance-<br>/service switch           |
|                        | Version as main switch                               |
|                        | Version as emergency stop<br>installation            |
|                        |                                                      |
| <b>FITTED WITH:</b>    | Red rotary handle and<br>yellow locking ring         |
| <b>FUNCTIONS</b>       | Emergency switching off<br>function<br>Interlockable |
| <b>NUMBER OF POLES</b> | 3                                                    |

## General

|                                               |                                                                                         |
|-----------------------------------------------|-----------------------------------------------------------------------------------------|
| <b>DEGREE OF PROTECTION</b>                   | NEMA 12                                                                                 |
| <b>DEGREE OF PROTECTION (FRONT SIDE)</b>      | IP65                                                                                    |
| <b>LIFESPAN, MECHANICAL</b>                   | 500,000 Operations                                                                      |
| <b>MOUNTING METHOD</b>                        | Surface mounting                                                                        |
| <b>MOUNTING POSITION</b>                      | As required                                                                             |
| <b>NUMBER OF CONTACT UNITS</b>                | 3                                                                                       |
| <b>OPERATING FREQUENCY</b>                    | 1200 Operations/h                                                                       |
| <b>OVERVOLTAGE CATEGORY</b>                   | III                                                                                     |
| <b>POLLUTION DEGREE</b>                       | 3                                                                                       |
| <b>PRODUCT CATEGORY</b>                       | Main switch                                                                             |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b> | 6000 V AC                                                                               |
| <b>SAFE ISOLATION</b>                         | 440 V AC, Between the<br>contacts, According to EN<br>61140                             |
| <b>SAFETY PARAMETER (EN ISO 13849-1)</b>      | B10d values as per EN ISO<br>13849-1, table C.1                                         |
| <b>SHOCK RESISTANCE</b>                       | 12 g, Mechanical,<br>According to IEC/EN<br>60068-2-27, Half-<br>sinusoidal shock 20 ms |
| <b>SUITABLE FOR</b>                           | Ground mounting<br>Branch circuits, suitable as<br>motor disconnect,<br>(UL/CSA)        |
| <b>SWITCHING ANGLE</b>                        | 90 °                                                                                    |

## Climatic environmental conditions

|                                            |        |
|--------------------------------------------|--------|
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b> | -25 °C |
|--------------------------------------------|--------|

|                                            |       |
|--------------------------------------------|-------|
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b> | 40 °C |
|--------------------------------------------|-------|

|                                                       |        |
|-------------------------------------------------------|--------|
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b> | -25 °C |
|-------------------------------------------------------|--------|

|                                                       |       |
|-------------------------------------------------------|-------|
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b> | 40 °C |
|-------------------------------------------------------|-------|

|                          |                                                                                |
|--------------------------|--------------------------------------------------------------------------------|
| <b>CLIMATIC PROOFING</b> | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
|--------------------------|--------------------------------------------------------------------------------|

## Terminal capacities

|                          |                                                                                                                                                                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>TERMINAL CAPACITY</b> | 2 x (0.75 - 4) mm <sup>2</sup> , flexible with ferrules to DIN 46228<br>1 x (0.75 - 4) mm <sup>2</sup> , flexible with ferrules to DIN 46228<br>2 x (1 - 6) mm <sup>2</sup> , solid or stranded<br>1 x (1 - 6) mm <sup>2</sup> , solid or stranded |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                    |
|-------------------|--------------------|
| <b>SCREW SIZE</b> | M4, Terminal screw |
|-------------------|--------------------|

|                          |                         |
|--------------------------|-------------------------|
| <b>TIGHTENING TORQUE</b> | 1.6 Nm, Screw terminals |
|--------------------------|-------------------------|

## Electrical rating

**RATED BREAKING  
CAPACITY AT 220/230 V** 260 A  
(COS PHI TO IEC 60947-3)

**RATED BREAKING  
CAPACITY AT 400/415 V** 260 A  
(COS PHI TO IEC 60947-3)

**RATED BREAKING  
CAPACITY AT 500 V (COS  
PHI TO IEC 60947-3)** 240 A

**RATED BREAKING  
CAPACITY AT 660/690 V** 170 A  
(COS PHI TO IEC 60947-3)

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,** 23.7 A  
220 V, 230 V, 240 V

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,** 23.7 A  
380 V, 400 V, 415 V

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,** 23.7 A  
500 V

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,** 14.7 A  
660 V, 690 V

**RATED OPERATIONAL  
CURRENT (IE) AT AC-21,** 32 A  
440 V

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,** 32 A  
230 V

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,** 32 A  
400 V, 415 V

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,** 26.4 A  
500 V

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,** 17 A  
690 V

**RATED OPERATIONAL  
CURRENT (IE) AT DC-1,  
LOAD-BREAK SWITCHES  
L/R = 1 MS** 25 A

**RATED OPERATIONAL  
CURRENT (IE) AT DC-13,  
CONTROL SWITCHES L/R  
= 50 MS** 20 A

**RATED OPERATIONAL  
CURRENT (IE) AT DC-21,** 1 A

## Short-circuit rating

**RATED CONDITIONAL  
SHORT-CIRCUIT CURRENT** 1 kA  
(IQ)

**RATED SHORT-TIME  
WITHSTAND CURRENT** 0.65 kA  
(ICW) 650 A, Contacts, 1 second

**SHORT-CIRCUIT  
PROTECTION RATING** 35 A gG/gL, Fuse, Contacts

|                                                                              |        |
|------------------------------------------------------------------------------|--------|
| <b>240 V</b>                                                                 |        |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>24 V</b>                | 25 A   |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>48 V</b>                | 25 A   |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>60 V</b>                | 25 A   |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>120 V</b>               | 12 A   |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>240 V</b>               | 5 A    |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) STAR-<br/>DELTA AT AC-3, 220/230 V</b> | 32 A   |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) STAR-<br/>DELTA AT AC-3, 380/400 V</b> | 32 A   |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) STAR-<br/>DELTA AT AC-3, 500 V</b>     | 32 A   |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) STAR-<br/>DELTA AT AC-3, 690 V</b>     | 25.5 A |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 380/400<br/>V, 50 HZ</b>             | 11 kW  |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 415 V, 50<br/>HZ</b>                 | 11 kW  |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 690 V, 50<br/>HZ</b>                 | 11 kW  |
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A,<br/>220/230 V, 50 HZ</b>           | 7.5 kW |
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 400 V,<br/>50 HZ</b>               | 15 kW  |
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 500 V,<br/>50 HZ</b>               | 15 kW  |
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 690 V,<br/>50 HZ</b>               | 15 kW  |
| <b>RATED OPERATIONAL</b>                                                     | 7.5 kW |

|                                                                       |                                                                           |
|-----------------------------------------------------------------------|---------------------------------------------------------------------------|
| <b>POWER STAR-DELTA AT<br/>220/230 V, 50 HZ</b>                       |                                                                           |
| <b>RATED OPERATIONAL<br/>POWER STAR-DELTA AT<br/>380/400 V, 50 HZ</b> | 15 kW                                                                     |
| <b>RATED OPERATIONAL<br/>POWER STAR-DELTA AT<br/>500 V, 50 HZ</b>     | 18.5 kW                                                                   |
| <b>RATED OPERATIONAL<br/>POWER STAR-DELTA AT<br/>690 V, 50 HZ</b>     | 22 kW                                                                     |
| <b>RATED OPERATIONAL<br/>VOLTAGE (UE) AT AC -<br/>MAX</b>             | 690 V                                                                     |
| <b>RATED UNINTERRUPTED<br/>CURRENT (IU)</b>                           | 32 A                                                                      |
| <b>UNINTERRUPTED<br/>CURRENT</b>                                      | Rated uninterrupted<br>current Iu is specified for<br>max. cross-section. |

## Switching capacity

|             |                                                                               |
|-------------|-------------------------------------------------------------------------------|
| LOAD RATING | 1.6 x I <sub>e</sub> (with intermittent operation class 12, 40 % duty factor) |
|             | 1.3 x I <sub>e</sub> (with intermittent operation class 12, 60 % duty factor) |
|             | 2 x I <sub>e</sub> (with intermittent operation class 12, 25 % duty factor)   |

NUMBER OF CONTACTS IN SERIES AT DC-21A, 240 V

1

NUMBER OF CONTACTS IN SERIES AT DC-23A, 24 V

1

NUMBER OF CONTACTS IN SERIES AT DC-23A, 48 V

2

NUMBER OF CONTACTS IN SERIES AT DC-23A, 60 V

3

NUMBER OF CONTACTS IN SERIES AT DC-23A, 120 V

3

NUMBER OF CONTACTS IN SERIES AT DC-23A, 240 V

5

RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)

320 A

VOLTAGE PER CONTACT PAIR IN SERIES

60 V

## Actuator

ACTUATOR COLOR Red

ACTUATOR TYPE Door coupling rotary drive

## Contacts

CONTROL CIRCUIT RELIABILITY 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)

0

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)

0

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)

2

## Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID 1.1 W

HEAT DISSIPATION CAPACITY PDISS 0 W

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID 1.1 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 32 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS 0 W

|                                                                                         |                                                                    |
|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                         |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                         |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                         |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                         |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | UV resistance only in connection with protective shield.           |
| <b>10.2.5 LIFTING</b>                                                                   | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.6 MECHANICAL IMPACT</b>                                                         | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.7 INSCRIPTIONS</b>                                                              | Meets the product standard's requirements.                         |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                                          | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                                           | Meets the product standard's requirements.                         |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                                           | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>                           | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>                                | Is the panel builder's responsibility.                             |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                                         | Is the panel builder's responsibility.                             |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                                         | Is the panel builder's responsibility.                             |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                                                 | Is the panel builder's responsibility.                             |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>                         | Is the panel builder's responsibility.                             |
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is                                               |

|                                            |                                                                                                             |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------|
|                                            | responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>          | Is the panel builder's responsibility. The specifications for the switchgear must be observed.              |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b> | Is the panel builder's responsibility. The specifications for the switchgear must be observed.              |
| <b>10.13 MECHANICAL FUNCTION</b>           | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.    |

## Resources

**BROCHURES** [Brochure - T Rotary Cam switch and P Switch-disconnector](#)

**CATALOGUES** [P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

**DECLARATIONS OF CONFORMITY** [DA-DC-00004923.pdf](#) [DA-DC-00004894.pdf](#)

**DRAWINGS** [eaton-rotary-switches-padlock-t0-main-switch-dimensions.eps](#)  
[eaton-rotary-switches-surface-mounting-t3-main-switch-dimensions-002.eps](#)  
[eaton-rotary-switches-dimensions-t3-main-switch-dimensions.eps](#)  
[eaton-general-totally-insulated-t0-main-switch-symbol.eps](#)  
[eaton-rotary-switches-t0-main-switch-symbol.eps](#)  
[eaton-general-switch-t0-main-switch-symbol.eps](#)

**ECAD MODEL** [ETN.222867.edz](#)

**INSTALLATION INSTRUCTIONS** [IL03801008Z2021\\_06.pdf](#)

**INSTALLATION VIDEOS** [Eaton's P Switch-disconnectors used in a factory](#)

**MCAD MODEL** [DA-CD-bauform5](#) [DA-CS-bauform5](#)

**PRODUCT NOTIFICATIONS** [MZ008005ZU Orderform Customized Switch.pdf](#)  
[MZ008006ZU Orderform Customized Switch.pdf](#)

**WIRING DIAGRAMS** [eaton-rotary-switches-t0-on-off-switch-wiring-diagram-023.eps](#)  
[eaton-rotary-switches-t0-on-off-switch-wiring-diagram-024.eps](#)

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

