

# DFLK-D25 SUB/S - Interface module

2280310

<https://www.phoenixcontact.com/us/products/2280310>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



The VARIOFACE feed-through module implements a 1:1 connection between screw connection terminal blocks and a D-SUB miniature pin strip (number of positions: 25). A separate ground pick-off is available.

## Your advantages

- 9-pos. ... 50-pos.
- 9- to 37-pos.: separate ground pick-off
- 50-pos.: no ground pick-off
- In accordance with IEC 60807-2
- 1:1 connection
- D-SUB 4-40 UNC thread
- Screw connection

## Commercial data

Item number	2280310
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	C422
Product key	CK2225
Catalog page	Page 556 (C-5-2019)
GTIN	4017918054427
Weight per piece (including packing)	84.27 g
Weight per piece (excluding packing)	0.91 g
Customs tariff number	85369010
Country of origin	DE

# DFLK-D25 SUB/S - Interface module



2280310

<https://www.phoenixcontact.com/us/products/2280310>

## Technical data

### Product properties

Product type	Interface module
Product family	VARIOFACE
Number of positions	25

### Insulation characteristics

Insulation	Functional insulation
------------	-----------------------

### Insulation characteristics: Air clearances and creepage distances

Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

### Electrical properties

Operating voltage (AC)	$\leq 30$ V AC
Operating voltage (DC)	$\leq 60$ V DC
Current (per branch)	$\leq 2.5$ A
Current (Total current)	$\leq 50$ A (50 °C)

### Air clearances and creepage distances

Rated insulation voltage	125 V
Rated surge voltage	1.2 kV (1.2/50 $\mu$ s)

### Connection data

#### Connection 1 (control level)

Connection in acc. with standard	IEC 60807-2
Connection method	D-SUB pin strip
Screw thread	UNC 4-40
Number of connections	1
Number of positions	25
Insertion/withdrawal cycles	> 500
Pitch	2.77 mm

#### Connection 2 (field level)

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Number of positions	26
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

### Signaling

# DFLK-D25 SUB/S - Interface module



2280310

<https://www.phoenixcontact.com/us/products/2280310>

Status display present	No
------------------------	----

## Dimensions

### Item dimensions

Width	39.88 mm
Height	83.4 mm
Depth	33 mm

## Material specifications

Color	gray (RAL 7042)
Housing insulation material	Polyamide PA non-reinforced

## Environmental and real-life conditions

### Ambient conditions

Degree of protection (Module)	IP20
Degree of protection (Installation location)	≥ IP54
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Altitude	≤ 2000 m

## Approvals

### UKCA

Certificate	UKCA-compliant
-------------	----------------

## Standards and regulations

### Air clearances and creepage distances

Standards/regulations	EN IEC 60664-1
-----------------------	----------------

## Mounting

Mounting type	Rear mounting
Mounting position	any

## Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

# DFLK-D25 SUB/S - Interface module

2280310

<https://www.phoenixcontact.com/us/products/2280310>



Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)