


Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with spring-cage connection and D-Subminiature socket strip, for mounting on NS 35/7.5, 15-pos.

Your advantages

- 9-pos. ... 50-pos.
- Spring-cage connection technology
- In accordance with IEC 60807-2
- 1:1 connection

Commercial data

|                                      |                    |
|--------------------------------------|--------------------|
| Item number                          | 2293679            |
| Packing unit                         | 1 pc               |
| Minimum order quantity               | 1 pc               |
| Sales key                            | C422               |
| Product key                          | CK2223             |
| Catalog page                         | Page 308 (IF-2011) |
| GTIN                                 | 4017918120573      |
| Weight per piece (including packing) | 87.7 g             |
| Weight per piece (excluding packing) | 58.84 g            |
| Customs tariff number                | 85369010           |
| Country of origin                    | DE                 |

# UM 45-D15SUB/B/ZFKDS - Interface module



2293679

<https://www.phoenixcontact.com/us/products/2293679>

## Technical data

### Product properties

|                     |                  |
|---------------------|------------------|
| Product type        | Interface module |
| Number of positions | 15               |

### Insulation characteristics

|            |                       |
|------------|-----------------------|
| Insulation | Functional insulation |
|------------|-----------------------|

### Insulation characteristics: Air clearances and creepage distances

|                      |                       |
|----------------------|-----------------------|
| Insulation           | Functional insulation |
| Overvoltage category | II                    |
| Pollution degree     | 2                     |

### Electrical properties

|                         |                        |
|-------------------------|------------------------|
| Operating voltage (AC)  | $\leq 30 \text{ V AC}$ |
| Operating voltage (DC)  | $\leq 60 \text{ V DC}$ |
| Current (per branch)    | $\leq 2.5 \text{ A}$   |
| Current (Total current) | $\leq 37.5 \text{ A}$  |

### Air clearances and creepage distances

|                          |                                |
|--------------------------|--------------------------------|
| Rated insulation voltage | 125 V                          |
| Rated surge voltage      | 1.2 kV (1.2/50 $\mu\text{s}$ ) |

### Connection data

#### Connection 1 (control level)

|                                  |                    |
|----------------------------------|--------------------|
| Connection in acc. with standard | IEC 60807-2        |
| Connection method                | D-SUB socket strip |
| Screw thread                     | UNC 4-40           |
| Number of connections            | 1                  |
| Number of positions              | 15                 |
| Insertion/withdrawal cycles      | > 500              |
| Pitch                            | 2.74 mm            |

#### Connection 2 (field level)

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| Connection method                | Spring-cage connection                      |
| Stripping length                 | 8 mm                                        |
| Number of positions              | 16                                          |
| Conductor cross section rigid    | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross section flexible | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Conductor cross section AWG      | 24 ... 14                                   |

### Signaling

|                        |    |
|------------------------|----|
| Status display present | No |
|------------------------|----|

# UM 45-D15SUB/B/ZFKDS - Interface module



2293679

<https://www.phoenixcontact.com/us/products/2293679>

## Dimensions

### Item dimensions

|        |          |
|--------|----------|
| Width  | 64 mm    |
| Height | 45 mm    |
| Depth  | 49.56 mm |

## Material specifications

|                             |                  |
|-----------------------------|------------------|
| Color                       | green (RAL 6021) |
| Housing insulation material | PVC              |

## Environmental and real-life conditions

### Ambient conditions

|                                              |                  |
|----------------------------------------------|------------------|
| Degree of protection (Module)                | IP20             |
| Degree of protection (Installation location) | ≥ IP54           |
| Ambient temperature (operation)              | -20 °C ... 50 °C |
| Ambient temperature (storage/transport)      | -20 °C ... 70 °C |
| Altitude                                     | ≤ 2000 m         |

## Approvals

### UKCA

|             |                |
|-------------|----------------|
| Certificate | UKCA-compliant |
|-------------|----------------|

## Standards and regulations

### Air clearances and creepage distances

|                       |                |
|-----------------------|----------------|
| Standards/regulations | EN IEC 60664-1 |
|-----------------------|----------------|

## Mounting

|                   |                   |
|-------------------|-------------------|
| Mounting type     | DIN rail mounting |
| Mounting position | any               |

## Notes

|         |                                                                                                                                                                                                                                                                                |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General | For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met. |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

# UM 45-D15SUB/B/ZFKDS - Interface module


2293679

<https://www.phoenixcontact.com/us/products/2293679>



## Drawings

Circuit diagram



# UM 45-D15SUB/B/ZFKDS - Interface module



2293679

<https://www.phoenixcontact.com/us/products/2293679>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141152 |
| ECLASS-13.0 | 27141152 |
| ECLASS-12.0 | 27141152 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC002780 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UM 45-D15SUB/B/ZFKDS - Interface module



2293679

<https://www.phoenixcontact.com/us/products/2293679>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)