

FLKM 50-PA-AB/1756 - Front adapter

2296427

<https://www.phoenixcontact.com/us/products/2296427>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE front adapters, for ControlLogix, max. 1 x 32 channels can be connected, number of positions 50.

The front adapters **cannot** be pushed into a hood!

Commercial data

Item number	2296427
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C421
Product key	CK2111
Catalog page	Page 144 (IF-2002)
GTIN	4017918584368
Weight per piece (including packing)	67.3 g
Weight per piece (excluding packing)	39.3 g
Customs tariff number	85366990
Country of origin	DE

FLKM 50-PA-AB/1756 - Front adapter



2296427

<https://www.phoenixcontact.com/us/products/2296427>

Technical data

Product properties

Product type	Front adapter
--------------	---------------

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Operating voltage (AC)	≤ 25 V AC
Operating voltage (DC)	≤ 60 V DC
Current (Per path)	≤ 1 A
Current (per connection)	≤ 8 A (Feed-in via separate power supply)

Supported controller ALLEN-BRADLEY ControlLogix

Suitable I/O card	1756-IA16I
	1756-IB16D
	1756-IB16I
	1756-IH16I
	1756-OB32
	1756-IF8
	1756-IF16
	1756-HSC
1756-M02AE	

Supported controller HONEYWELL Experion PKS C200

Suitable I/O card	TC-IDJ 161
	TC-IDX 161
	TC-IDK 161
	TC-ODD 321
	TC-IAH 161

Connection data

Field level

Connection method	IDC/FLK pin strip
Number of connections	1
Number of positions	50
Pitch	2.54 mm

Supply

Connection method	Screw connection
Conductor cross section rigid	0.14 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	26 ... 16

FLKM 50-PA-AB/1756 - Front adapter



2296427

<https://www.phoenixcontact.com/us/products/2296427>

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	IEC 60664
	IEC 60664A
	DIN VDE 0110
	DIN VDE 0160 (in parts)

Mounting

Mounting position	any
-------------------	-----

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

FLKM 50-PA-AB/1756 - Front adapter




2296427

<https://www.phoenixcontact.com/us/products/2296427>

Drawings

Circuit diagram



FLKM 50-PA-AB/1756 - Front adapter



2296427

<https://www.phoenixcontact.com/us/products/2296427>

Classifications

ECLASS

ECLASS-11.0	27242292
ECLASS-13.0	27242292

FLKM 50-PA-AB/1756 - Front adapter



2296427

<https://www.phoenixcontact.com/us/products/2296427>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com