

FLK 16/EZ-DR/ 300/KONFEK - Cable



2299330

<https://www.phoenixcontact.com/us/products/2299330>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Round cable set; connection 1: IDC/FLK socket strip (1x 16-position); connection 2: IDC/FLK socket strip (1x 16-position); cable length: 3 m

Your advantages

- Unshielded

Commercial data

Item number	2299330
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C421
Product key	CK2131
Catalog page	Page 566 (C-5-2019)
GTIN	4017918886059
Weight per piece (including packing)	205.2 g
Weight per piece (excluding packing)	186.1 g
Customs tariff number	85444290
Country of origin	DE

FLK 16/EZ-DR/ 300/KONFEK - Cable



2299330

<https://www.phoenixcontact.com/us/products/2299330>

Technical data

Product properties

Product type	System cable
--------------	--------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP00
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation) -10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

Electrical properties

Operating voltage (AC)	≤ 30 V AC
Operating voltage (DC)	≤ 60 V DC
Nominal operating mode	100% operating factor
Current (Per path, 50°C)	≤ 1 A (Uncoiled, see derating)
Current (Per path, 70°C)	≤ 0.6 A (Uncoiled, see derating)

Supported controller EMERSON DeltaV

Suitable I/O card	VE4001S2T2B3
	VE4001S2T2B3 Series 2
	VE4001S2T1B3
	VE4002S1T1B3
	VE4002S1T2B3
	VE4002S1T2B3 Series 2
	VE4003S2B4
	VE4005S2B3

Cable/line

Cable length	3 m
--------------	-----

16X0.14 [PVC]

Number of positions	16
Shielded	no
Cable type	16X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	16x 0.14 mm ²
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	6.80 mm ±0.4 mm

FLK 16/EZ-DR/ 300/KONFEK - Cable



2299330

<https://www.phoenixcontact.com/us/products/2299330>

Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	$\leq 145 \Omega/\text{km}$ (20 °C)
Insulation resistance	$\geq 20 \text{ M}\Omega \cdot \text{km}$ (20 °C)
Smallest bending radius, fixed installation	58 mm
Smallest bending radius, movable installation	108 mm
Max. bending cycles	5000 (at a radius of $\geq 15 \times$ outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
IDC/FLK16 (1)	IDC/FLK16 (1) = black
IDC/FLK16 (2)	IDC/FLK16 (2) = brown
IDC/FLK16 (3)	IDC/FLK16 (3) = red
IDC/FLK16 (4)	IDC/FLK16 (4) = orange
IDC/FLK16 (5)	IDC/FLK16 (5) = yellow
IDC/FLK16 (6)	IDC/FLK16 (6) = green
IDC/FLK16 (7)	IDC/FLK16 (7) = blue
IDC/FLK16 (8)	IDC/FLK16 (8) = violet
IDC/FLK16 (9)	IDC/FLK16 (9) = gray
IDC/FLK16 (10)	IDC/FLK16 (10) = white
IDC/FLK16 (11)	IDC/FLK16 (11) = white-black
IDC/FLK16 (12)	IDC/FLK16 (12) = white-brown
IDC/FLK16 (13)	IDC/FLK16 (13) = white-red
IDC/FLK16 (14)	IDC/FLK16 (14) = white-orange
IDC/FLK16 (15)	IDC/FLK16 (15) = white-yellow
IDC/FLK16 (16)	IDC/FLK16 (16) = white-green

Connection data

Connection 1

Connection in acc. with standard	based on IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	16
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Connection 2

Connection in acc. with standard	based on IEC 60603-13
Connection method	IDC/FLK socket strip

FLK 16/EZ-DR/ 300/KONFEK - Cable



2299330

<https://www.phoenixcontact.com/us/products/2299330>

Number of connections	1
Number of positions	16
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

Drawings

Diagram



Maximum permissible current per path in uncoiled state

FLK 16/EZ-DR/ 300/KONFEK - Cable



2299330

<https://www.phoenixcontact.com/us/products/2299330>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2299330>



EAC

Approval ID: RU*-DE.HB*35.B00385



UL Listed

Approval ID: FILE E 238705

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	125 V	1 A	-	-



cUL Listed

Approval ID: FILE E 238705

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	125 V	1 A	-	-

cULus Listed

FLK 16/EZ-DR/ 300/KONFEK - Cable



2299330

<https://www.phoenixcontact.com/us/products/2299330>

Classifications

ECLASS

ECLASS-11.0	27242220
ECLASS-12.0	27242220
ECLASS-13.0	27242220

ETIM

ETIM 9.0	EC000237
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

FLK 16/EZ-DR/ 300/KONFEK - Cable



2299330

<https://www.phoenixcontact.com/us/products/2299330>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com