



Figure similar

Reversing motor starter, Size 00, Three phase full voltage, Solid-state overload relay, OLRelay amp range 0.25-1a, 208VAC 60HZ coil, Non-combination type, Enclosure type (open), No enclosure

|   |                                      |
|---|--------------------------------------|
| product brand name  | Class 22                             |
| design of the product   | Full-voltage reversing motor starter |
| special product feature   | ESP200 overload relay                |
| <b>General technical data</b>   |                                      |
| weight [lb]   | 6 lb                                 |
| Height x Width x Depth [in]   | 7.69 × 10.5 × 3.92 in                |
| touch protection against electrical shock                               | Not finger-safe                      |
| installation altitude [ft] at height above sea level maximum            | 6560 ft                              |
| ambient temperature [°F]  |                                      |
| • during storage  | -22 ... +149 °F                      |
| • during operation  | -4 ... +104 °F                       |
| ambient temperature   |                                      |
| • during storage  | -30 ... +65 °C                       |
| • during operation  | -20 ... +40 °C                       |
| country of origin   | Mexico                               |
| <b>Horsepower ratings</b>   |                                      |
| yielded mechanical performance [hp] for 3-phase AC motor                |                                      |
| • at 200/208 V rated value  | 0.17 hp                              |
| • at 220/230 V rated value  | 0.17 hp                              |
| • at 460/480 V rated value  | 0.33 hp                              |
| • at 575/600 V rated value  | 0.5 hp                               |
| <b>Contactor</b>  |                                      |
| size of contactor   | NEMA controller size 00              |
| number of NO contacts for main contacts                                 | 3                                    |
| operating voltage for main current circuit at AC at 60 Hz maximum       | 600 V                                |
| operational current at AC at 600 V rated value                          | 9 A                                  |
| mechanical service life (operating cycles) of the main contacts typical | 10000000                             |
| <b>Auxiliary contact</b>  |                                      |
| number of NC contacts at contactor for auxiliary contacts               | 0                                    |
| number of NO contacts at contactor for auxiliary contacts               | 1                                    |
| number of total auxiliary contacts maximum                              | 8                                    |
| contact rating of auxiliary contacts of contactor according to UL       | 10A@600VAC (A600), 5A@600VDC (P600)  |
| <b>Coil</b>   |                                      |
| type of voltage of the control supply voltage                           | AC                                   |
| control supply voltage  |                                      |
| • at AC at 60 Hz rated value  | 208 V                                |
| holding power at AC minimum   | 8.6 W                                |
| apparent pick-up power of magnet coil at AC                             | 218 VA                               |

|  |              |
|--|--------------|
| apparent holding power of magnet coil at AC                              | 25 VA        |
| operating range factor control supply voltage rated value of magnet coil | 0.85 ... 1.1 |
| percentual drop-out voltage of magnet coil related to the input voltage  | 50 %         |
| ON-delay time  | 19 ... 29 ms |
| OFF-delay time   | 10 ... 24 ms |

#### Overload relay

|   |                                      |
|---|--------------------------------------|
| product function  |                                      |
| • overload protection   | Yes                                  |
| • phase failure detection   | Yes                                  |
| • asymmetry detection   | Yes                                  |
| • ground fault detection  | Yes                                  |
| • test function   | Yes                                  |
| • external reset  | No                                   |
| reset function  | Manual, automatic and remote         |
| trip class  | CLASS 5 / 10 / 20 (factory set) / 30 |
| adjustable current response value current of the current-dependent overload release | 0.25 ... 1 A                         |
| make time with automatic start after power failure maximum                          | 3 s                                  |
| relative repeat accuracy  | 1 %                                  |
| product feature protective coating on printed-circuit board                         | Yes                                  |
| number of NC contacts of auxiliary contacts of overload relay                       | 1                                    |
| number of NO contacts of auxiliary contacts of overload relay                       | 1                                    |
| operational current of auxiliary contacts of overload relay                         |                                      |
| • at AC at 600 V  | 5 A                                  |
| • at DC at 250 V  | 1 A                                  |
| contact rating of auxiliary contacts of overload relay according to UL              | 5A@600VAC (B600), 1A@250VDC (R300)   |
| insulation voltage (Ui)   |                                      |
| • with single-phase operation at AC rated value                                     | 600 V                                |
| • with multi-phase operation at AC rated value                                      | 300 V                                |

#### Enclosure

|                                  |                            |
|----------------------------------|----------------------------|
| degree of protection NEMA rating | Open device (no enclosure) |
| design of the housing            | NA                         |

#### Mounting/wiring

|   |   |
|---|---|
| mounting position   | Vertical  |
| fastening method  | Surface mounting and installation                   |
| type of electrical connection for supply voltage line-side  | Screw-type terminals                                |
| tightening torque [lbf-in] for supply   | 20 ... 20 lbf-in                                    |
| type of connectable conductor cross-sections at line-side at AWG cables single or multi-stranded                        | 1x (14 ... 2 AWG)                                   |
| temperature of the conductor for supply maximum permissible   | 75 °C   |
| material of the conductor for supply  | AL or CU  |
| type of electrical connection for load-side outgoing feeder   | Screw-type terminals                                |
| tightening torque [lbf-in] for load-side outgoing feeder  | 20 ... 24 lbf-in                                    |
| type of connectable conductor cross-sections at AWG cables for load-side outgoing feeder single or multi-stranded       | 2x (14 ... 10 AWG)                                  |
| temperature of the conductor for load-side outgoing feeder maximum permissible  | 75 °C   |
| material of the conductor for load-side outgoing feeder   | CU  |
| type of electrical connection of magnet coil  | Screw-type terminals                                |
| tightening torque [lbf-in] at magnet coil   | 5 ... 12 lbf-in                                     |
| type of connectable conductor cross-sections of magnet coil at AWG cables single or multi-stranded                      | 2x (16 ... 12 AWG)                                  |
| temperature of the conductor at magnet coil maximum permissible   | 75 °C   |
| material of the conductor at magnet coil  | CU  |
| type of electrical connection for auxiliary contacts  | Screw-type terminals                                |
| tightening torque [lbf-in] at contactor for auxiliary contacts  | 10 ... 15 lbf-in                                    |
| type of connectable conductor cross-sections at contactor at AWG cables for auxiliary contacts single or multi-stranded | 1x (12 AWG), 2x (16 ... 14 AWG), 2x (18 ... 16 AWG) |
| temperature of the conductor at contactor for auxiliary contacts maximum permissible                                    | 75 °C   |

|  |                      |
|--|----------------------|
| material of the conductor at contactor for auxiliary contacts  | CU                   |
| type of electrical connection at overload relay for auxiliary contacts   | Screw-type terminals |
| tightening torque [lbf-in] at overload relay for auxiliary contacts  | 7 ... 10 lbf-in      |
| type of connectable conductor cross-sections at overload relay at AWG cables for auxiliary contacts single or multi-stranded | 2x (20 ... 14 AWG)   |
| temperature of the conductor at overload relay for auxiliary contacts maximum permissible                                    | 75 °C                |
| material of the conductor at overload relay for auxiliary contacts   | CU                   |

#### Short-circuit current rating

|  |   |
|--|---|
| design of the fuse link for short-circuit protection of the main circuit required  | 10kA@600V (Class H or K); 100kA@600V (Class R or J) |
| design of the short-circuit trip   | Thermal magnetic circuit breaker                    |
| maximum short-circuit current breaking capacity (Icu) <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 480 V</li> <li>• at 600 V</li> </ul> | 14 kA<br>10 kA<br>10 kA                             |
| certificate of suitability   | NEMA ICS 2; UL 508; CSA 22.2, No.14                 |

#### Further information

**Industrial Controls - Product Overview (Catalogs, Brochures,...)**

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:22BUA32AD>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**


<https://support.industry.siemens.com/cs/US/en/ps/US2:22BUA32AD>



**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:22BUA32AD&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:22BUA32AD&lang=en)

**Certificates/approvals**

<https://support.industry.siemens.com/cs/US/en/ps/US2:22BUA32AD/certificate>





D46590003

**last modified:**

11/29/2021 