

Figure similar

Reversing motor starter Size 4 Three phase full voltage Solid-state overload relay  
OLRelay amp range 50-200A 220-240/440-480VAC 60HZ coil Non-combination  
type Enclosure type (open)

|   |                                      |
|---|--------------------------------------|
| product brand name  | Class 22                             |
| design of the product   | Full-voltage reversing motor starter |
| special product feature   | ESP200 overload relay                |
| <b>General technical data</b>   |                                      |
| weight [lb]   | 19 lb                                |
| Height x Width x Depth [in]   | 11.91 × 12.75 × 6.22 in              |
| touch protection against electrical shock                               | Not finger-safe                      |
| installation altitude [ft] at height above sea level maximum            | 6560 ft                              |
| ambient temperature [°F]  |                                      |
| • during storage  | -22 ... +149 °F                      |
| • during operation  | -4 ... +104 °F                       |
| ambient temperature   |                                      |
| • during storage  | -30 ... +65 °C                       |
| • during operation  | -20 ... +40 °C                       |
| country of origin   | USA                                  |
| <b>Horsepower ratings</b>   |                                      |
| yielded mechanical performance [hp] for 3-phase AC motor                |                                      |
| • at 200/208 V rated value  | 40 hp                                |
| • at 220/230 V rated value  | 50 hp                                |
| • at 460/480 V rated value  | 100 hp                               |
| • at 575/600 V rated value  | 100 hp                               |
| <b>Contactors</b>   |                                      |
| size of contactor   | NEMA controller size 4               |
| number of NO contacts for main contacts                                 | 3                                    |
| operating voltage for main current circuit at AC at 60 Hz maximum       | 600 V                                |
| operational current at AC at 600 V rated value                          | 135 A                                |
| mechanical service life (operating cycles) of the main contacts typical | 5000000                              |
| <b>Auxiliary contact</b>  |                                      |
| number of NC contacts at contactor for auxiliary contacts               | 0                                    |
| number of NO contacts at contactor for auxiliary contacts               | 1                                    |
| number of total auxiliary contacts maximum                              | 7                                    |
| contact rating of auxiliary contacts of contactor according to UL       | 10A@600VAC (A600), 5A@600VDC (P600)  |
| <b>Coil</b>   |                                      |
| type of voltage of the control supply voltage                           | AC                                   |
| control supply voltage  |                                      |
| • at AC at 60 Hz rated value  | 220 ... 480 V                        |
| holding power at AC minimum   | 22 W                                 |
| apparent pick-up power of magnet coil at AC                             | 510 VA                               |

|  |              |
|--|--------------|
| apparent holding power of magnet coil at AC                              | 51 VA        |
| operating range factor control supply voltage rated value of magnet coil | 0.85 ... 1.1 |
| percentual drop-out voltage of magnet coil related to the input voltage  | 50 %         |
| ON-delay time  | 18 ... 34 ms |
| OFF-delay time   | 10 ... 12 ms |

### Overload relay

|  |                                       |
|--|---------------------------------------|
| product function   |                                       |
| <ul style="list-style-type: none"> <li>• overload protection</li> <li>• phase failure detection</li> <li>• asymmetry detection</li> <li>• ground fault detection</li> <li>• test function</li> <li>• external reset</li> </ul> | Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>No |
| reset function   | Manual, automatic and remote          |
| trip class   | CLASS 5 / 10 / 20 (factory set) / 30  |
| adjustable current response value current of the current-dependent overload release  | 50 ... 200 A                          |
| make time with automatic start after power failure maximum   | 3 s                                   |
| relative repeat accuracy   | 1 %                                   |
| product feature protective coating on printed-circuit board  | Yes                                   |
| number of NC contacts of auxiliary contacts of overload relay  | 1                                     |
| number of NO contacts of auxiliary contacts of overload relay  | 1                                     |
| operational current of auxiliary contacts of overload relay  |                                       |
| <ul style="list-style-type: none"> <li>• at AC at 600 V</li> <li>• at DC at 250 V</li> </ul>   | 5 A<br>1 A                            |
| contact rating of auxiliary contacts of overload relay according to UL   | 5A@600VAC (B600), 1A@250VDC (R300)    |
| insulation voltage (Ui)  |                                       |
| <ul style="list-style-type: none"> <li>• with single-phase operation at AC rated value</li> <li>• with multi-phase operation at AC rated value</li> </ul>  | 600 V<br>300 V                        |

### Enclosure

|                                  |                            |
|----------------------------------|----------------------------|
| degree of protection NEMA rating | Open device (no enclosure) |
| design of the housing            | NA                         |

### Mounting/wiring

|   |   |
|---|---|
| mounting position   | Vertical  |
| fastening method  | Surface mounting and installation                   |
| type of electrical connection for supply voltage line-side  | Box lug   |
| tightening torque [lbf-in] for supply   | 200 ... 200 lbf-in                                  |
| type of connectable conductor cross-sections at line-side at AWG cables single or multi-stranded                        | 1x (6 AWG ... 250 MCM)                              |
| temperature of the conductor for supply maximum permissible   | 75 °C   |
| material of the conductor for supply  | CU  |
| type of electrical connection for load-side outgoing feeder   | Box lug   |
| tightening torque [lbf-in] for load-side outgoing feeder  | 200 ... 200 lbf-in                                  |
| type of connectable conductor cross-sections at AWG cables for load-side outgoing feeder single or multi-stranded       | 1x (6 AWG ... 250 MCM)                              |
| temperature of the conductor for load-side outgoing feeder maximum permissible  | 75 °C   |
| material of the conductor for load-side outgoing feeder   | CU  |
| type of electrical connection of magnet coil  | Screw-type terminals                                |
| tightening torque [lbf-in] at magnet coil   | 5 ... 12 lbf-in                                     |
| type of connectable conductor cross-sections of magnet coil at AWG cables single or multi-stranded                      | 2x (16 ... 12 AWG)                                  |
| temperature of the conductor at magnet coil maximum permissible   | 75 °C   |
| material of the conductor at magnet coil  | CU  |
| type of electrical connection for auxiliary contacts  | Screw-type terminals                                |
| tightening torque [lbf-in] at contactor for auxiliary contacts  | 10 ... 15 lbf-in                                    |
| type of connectable conductor cross-sections at contactor at AWG cables for auxiliary contacts single or multi-stranded | 1x (12 AWG), 2x (16 ... 14 AWG), 2x (18 ... 16 AWG) |
| temperature of the conductor at contactor for auxiliary contacts maximum permissible                                    | 75 °C   |

|  |                      |
|--|----------------------|
| material of the conductor at contactor for auxiliary contacts  | CU                   |
| type of electrical connection at overload relay for auxiliary contacts   | Screw-type terminals |
| tightening torque [lbf-in] at overload relay for auxiliary contacts  | 7 ... 10 lbf-in      |
| type of connectable conductor cross-sections at overload relay at AWG cables for auxiliary contacts single or multi-stranded | 2x (20 ... 14 AWG)   |
| temperature of the conductor at overload relay for auxiliary contacts maximum permissible                                    | 75 °C                |
| material of the conductor at overload relay for auxiliary contacts   | CU                   |

#### Short-circuit current rating

|   |   |
|---|---|
| design of the fuse link for short-circuit protection of the main circuit required | 10kA@600V (Class H or K); 100kA@600V (Class R or J) |
| design of the short-circuit trip  | Thermal magnetic circuit breaker                    |
| maximum short-circuit current breaking capacity (I <sub>cu</sub> )                |   |
| • at 240 V  | 10 kA   |
| • at 480 V  | 10 kA   |
| • at 600 V  | 10 kA   |
| certificate of suitability  | NEMA ICS 2; UL 508; CSA 22.2, No.14                 |

#### Further information

Industrial Controls - Product Overview (Catalogs, Brochures,...)

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:22JUH32AC>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/US/en/ps/US2:22JUH32AC>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:22JUH32AC&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:22JUH32AC&lang=en)

Certificates/approvals

<https://support.industry.siemens.com/cs/US/en/ps/US2:22JUH32AC/certificate>





D46590003

last modified:

11/29/2021