

# Specifications

## Eaton 230256

Eaton Moeller® series DILEM Auxiliary contact module, 4 pole, 2 N/O, 2 NC, Front fixing, Spring-loaded terminals, DILE(E)M...-C

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series DILEM Accessory Auxiliary contact module
<b>CATALOG NUMBER</b>	230256
<b>MODEL CODE</b>	22DILEM-C
<b>EAN</b>	4015082302566
<b>PRODUCT LENGTH/DEPTH</b>	39 mm
<b>PRODUCT HEIGHT</b>	37 mm
<b>PRODUCT WIDTH</b>	45 mm
<b>PRODUCT WEIGHT</b>	0.042 kg
<b>CERTIFICATIONS</b>	UL Category Control No.: NKCR CSA-C22.2 No. 14-05 IEC/EN 60947-4-1 IEC/EN 60947 VDE 0660 UL CSA Class No.: 3211-03 CSA UL 508 CSA File No.: 012528 CE UL File No.: E29184
<b>GLOBAL CATALOG</b>	230256

## Product specifications

<b>FEATURES</b>	Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L)
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product

## Resources

<b>CATALOGS</b>	<a href="#">Product Range Catalog Switching and protecting motors</a>  <a href="#">eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf</a>  <a href="#">Switching and protecting motors - catalog</a>
<b>CHARACTERISTIC CURVE</b>	<a href="#">eaton-contactors-short-time-loading-dilm-characteristic-curve.eps</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00004764.pdf</a> <a href="#">DA-DC-00004747.pdf</a>
<b>DRAWINGS</b>	<a href="#">eaton-contactors-diler-dimensions-002.eps</a> <a href="#">eaton-contactors-module-dile-accessory-3d-drawing.eps</a>
<b>ECAD MODEL</b>	<a href="#">ETN.230256.edz</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">IL03407009Z</a>
<b>MCAD MODEL</b>	<a href="#">DA-CS-hs_dile_c</a> <a href="#">DA-CD-hs_dile_c</a>
<b>WIRING DIAGRAMS</b>	<a href="#">eaton-contactors-contact-dilm-accessory-wiring-diagram-010.eps</a>

	standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>ELECTRIC CONNECTION TYPE</b>	Spring clamp connection
<b>FITTED WITH:</b>	Interlocked opposing contacts
<b>OPERATING FREQUENCY</b>	9000 Operations/h
<b>POLLUTION DEGREE</b>	3
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	50 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	-25 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	80 °C
<b>AMBIENT STORAGE</b>	-40 °C

<b>TEMPERATURE - MIN</b>	
<b>CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)</b>	10 A
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0.24 W
<b>NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	2
<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	2
<b>NUMBER OF SWITCHES (FAULT SIGNAL)</b>	0
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	6000 V AC
<b>SCREWDRIVER SIZE</b>	0.6 x 3.5 mm, Spring-loaded terminals
<b>MOUNTING POSITION</b>	As required (except vertical with terminals A1/A2 at the bottom)
<b>CONNECTION TYPE</b>	Spring-loaded terminals
<b>MOUNTING METHOD</b>	Front fastening
<b>OVERVOLTAGE CATEGORY</b>	III
<b>CONTROL CIRCUIT RELIABILITY</b>	< 2 λ, < 1 failure at 100,000,000 Operations (at U <sub>e</sub> = 24 V DC, U <sub>min</sub> = 17 V, I <sub>min</sub> = 5.4 mA)
<b>DEGREE OF PROTECTION</b>	IP20
<b>MODEL</b>	Top mounting
<b>LAMP HOLDER</b>	None
<b>FUNCTIONS</b>	For standard applications
<b>SAFE ISOLATION</b>	300 V AC, Between auxiliary contacts, According to EN 61140 300 V AC, Between coil

	and auxiliary contacts, According to EN 61140
<b>RATED OPERATIONAL CURRENT (IE)</b>	2.5 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series) 2.5 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series) 0.5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series) 1.5 A at 110 V, DC L/R ≤ 15 ms (with 3 contacts in series)
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)</b>	10 A, 600 V AC, (UL/CSA) 0.5 A, 250 V DC, (UL/CSA)
<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)</b>	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
<b>LIFESPAN, MECHANICAL</b>	10,000,000 Operations (AC operated) 20,000,000 Operations (DC operated) 150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A) 200,000 Operations (at 240 V, AC-15)
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>PROTECTION</b>	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
<b>NUMBER OF POLES</b>	Four-pole
<b>SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING</b>	6 A gG/gL, 500 V, Max. Fuse, Contacts
<b>SHORT-CIRCUIT PROTECTION RATING</b>	10 A fast, 500V, Maximum fuse, Short-circuit rating without welding, Contacts
<b>RATED INSULATION VOLTAGE (UI)</b>	690 V
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V</b>	4 A
<b>RATED OPERATIONAL</b>	2 A

<b>CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V</b>	
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V</b>	1.5 A
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	4 A
<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	600 V
<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	2 x (1 - 2.5) mm <sup>2</sup> 1 x (1 - 2.5) mm <sup>2</sup>
<b>TERMINAL CAPACITY (SOLID)</b>	1 x (1 - 2.5) mm <sup>2</sup> 2 x (1 - 2.5) mm <sup>2</sup>
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	Single 16 – 14, double 16 – 14
<b>SHOCK RESISTANCE</b>	8 g, N/C contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 10 g, N/O contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms

<b>PROJECT NAME:</b>
<b>PROJECT NUMBER:</b>
<b>PREPARED BY:</b>
<b>DATE:</b>



**Eaton Corporation plc**  
 Eaton House  
 30 Pembroke Road  
 Dublin 4, Ireland  
 Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

