

PSI-DATA/BASIC-MODEM/RS232 - Modem



2313067
<https://www.phoenixcontact.com/it/products/2313067>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Industrial analog modem for assembly on EN DIN rails. Worldwide access to industrial PCs, machines and systems. Serial RS-232 interface, 3-way electrical isolation, supply voltage 24 V DC.

Your advantages

- Configurable, selective call acceptance
- High-quality electrical isolation
- Connection establishment with password protection
- Integrated surge protection to ensure high system availability
- Callback function

Commercial data

Item number	2313067
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	DNC
Product key	DNC411
Catalog page	Page 411 (C-6-2019)
GTIN	4046356098823
Weight per piece (including packing)	228.1 g
Weight per piece (excluding packing)	117.8 g
Customs tariff number	85176200
Country of origin	DE

Technical data

Notes

Utilization restriction

CCCex note	Use in potentially explosive areas is not permitted in China.
------------	---

Product properties

Product type	Modem
MTTF	628 Years (SN 29500 standard, temperature 25°C, operating cycle 21%)
	290 Years (SN 29500 standard, temperature 40°C, operating cycle 34.25%)
	115 Years (SN 29500 standard, temperature 40°C, operating cycle 100%)

Electrical properties

Electrical isolation	VCC // PSTN // V.24 (RS-232)
Maximum power dissipation for nominal condition	2.4 W
Mains type	Fixed-line network
Test voltage data interface/power supply	1.5 kV _{rms} (50 Hz, 1 min.)
Test voltage data interfaces	1500 V

Supply

Supply voltage range	10 V DC ... 30 V DC (via pluggable COMBICON screw terminal block)
Nominal supply voltage	24 V DC ±5 % (as an alternative or redundant, via backplane bus contact and system current supply)
Typical current consumption	< 100 mA (24 V DC)
	< 40 mA

Connection data

Supply

Tightening torque	0.56 Nm ... 0.79 Nm
-------------------	---------------------

Interfaces

Signal	RS-232
--------	--------

Data: V.24 (RS-232) interface in acc. with ITU-T V.28, EIA/TIA-232, DIN 66259-1

Serial transmission speed	0.3; 1.2; 2.4; 4.8; 9.6; 19.2; 38.4; 57.6; 115.2 kbps
Connection method	D-SUB 9 plug
Transmission length	15 m
File format/coding	Serial asynchronous UART/NRZ, 7/8 data, 1/2 stop, 1 parity, 10/11-bit character length
Data flow control/protocols	Software handshake, Xon/Xoff or hardware handshake RTS/CTS

Data: PSTN-Port (a/b-Line)

Connection method	RJ12, 6-pos.
Dialing procedure	Multiple frequency/pulse dialing, configuration via software

Dimensions

Width	22.5 mm
Height	99 mm
Depth	114.5 mm

Material specifications

Material Housing	PA V0
------------------	-------

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C

Approvals

EAC	
Identification	EAC

Corrosive gas test	
Identification	ISA-S71.04-1985 G3 Harsh Group A

EMC data

Noise immunity	EN 61000-6-2:2005
Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
Noise emission	EN 55032

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

2313067

<https://www.phoenixcontact.com/it/products/2313067>

Classifications

ECLASS

ECLASS-11.0	19060590
-------------	----------

ETIM

ETIM 8.0	EC000740
----------	----------

UNSPSC

UNSPSC 21.0	43222600
-------------	----------

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact UAB
Svitrigailos str. 11B
03228 Vilnius
+370 5 2106321
balticinfo@phoenixcontact.com