

VIP-3/SC/FLK60/LED - Interface module



2322126

<https://www.phoenixcontact.com/pc/products/2322126>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with screw connection and flat-ribbon cable connector, for mounting on NS 35 rails, with pin strip and short and long locking latches for socket strips, 60-pos., with LED

Your advantages

- 10-pos. ... 64-pos.
- Metal foot
- In accordance with IEC 60603-13
- 1:1 connection
- Screw connection

Commercial data

Item number	2322126
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	CK2412
Catalog page	Page 567 (C-5-2017)
GTIN	4046356450850
Weight per piece (including packing)	280 g
Weight per piece (excluding packing)	280 g
Customs tariff number	85366990
Country of origin	US

VIP-3/SC/FLK60/LED - Interface module



2322126

<https://www.phoenixcontact.com/pc/products/2322126>

Technical data

Product properties

Product type	Interface module
Product family	VARIOFACE Professional
Number of positions	60

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Nominal voltage U_N	24 V DC
Max. current carrying capacity per branch	1 A

Connection data

Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Controller level

Connection method	IDC/FLK pin strip
Number of connections	1
Number of positions	60
Pitch	2.54 mm

Signaling

Status display	LED
Status display present	Yes

Dimensions

Item dimensions

Width	113.5 mm
Height	69 mm
Depth	62 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0

VIP-3/SC/FLK60/LED - Interface module



2322126

<https://www.phoenixcontact.com/pc/products/2322126>

Housing insulation material	Polyamide 6.6 green
-----------------------------	---------------------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	IEC 60664
	DIN EN 50178

Mounting


Mounting type	DIN rail mounting
Mounting position	any

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

Drawings

Circuit diagram



VIP-3/SC/FLK60/LED - Interface module



2322126

<https://www.phoenixcontact.com/pc/products/2322126>

Classifications

UNSPSC

UNSPSC 21.0	39121432
-------------	----------

VIP-3/SC/FLK60/LED - Interface module



2322126

<https://www.phoenixcontact.com/pc/products/2322126>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com