

VIP-3/SC/HD26SUB/M - Interface module



2322375

<https://www.phoenixcontact.com/us/products/2322375>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with screw connection and high density D-SUB miniature pin strip, for mounting on NS 35 rails, no. of pos.: 26, width: 79 mm

Your advantages

- Screw connection
- 1:1 connection

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 2322375 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | C423 |
| Product key | CK2451 |
| Catalog page | Page 558 (C-5-2019) |
| GTIN | 4046356451673 |
| Weight per piece (including packing) | 141.4 g |
| Weight per piece (excluding packing) | 138.2 g |
| Customs tariff number | 85366990 |
| Country of origin | US |

VIP-3/SC/HD26SUB/M - Interface module



2322375

<https://www.phoenixcontact.com/us/products/2322375>

Technical data

Product properties

| | |
|---------------------|------------------------|
| Product type | Interface module |
| Product family | VARIOFACE Professional |
| Number of positions | 26 |

Electrical properties

| | |
|---|---------|
| Nominal voltage U_N | 25 V AC |
| | 60 V DC |
| Max. current carrying capacity per branch | 1 A |

Connection data

Field level

| | |
|----------------------------------|---|
| Connection in acc. with standard | IEC / EN |
| Connection method | Screw connection |
| Stripping length | 8 mm |
| Screw thread | M3 |
| Number of positions | 26 |
| Conductor cross section rigid | 0.2 mm ² ... 4 mm ² |
| Conductor cross section flexible | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross section AWG | 24 ... 12 |
| Tightening torque | 0.5 Nm ... 0.6 Nm |

Controller level

| | |
|-----------------------|------------------------------|
| Connection method | High density D-SUB pin strip |
| Number of connections | 1 |
| Number of positions | 26 |

Signaling

| | |
|------------------------|----|
| Status display | No |
| Status display present | No |

Dimensions

Item dimensions

| | |
|--------|---------|
| Width | 52.3 mm |
| Height | 69 mm |
| Depth | 62 mm |

Material specifications

| | |
|--|-----------------------------|
| Color | gray (RAL 7042) |
| Flammability rating according to UL 94 | V0 |
| Housing insulation material | Polyamide PA non-reinforced |

VIP-3/SC/HD26SUB/M - Interface module



2322375

<https://www.phoenixcontact.com/us/products/2322375>

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

Standards and regulations

| | |
|-----------------------|----------|
| Standards/regulations | EN 50178 |
|-----------------------|----------|

Mounting

| | |
|-------------------|-------------------|
| Mounting type | DIN rail mounting |
| Mounting position | any |

Notes

| | |
|---------|--|
| General | For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met. |
|---------|--|

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com