

# VIP-3/SC/HD44SUB/M - Interface module



2322388

<https://www.phoenixcontact.com/us/products/2322388>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with screw connection and high density D-SUB miniature pin strip, for mounting on NS 35 rails, no. of pos.: 44, width: 135 mm

## Your advantages

- Screw connection
- 1:1 connection

## Commercial data

Item number	2322388
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C423
Product key	CK2451
Catalog page	Page 558 (C-5-2019)
GTIN	4046356451680
Weight per piece (including packing)	213.8 g
Weight per piece (excluding packing)	213.8 g
Customs tariff number	85366990
Country of origin	US

# VIP-3/SC/HD44SUB/M - Interface module



2322388

<https://www.phoenixcontact.com/us/products/2322388>

## Technical data

### Product properties

Product type	Interface module
Product family	VARIOFACE Professional
Number of positions	44

### Electrical properties

Nominal voltage $U_N$	25 V AC
	60 V DC
Max. current carrying capacity per branch	1 A

### Connection data

#### Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Number of positions	44
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12
Tightening torque	0.5 Nm ... 0.6 Nm

#### Controller level

Connection method	High density D-SUB pin strip
Number of connections	1
Number of positions	44

### Signaling

Status display	No
Status display present	No

### Dimensions

#### Item dimensions

Width	82.9 mm
Height	69 mm
Depth	62 mm

### Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0
Housing insulation material	Polyamide PA non-reinforced

# VIP-3/SC/HD44SUB/M - Interface module



2322388

<https://www.phoenixcontact.com/us/products/2322388>

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

## Standards and regulations

Standards/regulations	EN 50178
-----------------------	----------

## Mounting

Mounting type	DIN rail mounting
Mounting position	any

## Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)