

VIP-2/SC/HD15SUB/F - Interface module



2322401

<https://www.phoenixcontact.com/us/products/2322401>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with screw connection and high density D-Subminiature female connector, for mounting on NS 35, no. of pos.: 15, width: 44.9 mm

Your advantages

- Screw connection
- 1:1 connection

Commercial data

Item number	2322401
Packing unit	1 pc
Sales key	C423
Product key	CK2451
Catalog page	Page 558 (C-5-2019)
GTIN	4046356451703
Weight per piece (including packing)	105.6 g
Weight per piece (excluding packing)	105.6 g
Customs tariff number	85366990
Country of origin	US

VIP-2/SC/HD15SUB/F - Interface module



2322401

<https://www.phoenixcontact.com/us/products/2322401>

Technical data

Product properties

Product type	Interface module
Product family	VARIOFACE Professional
Number of positions	15

Electrical properties

Nominal voltage U_N	25 V AC
	60 V DC
Max. current carrying capacity per branch	1 A

Connection data

Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Number of positions	15
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12
Tightening torque	0.5 Nm ... 0.6 Nm

Controller level

Connection method	High-density D-SUB socket strip
Number of connections	1
Number of positions	15

Signaling

Status display	No
Status display present	No

Dimensions

Item dimensions

Width	44.9 mm
Height	65.5 mm
Depth	45.1 mm

Material specifications

Color	gray (RAL 7042)
Housing insulation material	Polyamide PA non-reinforced

VIP-2/SC/HD15SUB/F - Interface module



2322401

<https://www.phoenixcontact.com/us/products/2322401>

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	EN 50178
-----------------------	----------

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com