

# TP150STX/100130003 S00068 - Touch panel



2401526  
<https://www.phoenixcontact.com/be/products/2401526>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Touch panel with 38.1 cm / 15"-TFT display (analog resistive (polyester)), 1024 x 768 pixel(s) (XGA), 262144 colors, Arm® Cortex®-A8, 800 MHz, 2x USB Host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Windows® Embedded Compact 7 and user software: Movicon™. (bus system: without)

## Commercial data

Item number	2401526
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DRCABC
Product key	DRCABC
GTIN	4055626196800
Weight per piece (including packing)	3.000 g
Weight per piece (excluding packing)	4.749 g
Customs tariff number	84714100
Country of origin	DE

## Technical data

### Product properties

Product type	Operator panel
--------------	----------------

#### Computer data

Processor	Arm® Cortex®-A8, 800 MHz
Operating system	Windows® Embedded Compact 7
RAM	512 MB LPDDR SDRAM
Data storage system	NAND-Flash, 256 MB
Slots	1x SD

#### Display

Display type	38.1 cm / 15"-TFT
Screen resolution	1024 x 768 Pixel(s) (XGA)
Touch technology	analog resistive (polyester)
Display lighting type	LED
Brightness	480 cd/m² typical (adjustable)
MTBF	50000 h
Color spectrum	262144 colors
Reading angle left	80.00 °
Reading angle right	80.00 °
Reading angle top	65.00 °
Reading angle bottom	80.00 °

### Interfaces

Interfaces	2x USB Host 2.0
Network	1 x Ethernet (10/100 Mbps), RJ45
Bus system	without

### System properties

User software	Movicon™
---------------	----------

### Electrical properties

Service life of battery	5 years (typical)
-------------------------	-------------------

#### Supply

Power supply unit	24 V DC ±20 %
Typical current consumption	0.8 A

#### Real-time clock

Realtime clock	Yes (battery-backed)
----------------	----------------------

### Mounting

Mounting type	Front mounting
---------------	----------------

# TP150STX/100130003 S00068 - Touch panel



2401526

<https://www.phoenixcontact.com/be/products/2401526>

## Material specifications

Material front plate	Aluminum (natural anodized)
Housing material	Steel sheet, zinc-plated

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP65 (front), IP20 (back) NEMA 4X
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	20 % ... 85 % (non-condensing)
Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

## Dimensions

### External dimensions

Width / Height / Depth	400 mm / 329 mm / 5 mm (Dimensions of the front plate)
------------------------	--------------------------------------------------------

### Installation dimensions

Width / Height / Installation depth	372 mm / 301 mm / (Installation cutout)
Installation depth	55 mm,

# TP150STX/100130003 S00068 - Touch panel



2401526

<https://www.phoenixcontact.com/be/products/2401526>

## Classifications

### ECLASS

ECLASS-11.0	27330201
-------------	----------

### ETIM

ETIM 8.0	EC001412
----------	----------

### UNSPSC

UNSPSC 21.0	43211900
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(a), 6(a)-I, 6(b), 6(b)-II, 6(c), 7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-15
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)

# TP150STX/100130003 S00068 - Touch panel



2401526

<https://www.phoenixcontact.com/be/products/2401526>

## Accessories

### TOUCH PEN - Touch pen

2701379

<https://www.phoenixcontact.com/be/products/2701379>



Touch pen for analog-resistive HMI's, silver coated. Delivery includes self-adhesive pen holder.

---

### USB FLASH DRIVE - USB memory stick

2402809

<https://www.phoenixcontact.com/be/products/2402809>



USB memory stick, 8 GB

# TP150STX/100130003 S00068 - Touch panel



2401526

<https://www.phoenixcontact.com/be/products/2401526>

## SD FLASH 2GB - Program/configuration memory

2988162

<https://www.phoenixcontact.com/be/products/2988162>




Program and configuration memory, for extending the internal flash memory, pluggable, 2 GB.

---

## 15,0" DISPLAY PROTECTIVE FOIL - Protective foil

2701378

<https://www.phoenixcontact.com/be/products/2701378>



Protective film set comprising 10 pieces of film for a 15" display. Including a squeegee to apply film and instructions.

## TP150STX/100130003 S00068 - Touch panel

2401526

<https://www.phoenixcontact.com/be/products/2401526>



### HMI BATTERY - Battery/accumulator

2701383

<https://www.phoenixcontact.com/be/products/2701383>

Lithium battery



---

### HMI SCB MOUNTING KIT 8 - Mounting material

2701387

<https://www.phoenixcontact.com/be/products/2701387>



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.



# TP150STX/100130003 S00068 - Touch panel



2401526


<https://www.phoenixcontact.com/be/products/2401526>

## HMI WALL MOUNTING KIT - Mounting material

2701380

<https://www.phoenixcontact.com/be/products/2701380>


HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.



## MC 1,5/ 3-STF-3,5 BD:1-3 - PCB connector

1751312

<https://www.phoenixcontact.com/be/products/1751312>



PCB connector, nominal cross section: 1.5 mm<sup>2</sup>, color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Socket, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MC 1,5/...-STF, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT nv/sa  
Minervastraat 10-12  
1930 Zaventem-Keiberg II  
+32 (0)2/723 98 11  
[info@phoenixcontact.be](mailto:info@phoenixcontact.be)