

TP090STW/100130003 S00127 - Touch panel



2401619

<https://www.phoenixcontact.com/pc/products/2401619>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Touch panel with 22.9 cm / 9"-TFT display (analog resistive (polyester)), 800 x 480 pixel(s) (WVGA), 262144 colors, Arm® Cortex®-A8, 800 MHz, 2x USB Host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Windows® Embedded Compact 7 and user software: IniNet Browser. (bus system: without)

Commercial data

Item number	2401619
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DRCABD
GTIN	4055626291994
Weight per piece (including packing)	1,300 g
Weight per piece (excluding packing)	1,300 g
Customs tariff number	84714100
Country of origin	DE

Technical data

Product properties

Product type	Operator panel
--------------	----------------

Computer data

Processor	Arm® Cortex®-A8, 800 MHz
Operating system	Windows® Embedded Compact 7
RAM	512 MB LPDDR SDRAM
Data storage system	NAND-Flash, 256 MB
Slots	1x SD

Display

Display type	22.9 cm / 9"-TFT
Screen resolution	800 x 480 Pixel(s) (WVGA)
Touch technology	analog resistive (polyester)
Display lighting type	LED
Brightness	800 cd/m², typical (adjustable)
MTBF	70000 h
Color spectrum	262144 colors
Reading angle left	85.00 °
Reading angle right	85.00 °
Reading angle top	85.00 °
Reading angle bottom	85.00 °

Interfaces

Interfaces	2x USB Host 2.0
Network	1 x Ethernet (10/100 Mbps), RJ45
Bus system	without

System properties

User software	IniNet Browser
---------------	----------------

Electrical properties

Service life of battery	5 years (typical)
-------------------------	-------------------

Supply

Power supply unit	24 V DC ±20 %
Typical current consumption	0.6 A

Real-time clock

Realtime clock	Yes (battery-backed)
----------------	----------------------

Mounting

Mounting type	Front mounting
---------------	----------------

Material specifications

Material front plate	Aluminum (natural anodized)
Housing material	Steel sheet, zinc-plated

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 (front), IP20 (back) NEMA 4X
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Altitude	3000 m
Permissible humidity (operation)	20 % ... 85 %
Shock	15g, according to IEC 60068-2-27
Vibration (operation)	1g, according to EN 60068-2-6

Dimensions

External dimensions

Width / Height / Depth	260 mm / 172 mm / 5 mm (Dimensions of the front plate)
------------------------	--

Installation dimensions

Width / Height / Installation depth	252 mm / 164 mm / 54 mm (Mounting cutout, depth with bus if bus system present in the device)
-------------------------------------	---

Classifications

ECLASS

ECLASS-11.0	27330201
-------------	----------

UNSPSC

UNSPSC 21.0	43211904
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(a), 6(a)-I, 6(b), 6(b)-II, 6(c), 7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-15
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)

TP090STW/100130003 S00127 - Touch panel



2401619

<https://www.phoenixcontact.com/pc/products/2401619>

Accessories

TOUCH PEN - Touch pen

2701379

<https://www.phoenixcontact.com/pc/products/2701379>



Touch pen for analog-resistive HMI, silver coated. Delivery includes self-adhesive pen holder.

USB FLASH DRIVE - USB memory stick

2402809

<https://www.phoenixcontact.com/pc/products/2402809>



USB memory stick, 8 GB

TP090STW/100130003 S00127 - Touch panel



2401619

<https://www.phoenixcontact.com/pc/products/2401619>

SD FLASH 2GB - Program/configuration memory

2988162

<https://www.phoenixcontact.com/pc/products/2988162>




Program and configuration memory, for extending the internal flash memory, pluggable, 2 GB.

9" DISPLAY PROTECTIVE FOIL - Protective foil

2701375

<https://www.phoenixcontact.com/pc/products/2701375>



Protective film set comprising 10 pieces of film for a 9" display. Including a squeegee to apply film and instructions.

TP090STW/100130003 S00127 - Touch panel

2401619

<https://www.phoenixcontact.com/pc/products/2401619>



HMI BATTERY - Battery/accumulator

2701383

<https://www.phoenixcontact.com/pc/products/2701383>

Lithium battery



HMI SCB MOUNTING KIT 4 - Mounting material

2701384

<https://www.phoenixcontact.com/pc/products/2701384>



HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.

TP090STW/100130003 S00127 - Touch panel



2401619

<https://www.phoenixcontact.com/pc/products/2401619>

HMI SCB MOUNTING KIT 6 - Mounting material

2701385

<https://www.phoenixcontact.com/pc/products/2701385>



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

HMI SCB MOUNTING KIT 8 - Mounting material

2701387

<https://www.phoenixcontact.com/pc/products/2701387>



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.

TP090STW/100130003 S00127 - Touch panel



2401619


<https://www.phoenixcontact.com/pc/products/2401619>

HMI WALL MOUNTING KIT - Mounting material

2701380

<https://www.phoenixcontact.com/pc/products/2701380>

HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.



MC 1,5/ 3-STF-3,5 BD:1-3 - PCB connector

1751312

<https://www.phoenixcontact.com/pc/products/1751312>



PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Socket, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MC 1,5/...-STF, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com