

# Specifications



## Eaton 262041

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=280x200x160mm for T5-4, NA type

### General Specifications

|                             |  |
|-----------------------------|--|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series CI-K Insulated enclosure |
| <b>CATALOG NUMBER</b>       | 262041   |
| <b>PRODUCT LENGTH/DEPTH</b> | 160 mm   |
| <b>PRODUCT HEIGHT</b>       | 280 mm   |
| <b>PRODUCT WIDTH</b>        | 200 mm   |
| <b>PRODUCT WEIGHT</b>       | 1.2 kg   |
| <b>COMPLIANCES</b>          | CE   |
| <b>CATALOG NOTES</b>        | 1 contact unit = 2 contacts                    |
| <b>EAN</b>                  | 4015082620417                                  |
| <b>MODEL CODE</b>           | CI-K5-T5-4-NA                                  |

## Product specifications

|   |  |
|---|--|
| <b>USED WITH</b>  | 3 - 4 contact units and with an additional PE clamp  |
| <b>TYPE</b>   | Insulated enclosure  |
| <b>10.10 TEMPERATURE RISE</b>   | Not applicable.  |
| <b>10.11 SHORT-CIRCUIT RATING</b>   | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| <b>10.13 MECHANICAL FUNCTION</b>  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| <b>10.2.2 CORROSION RESISTANCE</b>  | Meets the product standard's requirements.   |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.   |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.   |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.   |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.   |
| <b>10.2.5 LIFTING</b>   | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| <b>10.2.6 MECHANICAL IMPACT</b>   | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| <b>10.2.7 INSCRIPTIONS</b>  | Meets the product standard's requirements.   |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| <b>10.4 CLEARANCES AND</b>  | Meets the product  |

## Resources

|                                  |  |
|----------------------------------|--|
| <b>BROCHURES</b>                 | <a href="#">Brochure - CI-K small enclosures</a> |
| <b>ECAD MODEL</b>                | <a href="#">DA-CE-ETN.CI-K5-T5-4-NA</a>          |
| <b>INSTALLATION INSTRUCTIONS</b> | <a href="#">IL03801009Z</a>                      |

|  |  |
|--|--|
| <b>CREEPAGE DISTANCES</b>  | standard's requirements.   |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                        | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>        | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>             | Is the panel builder's responsibility.                             |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                              | Is the panel builder's responsibility.                             |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>      | Is the panel builder's responsibility.                             |
| <b>ENCLOSURE MATERIAL</b>  | Plastic  |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>            | 0 W  |
| <b>HEAT DISSIPATION CAPACITY PDISS</b>                               | 0 W  |
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>             | 0 W  |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 0 A  |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>            | 0 W  |
| <b>DEGREE OF PROTECTION</b>  | IP65<br>NEMA 12  |
| <b>MODEL</b>   | Surface mounting   |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

