

# Specifications



Photo is representative

## Eaton 265927

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 4p, 1250A, H4-4-AE1250

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series NZM molded case circuit breaker electronic
<b>CATALOG NUMBER</b>	265927
<b>MODEL CODE</b>	NZMH4-4-AE1250
<b>EAN</b>	4015082659271
<b>PRODUCT LENGTH/DEPTH</b>	401 mm
<b>PRODUCT HEIGHT</b>	207 mm
<b>PRODUCT WIDTH</b>	280 mm
<b>PRODUCT WEIGHT</b>	27 kg
<b>COMPLIANCES</b>	RoHS conform
<b>CERTIFICATIONS</b>	IEC/EN 60947 IEC
<b>GLOBAL CATALOG</b>	265927

## Product specifications

<b>AMPERAGE RATING</b>	1250 A
<b>VOLTAGE RATING</b>	690 V - 690 V
<b>CIRCUIT BREAKER FRAME TYPE</b>	NZM4
<b>FEATURES</b>	Motor drive optional Protection unit
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.

## Resources

<b>BROCHURES</b>	<a href="#">eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf</a>
<b>CATALOGS</b>	<a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a>
<b>CHARACTERISTIC CURVE</b>	<a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-047.eps</a>
<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250294en.pdf</a>
<b>DRAWINGS</b>	<a href="#">eaton-circuit-breaker-nzm-mccb-dimensions-023.eps</a>
<b>ECAD MODEL</b>	<a href="#">ETN.265927.edz</a>
<b>INSTALLATION INSTRUCTIONS</b>	<a href="#">eaton-circuit-breaker-basic-unit-nzmn4-il01210010z.pdf</a>
<b>INSTALLATION VIDEOS</b>	<a href="#">Introduction of the new digital circuit breaker NZM</a> <a href="#">The new digital NZM Range</a>
<b>MCAD MODEL</b>	<a href="#">DA-CD-nzm4_4p</a> <a href="#">DA-CS-nzm4_4p</a>
<b>PEP ECO-PASSPORT</b>	<a href="#">eaton-molded-case-switches-pep-eato-00221-v0101-en.pdf</a>
<b>TECHNICAL DATA SHEETS</b>	<a href="#">eaton-nzm-technical-information-sheet</a>

<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>POLLUTION DEGREE</b>	3
<b>MOUNTING METHOD</b>	Built-in device fixed built-in technique Fixed
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	173.44 W
<b>UTILIZATION CATEGORY</b>	A (IEC/EN 60947-2)
<b>ISOLATION</b>	500 V AC (between auxiliary contacts and main contacts) 300 V AC (between the auxiliary contacts)
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	40 °C
<b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>	0

<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>	0
<b>PROTECTION AGAINST DIRECT CONTACT</b>	Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
<b>DEGREE OF PROTECTION</b>	IP20 (basic degree of protection, in the operating controls area) IP20
<b>DIRECTION OF INCOMING SUPPLY</b>	As required
<b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>	Screw connection
<b>CURRENT RATING OF NEUTRAL CONDUCTOR</b>	200% of phase conductor
<b>LIFESPAN, MECHANICAL</b>	10000 operations
<b>OVERVOLTAGE CATEGORY</b>	III
<b>DEGREE OF PROTECTION (IP), FRONT SIDE</b>	IP66 (with door coupling rotary handle) IP40 (with insulating surround)
<b>DEGREE OF PROTECTION (TERMINATIONS)</b>	IP10 (tunnel terminal) IP00 (terminations, phase isolator and strip terminal)
<b>NUMBER OF POLES</b>	Four-pole
<b>TERMINAL CAPACITY (COPPER STRIP)</b>	Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor terminal Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal Min. 5 segments of 25 mm x 1 mm at rear-side connection (punched) 10 segments of 80 mm x 1 mm (2x) at rear-side width extension 10 segments of 50 mm x 1 mm (2x) at 1-hole module plate Max. 10 segments of 50 mm x 1 mm x 1 mm (2x) at rear-side connection (punched)
<b>LIFESPAN, ELECTRICAL</b>	2000 operations at 400 V AC-3 1000 operations at 690 V AC-3 3000 operations at 415 V

AC-1
2000 operations at 415 V
AC-3
2000 operations at 690 V
AC-1
3000 operations at 400 V
AC-1

<b>FUNCTIONS</b>	System and cable protection
<b>TYPE</b>	Circuit breaker

<b>SPECIAL FEATURES</b>	<ul style="list-style-type: none"> <li>Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity <math>I_{cn}</math>)</li> <li>Rated current = rated uninterrupted current: 1250 A</li> <li>Set value in neutral conductor is synchronous with set value <math>I_r</math> of main pole.</li> <li>R.m.s. value measurement and "thermal memory"</li> </ul>
-------------------------	---

<b>APPLICATION</b>	Use in unearthing supply systems at 525 V
--------------------	---

<b>SHOCK RESISTANCE</b>	15 g (half-sinusoidal shock 11 ms)
-------------------------	------------------------------------

<b>POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT</b>	Front side
--	------------

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	1250 A
--	--------

<b>RELEASE SYSTEM</b>	Electronic release
-----------------------	--------------------

<b>SHORT-CIRCUIT TOTAL BREAKTIME</b>	< 25 ms ( $\leq 415$ V); < 35 ms ( $> 415$ V)
--------------------------------------	---

<b>RATED SHORT-TIME WITHSTAND CURRENT (T = 0.3 S)</b>	19.2 kA
---	---------

<b>RATED SHORT-TIME WITHSTAND CURRENT (T = 1 S)</b>	19.2 kA
---	---------

**SHORT-CIRCUIT RELEASE**

**NON-DELAYED SETTING -** 15000 A  
**MAX**

**SHORT-CIRCUIT RELEASE**

**NON-DELAYED SETTING -** 2500 A  
**MIN**

**TERMINAL CAPACITY  
(CONTROL CABLE)**

0.75 mm<sup>2</sup> - 1.5 mm<sup>2</sup> (2x)  
0.75 mm<sup>2</sup> - 2.5 mm<sup>2</sup> (1x)

Min. 25 mm x 5 mm direct  
at switch rear-side  
connection

Max. 50 mm x 10 mm (2x)  
direct at switch rear-side  
connection

Min. 25 mm x 5 mm at  
rear-side 1-hole module  
plate

50 mm x 10 mm (2x) at  
rear-side 2-hole module  
plate

M10 at rear-side screw  
connection

Max. 80 mm x 10 mm (2x)  
at rear-side width  
extension

Min. 60 mm x 10 mm at  
rear-side width extension

Max. 50 mm x 10 mm (2x)  
at rear-side 1-hole module  
plate

35 mm<sup>2</sup> - 185 mm<sup>2</sup> (4x) at  
rear-side 2-hole module  
plate

95 mm<sup>2</sup> - 185 mm<sup>2</sup> (2x) at  
rear-side 2-hole module  
plate

95 mm<sup>2</sup> - 240 mm<sup>2</sup> (6x) at  
rear-side width extension

50 mm<sup>2</sup> - 240 mm<sup>2</sup> (4x) at  
4-hole tunnel terminal

300 mm<sup>2</sup> (4x) at rear-side  
width extension

120 mm<sup>2</sup> - 300 mm<sup>2</sup> (1x) at  
rear-side 1-hole module  
plate

95 mm<sup>2</sup> - 300 mm<sup>2</sup> (2x) at  
rear-side 1-hole module  
plate

70 mm<sup>2</sup> - 185 mm<sup>2</sup> (2x) at  
rear-side 1-hole module  
plate

185 mm<sup>2</sup> - 240 mm<sup>2</sup> (1x) at  
rear-side 1-hole module  
plate

50 mm<sup>2</sup> (4x) at rear-side 2-  
hole module plate

70 mm<sup>2</sup> - 240 mm<sup>2</sup> (6x) at  
rear-side width extension

**TERMINAL CAPACITY  
(COPPER SOLID  
CONDUCTOR/CABLE)****TERMINAL CAPACITY  
(ALUMINUM SOLID  
CONDUCTOR/CABLE)**

	240 mm <sup>2</sup> (2x) at rear-side width extension
<b>TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)</b>	120 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) direct at switch rear-side connection 50 mm <sup>2</sup> - 185 mm <sup>2</sup> (4x) direct at switch rear-side connection
<b>TERMINAL CAPACITY (ALUMINUM STRANDED CONDUCTOR/CABLE)</b>	50 mm <sup>2</sup> - 240 mm <sup>2</sup> (4x) at 4-hole tunnel terminal
<b>HANDLE TYPE</b>	Rocker lever
<b>SHORT DELAY CURRENT SETTING (ISD) - MAX</b>	0 A
<b>SHORT DELAY CURRENT SETTING (ISD) - MIN</b>	0 A
<b>INSTANTANEOUS CURRENT SETTING (II) - MAX</b>	15000 A
<b>INSTANTANEOUS CURRENT SETTING (II) - MIN</b>	2500 A
<b>NUMBER OF OPERATIONS PER HOUR - MAX</b>	60
<b>OVERLOAD CURRENT SETTING (IR) - MAX</b>	1250 A
<b>OVERLOAD CURRENT SETTING (IR) - MIN</b>	630 A
<b>OVERLOAD CURRENT SETTING (IR)</b>	630 A - 1250 A
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 Hz</b>	63 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 Hz</b>	50 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 440 V, 50/60 Hz</b>	50 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 525 V, 50/60 Hz</b>	50 kA
<b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 690 V, 50/60 Hz</b>	37 kA
<b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM</b>	187 kA

**AT 400/415 V, 50/60 Hz**

**RATED SHORT-CIRCUIT**  
**MAKING CAPACITY ICM** 187 kA  
**AT 440 V, 50/60 Hz**

**RATED SHORT-CIRCUIT**  
**MAKING CAPACITY ICM** 143 kA  
**AT 525 V, 50/60 Hz**

**RATED SHORT-CIRCUIT**  
**MAKING CAPACITY ICM** 100 kA  
**AT 690 V, 50/60 Hz**

**STANDARD TERMINALS** Screw terminal

**OPTIONAL TERMINALS** Connection on rear. Strip terminal. Tunnel terminal

**RATED SHORT-CIRCUIT**  
**MAKING CAPACITY ICM** 275 kA  
**AT 240 V, 50/60 Hz**

**RATED IMPULSE**  
**WITHSTAND VOLTAGE**  
**(UIMP) AT AUXILIARY** 6000 V  
**CONTACTS**

**RATED IMPULSE**  
**WITHSTAND VOLTAGE**  
**(UIMP) AT MAIN** 8000 V  
**CONTACTS**

**RATED INSULATION**  
**VOLTAGE (UI)** 1000 V AC

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

