

Specifikace



Foto je ilustrační

Eaton 265981

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 4p, 1250A, N4-4-VE1250

General specifications

PRODUCT NAME	Eaton Moeller series NZM molded case circuit breaker electronic
CATALOG NUMBER	265981
EAN	4015082659813
PRODUCT LENGTH/DEPTH	401 mm
PRODUCT HEIGHT	207 mm
PRODUCT WIDTH	280 mm
PRODUCT WEIGHT	27 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC IEC/EN 60947
MODEL CODE	NZMN4-4-VE1250

Technické údaje produktu

AMPERAGE RATING	1250 A
VOLTAGE RATING	690 V - 690 V
CIRCUIT BREAKER FRAME TYPE	NZM4
FEATURES	Protection unit Motor drive optional
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

Zdroje

DECLARATIONS OF CONFORMITY	eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250294en.pdf
ECAD MODEL	ETN.265981.edz
CHARACTERISTIC CURVE	eaton-circuit-breaker-nzm-mccb-characteristic-curve-048.eps eaton-circuit-breaker-nzm-mccb-characteristic-curve-049.eps
INSTALAČNÍ NÁVODY	eaton-circuit-breaker-basic-unit-nzmn4-il01210010z.pdf
MCAD MODEL	DA-CS-nzm4_4p DA-CD-nzm4_4p
PEP ECO-PASSPORT	eaton-molded-case-switches-pep-eato-00221-v0101-en.pdf
VÝKRESY	eaton-circuit-breaker-nzm-mccb-dimensions-023.eps

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
POLLUTION DEGREE	3
MOUNTING METHOD	Fixed Built-in device fixed built-in technique
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	173.44 W
UTILIZATION CATEGORY	B (IEC/EN 60947-2)
ISOLATION	300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
PROTECTION AGAINST DIRECT CONTACT	Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
DEGREE OF PROTECTION	IP20 IP20 (basic degree of protection, in the operating controls area)
DIRECTION OF INCOMING SUPPLY	As required
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
CURRENT RATING OF NEUTRAL CONDUCTOR	200% of phase conductor
LIFESPAN, MECHANICAL	10000 operations
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION (IP), FRONT SIDE	IP40 (with insulating surround) IP66 (with door coupling rotary handle)
DEGREE OF PROTECTION (TERMINATIONS)	IP10 (tunnel terminal) IP00 (terminations, phase isolator and strip terminal)
NUMBER OF POLES	Four-pole
TERMINAL CAPACITY (COPPER STRIP)	10 segments of 80 mm x 1 mm (2x) at rear-side width extension Min. 5 segments of 25 mm x 1 mm at rear-side connection (punched) 10 segments of 50 mm x 1 mm (2x) at 1-hole module plate Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor terminal Max. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched)
LIFESPAN, ELECTRICAL	3000 operations at 400 V AC-1 2000 operations at 400 V AC-3 2000 operations at 690 V

AC-1 1000 operations at 690 V
AC-3 3000 operations at 415 V
AC-1 2000 operations at 415 V
AC-3

FUNCTIONS	Systems, cable, selectivity and generator protection
------------------	--

TYPE	Circuit breaker
-------------	-----------------

SPECIAL FEATURES	<ul style="list-style-type: none"> Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn}) R.m.s. value measurement and "thermal memory" Adjustable time delay setting to overcome current peaks t_r at $6 \times I_r$ also infinity (without overload releases) Adjustable delay time t_{sd} i^2t constant function: switchable Set value in neutral conductor is synchronous with set value I_r of main pole. Rated current = rated uninterrupted current: 1250 A
-------------------------	--

APPLICATION	Use in unearthing supply systems at 525 V
--------------------	---

SHOCK RESISTANCE	15 g (half-sinusoidal shock 11 ms)
-------------------------	------------------------------------

POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT	Front side
--	------------

RATED OPERATIONAL CURRENT FOR SPECIFIED	1250 A
--	--------

HEAT DISSIPATION (IN)

RELEASE SYSTEM	Electronic release
SHORT-CIRCUIT TOTAL BREAKTIME	< 25 ms (≤ 415 V); < 35 ms (> 415 V)
RATED SHORT-TIME WITHSTAND CURRENT (T = 0.3 S)	19.2 kA
RATED SHORT-TIME WITHSTAND CURRENT (T = 1 S)	19.2 kA
SHORT-CIRCUIT RELEASE DELAYED SETTING - MAX	12500 A
SHORT-CIRCUIT RELEASE DELAYED SETTING - MIN	1260 A
SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MAX	15000 A
SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MIN	2500 A
TERMINAL CAPACITY (CONTROL CABLE)	0.75 mm ² - 1.5 mm ² (2x) 0.75 mm ² - 2.5 mm ² (1x)
TERMINAL CAPACITY (COPPER BUSBAR)	Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate Min. 25 mm x 5 mm at rear-side 1-hole module plate Min. 60 mm x 10 mm at rear-side width extension Min. 25 mm x 5 mm direct at switch rear-side connection Max. 50 mm x 10 mm (2x) direct at switch rear-side connection M10 at rear-side screw connection Max. 80 mm x 10 mm (2x) at rear-side width extension 50 mm x 10 mm (2x) at rear-side 2-hole module plate
TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE)	120 mm ² - 300 mm ² (1x) at rear-side 1-hole module plate 35 mm ² - 185 mm ² (4x) at rear-side 2-hole module plate 95 mm ² - 300 mm ² (2x) at rear-side 1-hole module plate 95 mm ² - 185 mm ² (2x) at rear-side 2-hole module plate

	plate 95 mm ² - 240 mm ² (6x) at rear-side width extension 50 mm ² - 240 mm ² (4x) at 4-hole tunnel terminal 300 mm ² (4x) at rear-side width extension
TERMINAL CAPACITY (ALUMINUM SOLID CONDUCTOR/CABLE)	240 mm ² (2x) at rear-side width extension 70 mm ² - 240 mm ² (6x) at rear-side width extension 185 mm ² - 240 mm ² (1x) at rear-side 1-hole module plate 50 mm ² (4x) at rear-side 2-hole module plate 70 mm ² - 185 mm ² (2x) at rear-side 1-hole module plate
TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)	50 mm ² - 185 mm ² (4x) direct at switch rear-side connection 120 mm ² - 185 mm ² (1x) direct at switch rear-side connection
TERMINAL CAPACITY (ALUMINUM STRANDED CONDUCTOR/CABLE)	50 mm ² - 240 mm ² (4x) at 4-hole tunnel terminal
HANDLE TYPE	Rocker lever
SHORT DELAY CURRENT SETTING (ISD) - MAX	12500 A
SHORT DELAY CURRENT SETTING (ISD) - MIN	1250 A
INSTANTANEOUS CURRENT SETTING (II) - MAX	15000 A
INSTANTANEOUS CURRENT SETTING (II) - MIN	2500 A
NUMBER OF OPERATIONS PER HOUR - MAX	60
OVERLOAD CURRENT SETTING (IR) - MAX	1250 A
OVERLOAD CURRENT SETTING (IR) - MIN	630 A
OVERLOAD CURRENT SETTING (IR)	630 A - 1250 A
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 Hz	37 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS	37 kA

**(IEC/EN 60947) AT
400/415 V, 50/60 Hz**

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS
(IEC/EN 60947) AT 440 V,
50/60 Hz**

26 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS
(IEC/EN 60947) AT 525 V,
50/60 Hz**

19 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS
(IEC/EN 60947) AT 690 V,
50/60 Hz**

15 kA

**RATED SHORT-CIRCUIT
MAKING CAPACITY ICM
AT 400/415 V, 50/60 Hz**

105 kA

**RATED SHORT-CIRCUIT
MAKING CAPACITY ICM
AT 440 V, 50/60 Hz**

74 kA

**RATED SHORT-CIRCUIT
MAKING CAPACITY ICM
AT 525 V, 50/60 Hz**

53 kA

**RATED SHORT-CIRCUIT
MAKING CAPACITY ICM
AT 690 V, 50/60 Hz**

40 kA

STANDARD TERMINALS Screw terminal

OPTIONAL TERMINALS Connection on rear. Strip terminal. Tunnel terminal

**RATED SHORT-CIRCUIT
MAKING CAPACITY ICM
AT 240 V, 50/60 Hz**

105 kA

**RATED IMPULSE
WITHSTAND VOLTAGE
(UIMP) AT AUXILIARY
CONTACTS**

6000 V

**RATED IMPULSE
WITHSTAND VOLTAGE
(UIMP) AT MAIN
CONTACTS**

8000 V

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICU
(IEC/EN 60947) AT 525 V,
50/60 Hz**

25 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICU
(IEC/EN 60947) AT
400/415 V, 50/60 Hz**

50 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICU
(IEC/EN 60947) AT 230 V,
50/60 Hz**

50 kA

RATED SHORT-CIRCUIT 20 kA

BREAKING CAPACITY ICU

(IEC/EN 60947) AT 690 V,

50/60 HZ

RATED SHORT-CIRCUIT

BREAKING CAPACITY ICU

(IEC/EN 60947) AT 440 V,

50/60 HZ

35 kA

RATED INSULATION

VOLTAGE (UI)

1000 V AC

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATUM:



Eaton Corporation Plc.

Eaton House

30 Pembroke Road

Dublin 4, Irsko

Eaton.com

© 2025 Eaton. Všechna práva vyhrazena.

Follow us on social media to get the latest product and support information.

