

Specifications



Eaton 266676

Eaton Moeller series NZM - Molded Case Circuit Breaker. Additional plate

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element accessory
CATALOG NUMBER	266676
MODEL CODE	NZM1/2-XZB
EAN	4015082666767
PRODUCT LENGTH/DEPTH	145 mm
PRODUCT HEIGHT	3 mm
PRODUCT WIDTH	50 mm
PRODUCT WEIGHT	0.176 kg
COMPLIANCES	UL/CSA IEC RoHS conform

Product specifications

USED WITH	NZM1-4
	PN1
	PN2-4
	NZM1
	NZM1-NA
	NZM2
	NZM2-4
	NS1
	N2
	N1-4
	N2-4
	NZM2-NA
	PN1-4
	N1
	NS2
	PN2
FEATURES	For fitting to the mounting bracket when using N conductor or PE conductor terminals K25, K50, K95 or K150
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
INSTALLATION INSTRUCTIONS	eaton-side-wall-actuator-nzm1-xs-xzb-il01203006z.pdf eaton-side-wall-actuator-nzm2-xzb-xs-il01206004z.pdf
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
MCAD MODEL	nzm1_2_xzb.stp nzm1_2_xzb.dwg
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Black
FRAME	NZM1/2
SUITABLE FOR	Switch disconnectors Power circuit breaker
TYPE	• Accessory • Additional plate

SPECIAL FEATURES

- Additional terminal arrangement for sidewall drive with mounting bracket
- For fitting to the mounting bracket when using N conductor or PE conductor terminals K50/1, K95/... or K150/...

DEGREE OF PROTECTION IP66
/ NEMA ENCLOSURE TYPE Other

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

