Product data sheet

Specification





auxiliary contact - 1 OC - 380..415 V - 6 A - for C60 ID

26924

! Discontinued on: Jul 12, 2021

Product availability: Non-Stock - Not normally stocked in distribution facility

① Discontinued

Main

Range Of Product	Multi9
Product Or Component Type	OC contact
Device Short Name	OF
Signal Contacts Composition	1 C/O
Line Rated Current	AC-12 3 A at 380415 V, AC 50/60 Hz AC-12 6 A at 220240 V, AC 50/60 Hz DC-12 1 A at 130 V, DC DC-12 1.5 A at 60 V, DC DC-12 2 A at 48 V, DC DC-12 6 A at 24 V, DC
9 Mm Pitches	1

Complementary

Mounting Mode	Fixed	
Mounting Support	DIN rail	
Height	3.31 in (84 mm)	
Width	0.35 in (9 mm)	
Depth	2.87 in (73 mm)	
Connections - Terminals	Clamp terminal2 0.00 in² (1.5 mm²) - flexible Clamp terminal2 0.00 in² (1.5 mm²) - rigid Clamp terminal1 0.000.00 in² (0.52.5 mm²) - flexible Clamp terminal1 0.000.00 in² (0.52.5 mm²) - rigid	
Wire Stripping Length	tripping Length 0.35 in (9 mm)	
Tightening Torque	8.85 lbf.in (1 N.m)	

Environment

Standards	EN/IEC 60947-5-1	
Product Certifications	ASTA KEMA ASEFA LCIE	
Ip Degree Of Protection	IP20 conforming to EN/IEC 60947-5-1	
Pollution Degree	3 EN/IEC 60947-5-1	
Tropicalisation	2 EN/IEC 60947-5-1	
Relative Humidity	95 % 131 °F (55 °C)	
Ambient Air Temperature For Operation	-13122 °F (-2550 °C)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

	• • •
Category	US10DE201078
Discount Schedule	0DE2
Gtin	3303430269243
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.79 in (2 cm)
Package 1 Width	3.15 in (8 cm)
Package 1 Length	3.46 in (8.8 cm)
Package 1 Weight	1.34 oz (38 g)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Toxic Heavy Metal Free	
⊘	Mercury Free	
②	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
	The active offinal Notice decidation (out of offinal Notice legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information