

# IB IL 24 PWR IN/R/L-0.8A-PAC - Power module



2693020  
<https://www.phoenixcontact.com/pc/products/2693020>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Inline boost terminal for the communications power  $U_L$  of 0.8 A, complete with accessories (connectors and labeling field)

## Product description

The terminal is designed for use within an Inline station. If the maximum load of the bus coupler for the communications power ( $U_L$ ) is reached, this terminal can be used to provide this voltage again. To do this, apply a 24 V DC voltage ( $U_{24V}$ ) to the terminal. The communications power ( $U_L$ ) is generated from this voltage.

## Your advantages

- Supply of the 24 V voltage for generating the communications power ( $U_L$ ) up to 0.8 A

## Commercial data

Item number	2693020
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DRI123
Catalog page	Page 113 (C-6-2019)
GTIN	4046356447416
Weight per piece (including packing)	90.2 g
Weight per piece (excluding packing)	65 g
Customs tariff number	85389099
Country of origin	DE

# IB IL 24 PWR IN/R/L-0.8A-PAC - Power module




2693020

<https://www.phoenixcontact.com/pc/products/2693020>

## Technical data

### Dimensions

Dimensional drawing	
Width	12.2 mm
Height	119.8 mm
Depth	71.5 mm

### Notes

#### Utilization restriction

CCCex note	Use in potentially explosive areas is not permitted in China.
------------	---

### Interfaces

#### Inline local bus

Number of interfaces	2
Connection method	Inline data jumper
Transmission speed	500 kbps / 2 Mbps (Can be used in Inline stations with these transmission speeds)

### System properties

#### Module

ID code (dec.)	none
ID code (hex)	none
Register length	0 Byte
Required parameter data	0 Byte
Required configuration data	0 Byte

### Product properties

Type	modular
Product type	I/O component
Product family	Inline
Number of plugs	1
Special properties	24 V DC
	Boost $U_L$ (0.8 A)

#### Insulation characteristics

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

# IB IL 24 PWR IN/R/L-0.8A-PAC - Power module



2693020

<https://www.phoenixcontact.com/pc/products/2693020>

## Electrical properties

Test section	7.5 V communications power, 24 V analog supply/functional ground 500 V AC 50 Hz 1 min.
	7.5 V logics supply, 24 V analog supply / 24 V main supply, 24 V segment supply 500 V AC 50 Hz 1 min.
	24 V main supply, 24 V segment supply/functional ground 500 V AC 50 Hz 1 min.
Protective circuit	Surge protection; Input protective diodes (can be destroyed by permanent overload)Pulse loads up to 1500 W are short circuited by the input protective diode.
	Protection against polarity reversal (segment supply/main supply); Serial diode in the lead path of the power supply unit; in the event of an error only a low current flows. In the event of an error, no fuse trips within the external power supply unit.
Fuse	electrical/thermal overload protection, included in scope of delivery

### Supply

I/O voltage	24 V DC
I/O voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Max. current consumption	274 mA (at nominal voltage)

### Potentials

Power consumption	max. 0.6 W (entire device)
-------------------	----------------------------

### Potentials: 24 V supply ( $U_{24V}$ ) for generating $U_L$

Supply voltage	24 V DC (via Inline connector)
Supply voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current draw	max. 274 mA DC (at nominal voltage)
	min. 13 mA DC (at nominal voltage)

### Potentials: Communications power ( $U_L$ )

Supply voltage	7.5 V DC (via voltage jumper)
----------------	-------------------------------

## Connection data

### Connection technology

Connection name	Inline connector
-----------------	------------------

### Conductor connection

Connection method	Spring-cage connection
Conductor cross section rigid	0.08 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section flexible	0.08 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

### Inline connector

Connection method	Spring-cage connection
Conductor cross section, rigid	0.08 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>

# IB IL 24 PWR IN/R/L-0.8A-PAC - Power module



2693020

<https://www.phoenixcontact.com/pc/products/2693020>

Conductor cross section, flexible	0.08 mm² ... 1.5 mm²
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)

## Mounting

Mounting type	DIN rail mounting
---------------	-------------------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)