

2700121

https://www.phoenixcontact.com/us/products/2700121

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



LED flashing light element, 24 V AC/DC, green

Your advantages

- · Tool-free element changeover
- · Can be freely combined
- · High light and color intensity
- Minimum LED service life of 50,000 h
- Low power consumption
- Degree of protection IP65

Commercial data

Item number	2700121
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR07
Product key	DRL112
Catalog page	Page 516 (C-6-2019)
GTIN	4046356491150
Weight per piece (including packing)	73.4 g
Weight per piece (excluding packing)	73.4 g
Customs tariff number	85318070
Country of origin	DE



https://www.phoenixcontact.com/us/products/2700121



Technical data

Notes

110tc on application	Note on application	Only for industrial us
----------------------	---------------------	------------------------

Product properties

Product type	Optical element
Area of application	Signal tower

Electrical properties

Maximum power dissipation for nominal condition	0.6 W
Maximum power dissipation for norminal condition	0.0 44

Genera

General	
Input voltage	24 V AC/DC
Maximum inrush current	max. 500 mA
Current consumption	25 mA
Source of light type	LED
Operating time	100 %
Service life electrical	max. 100,000 h
Optical signal type	LED flashlight
Signal frequency	approx. 1 Hz

Dimensions

Height	65.5 mm
Diameter	70 mm

Material specifications

Calotte color	green
Material	Polycarbonate PC

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 (when installed or with end cover)
Ambient temperature (operation)	-20 °C 50 °C

EMC data

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
-------------------------------	---

Mounting

Mounting type	Plug-in mounting
Assembly note	Rubber seal pre-installed for each element
Mounting position	any



2700121

https://www.phoenixcontact.com/us/products/2700121

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2700121



EAC

Approval ID: RU *-DE.A*30.B.00237



UL Listed

Approval ID: E123528



cUL Listed

Approval ID: E123528



EAC-RoHS

Approval ID: RU D-DE.HB35.B.00391

cULus Listed



2700121

https://www.phoenixcontact.com/us/products/2700121

Classifications

UNSPSC 21.0

ECLASS

27371220
27371220
27371220
EC000232

46171600



2700121

https://www.phoenixcontact.com/us/products/2700121

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-l
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	3b83f47d-3d9c-46f2-9e90-e25b1d092a03

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com