

# PSD-S OE LED FL YE - Optical element



2700124

<https://www.phoenixcontact.com/us/products/2700124>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



LED flashing beacon element, 24 V DC, double flash, yellow

## Your advantages

- Tool-free element changeover
- High light and color intensity
- Can be freely combined
- Minimum LED service life of 50,000 h
- Low power consumption
- Optimum detection thanks to double flash
- Degree of protection IP65

## Commercial data

Item number	2700124
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR07
Product key	DRL112
Catalog page	Page 517 (C-6-2019)
GTIN	4046356491181
Weight per piece (including packing)	86 g
Weight per piece (excluding packing)	72 g
Customs tariff number	85318070
Country of origin	DE

# PSD-S OE LED FL YE - Optical element



2700124

<https://www.phoenixcontact.com/us/products/2700124>

## Technical data

### Product properties

Product type	Optical element
Area of application	Signal tower

### Electrical properties

Maximum power dissipation for nominal condition	0.84 W
---	--------

#### General

Input voltage	24 V DC
Maximum inrush current	max. 200 mA
Current consumption	35 mA
Source of light type	LED
Operating time	100 %
Service life electrical	max. 50,000 h
Optical signal type	LED flashing beacon with double flash
Signal frequency	approx. 1 Hz

### Dimensions

Height	65.5 mm
Diameter	70 mm

### Material specifications

Calotte color	yellow
Material	Polycarbonate PC

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP65 (when installed or with end cover)
Ambient temperature (operation)	-20 °C ... 50 °C

### EMC data

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
-------------------------------	---

### Mounting

Mounting type	Plug-in mounting
Assembly instructions	Rubber seal pre-installed for each element
Mounting position	any

# PSD-S OE LED FL YE - Optical element




2700124


<https://www.phoenixcontact.com/us/products/2700124>

## Approvals


To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2700124>




**EAC**  
Approval ID: RU \*-DE.A\*30.B.00237



**UL Listed**  
Approval ID: FILE E 123528



**cUL Listed**  
Approval ID: FILE E 123528



**EAC-RoHS**  
Approval ID: RU D-DE.HB35.B.00391

**cULus Listed**

# PSD-S OE LED FL YE - Optical element



2700124

<https://www.phoenixcontact.com/us/products/2700124>

## Classifications

### ECLASS

ECLASS-11.0	27371220
ECLASS-13.0	27371220
ECLASS-12.0	27371220

### ETIM

ETIM 9.0	EC000232
----------	----------

### UNSPSC

UNSPSC 21.0	46171600
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)