

FL WLAN 24 AP 802-11-US - Wireless module



2700448

<https://www.phoenixcontact.com/pc/products/2700448>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



WLAN access point for the USA and Canada, 24 V DC, PoE, IEEE 802.11 a/b/g, 2.4 GHz, 5 GHz, client adapter, antenna diversity, web-based management, 802.11i, WPA2, WPA-PSK, RADIUS, WEP, TKIP, AES

Your advantages

- 2.4 GHz and 5 GHz supported
- Maximum security according to IEEE 802.11i with AES encryption
- High resistance to vibration, shock, and EMI
- Range of several hundred meters*

Commercial data

Item number	2700448
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DNN2W1
Catalog page	Page 124 (AX-2011)
GTIN	4046356553025
Weight per piece (including packing)	1.3 kg
Weight per piece (excluding packing)	1.3 kg
Customs tariff number	85176200
Country of origin	DE

2700448

<https://www.phoenixcontact.com/pc/products/2700448>

Technical data

Product properties

Type	Stand-Alone
Product type	Wireless module

Wireless card

Number	1
Type	IEEE 802.11a/b/g, 2.4 and 5 GHz to 54 Mbps
Assembly instructions	Permanently installed

Electrical properties

Supply: Module electronics

Connection method	Via COMBICON
Supply voltage	24 V DC (PoE)
Supply voltage range	18.5 V DC ... 30.5 V DC
Supply current	400 mA (Recommended protection 2AT)

Interfaces

Ethernet

Interface	Ethernet
Number	1
Connection method	RJ45 jack

Antenna

Number	2
Connection method	RSMA (male)

Functions

Operating modes	Access Point
Configuration	Multilingual web-based interface (German/English) under http or https, with password protection
Automatic channel selection	yes
Quality of service (QoS)	Yes
Virtual LAN (VLAN) support 802.1Q	yes
Security	WEP 64 bit/128 bit
	WEPplus
	WPA TKIP
	802.11i WPA2 (RSN,AES)
	WPA PSK (preshared key)
	WPA group & master rekeying
Wireless licenses	USA, Canada
Country support	USA
	Canada

FL WLAN 24 AP 802-11-US - Wireless module



2700448

<https://www.phoenixcontact.com/pc/products/2700448>

Wireless

Designation	Wireless card
Antenna connection method	RSMA (female)
Frequency band	2.4 GHz
	5 GHz
Wireless standard	WLAN
	IEEE 802.11
	a
	b
	g
	h
Transmission power	20 dBm (EIRP)
Number of wireless interfaces	1 IEEE 802.11 a/b/g
Wireless modules that can be connected	256 (More than)

Dimensions

Width	159 mm
Height	250 mm
Depth	65 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-20 °C ... 55 °C
Air pressure (operation)	795 hPa ... 1080 hPa (up to 2000 m above sea level)
Permissible humidity (operation)	10 % ... 85 % (non-condensing)

Standards and regulations

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Mounting

Mounting type	Adapter plate
	Wall mounting on adapter plate
Assembly instructions	External OMNI omnidirectional antenna, the antennas can be exchanged

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com