

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Ethernet Gigabit Modular Switch with four 1000 Mbps combo ports and twelve 10/100 Mbps RJ45 slots, can be extended by an extension station to up to 24 ports, with integrated routing function



Product description

The Gigabit Modular Switch is a high-performance managed switch, which covers the port requirements of industrial applications in a modular and flexible way. It also supports all popular Gigabit and Fast Ethernet transmission standards, IT standard protocols, and the PROFINET and EtherNet/IP™ automation protocols. For use in the production backbone or automation cell, the FL SWITCH GHS 4G/12 has four integrated Gigabit ports, which can either be used via SFP modules or twisted pair connections. In addition to the four integrated 100 Mbps TX ports, up to 16 more 100 Mbps ports can be used via interface modules.

The switch can be configured as a router using the integrated Layer 3 license. The GHS switch can be routed into up to 28 different subnetworks. It can also be operated as a redundant router using VRRP (Virtual Redundancy Routing Protocol) .

Your advantages

- Connection of Gigabit fiberglass via FL SFP plug-in modules
- Integrated routing function
- Security in the automation network according to IEEE 802.1X
- Connection of connection media that can be assembled in the field, such as POF, HCS, and GI HCS
- Quick and easy local configuration options with the new operator/display interface

Commercial data

Item number	2700786
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DN17
Product key	DNN123
Catalog page	Page 329 (C-6-2019)
GTIN	4046356647151
Weight per piece (including packing)	3,032 g
Weight per piece (excluding packing)	2,700 g
Customs tariff number	85176200
Country of origin	DE

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

Technical data

Dimensions

Width	289 mm
Height	127 mm
Depth	122 mm

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Material specifications

Material base plate	Die-cast aluminum, corrosion-resistant
Housing surface material	Stainless steel, smooth, corrosion-resistant

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

Interfaces

Ethernet

Connection method	RJ45
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100 Mbps
Transmission physics	Copper
Transmission length	100 m (per segment)
Signal LEDs	Supply voltage, data transmission, error, link, activity
No. of channels	4 (RJ45 ports)

Ethernet

Connection method	via interface module
Note on the connection method	Max. 4 interface modules (without extension)
Transmission speed	10/100 Mbps (full duplex)
Transmission physics	multi-mode fiberglass
	Single-mode fiberglass
	POF-SCRJ
	GI-HCS fibers
	Copper
	PoE
Signal LEDs	Data receive, link status
No. of channels	2 (Per interface module)

Ethernet (combo)

Connection method	SFP/RJ45
-------------------	----------

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

Transmission speed	1000 Mbps (full duplex)
Transmission physics	FO
	Copper
Transmission length	up to 80 km (Depending on the fiber/SFP module used)
Wavelength	850 nm / 1310 nm / 1550 nm
No. of channels	4 (SFP ports or RJ45 ports)

Ethernet (combo)

Connection method	SFP/RJ45
Note on the connection method	Either SFP port or RJ45 port active
Transmission speed	10/100/1000 Mbps (SFP module: 1000 Mbps)
Transmission physics	Copper or SFP module
Transmission length	up to 80 km (Depending on the fiber/SFP module used)
Wavelength	850 nm / 1310 nm / 1550 nm
Signal LEDs	Data receive, link status
No. of channels	4 (Combo ports)

Serial (RS-232)

Connection method	RS-232-C, 6-pos. MINI-DIN socket (PS/2)
-------------------	---

Product properties

Product type	Switch
Product family	Managed Switch GHS
Type	Stand-Alone

Insulation characteristics

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Switch functions

Diagnostic functions	RMON History
	N:1-Portmirroring
	LLDP (Link Layer Discovery Protocol)
	SNMP-Traps
Basic functions	Store-and-forward switch complies with IEEE 802.3, 8 priority classes according to IEEE 802.1p, smart mode, port mirroring, multicast filtering, IGMP snooping, VLANs, Media Redundancy Protocol (MRP according to IEC 62439), Rapid Spanning Tree (RSTP), Fast Ring Detection (FRD), Large Tree Support, IEEE 802.1X security, port security, SNMPv3, HTTPS, PROFINET device, GMRP, GVRP, SNTP, 2 digital inputs
Signal contact control voltage	24 V (typical)
Signal contact control current	190 mA (maximum)
PROFINET conformance class	Conformance-Class B
PROFINET device function	PROFINET device
	PROFINET energy
	Fast Startup
PROFINET specification	Version 1.1
	Quality of Service (8 priority classes)

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

Filter functions	Port-Priorisierung
	VLAN (up to 223 VLANs)
Management	Web-based management (HTTP)
	SNMPv1/v2/v3
Redundancy	MRP (Media Redundancy Protocol)
	RSTP (Rapid Spanning Tree Protocol)
	FRD (Fast Ring Detection)
	Large Tree Support
	STP (Spanning Tree Protocol)
	MSTP (Multiple Spanning Tree Protocol)
Status and diagnostic indicators	LEDs: US1, US2 (power supply), Fail (alarm contact), 2 LEDs per Ethernet port (Link and switchable Activity/Speed/Duplex), DI1, DI2 (Digital Input), UI (supply voltage for ext. sensor), and large operator display (display of IP address and other parameters)
Supported browsers	Internet Explorer 5.5 or higher
Additional functions	DHCP Option 82 (Relay Agent)
	Link aggregation (up to 8 trunks)
	BootP
	DHCP-Client
	MAC-based Port-Security
	Jumbo frames

Security functions

Basic functions	Store-and-forward switch complies with IEEE 802.3, 8 priority classes according to IEEE 802.1p, smart mode, port mirroring, multicast filtering, IGMP snooping, VLANs, Media Redundancy Protocol (MRP according to IEC 62439), Rapid Spanning Tree (RSTP), Fast Ring Detection (FRD), Large Tree Support, IEEE 802.1X security, port security, SNMPv3, HTTPS, PROFINET device, GMRP, GVRP, SNTp, 2 digital inputs
-----------------	---

Electrical properties

Power consumption	typ. 19 W (without plugged-in interface modules)
Local diagnostics	US1/2 Supply voltage US1, US2 Green LED
	FAIL Div. LED red
	LINK Link status Green LED
	MODE Data transmission speed Green LED
	MODE Data transmission speed Green/orange LED
Maximum power dissipation for nominal condition	19.2 W
Transmission medium	Copper
	FO

Supply

Supply voltage (DC)	24 V DC (redundant)
Supply voltage range	18.5 V DC ... 30.2 V DC
Power supply connection	Via COMBICON, max. conductor cross section 2.5 mm ²
Residual ripple	3.6 V _{PP} (within the permitted voltage range)
Max. current consumption	2.7 A

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

Typical current consumption	800 mA (up to 2.5 A, depends on the configuration)
-----------------------------	--

Function

Signal contact control voltage	24 V (typical)
Signal contact control current	190 mA (maximum)

Connection data

Connection method	Screw connection
Conductor cross section, rigid	0.2 mm² ... 2.5 mm²
Conductor cross section, flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	24 ... 12
Stripping length	7 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 55 °C (non-condensing)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)
Vibration (operation)	in acc. with IEC 60068-2-6: 5g, 150 Hz
Air pressure (operation)	80 kPa ... 108 kPa (2000 m above mean sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)

Standards and regulations

Free from substances that could impair the application of coating	In acc. with VW specification
---	-------------------------------

EMC data

Conformance with EMC directives	IEC 61000-4-2 (ESD) Criterion B, Class 3
	IEC 61000-4-3 (immunity to radiated interference) Criterion A, 10 V/m
	IEC 61000-4-4 (burst) Criterion A, 1 kV
	IEC 61000-4-5 (surge) Criterion B
	IEC 61000-4-6 (immunity to conducted interference) Criterion A, 10 Vrms
	EN 55022 (emitted interference) Class A
Noise immunity	EN 61000-6-2:2005
Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
Noise emission	EN 61000-6-3/-4

System properties

Functionality

Basic functions	Store-and-forward switch complies with IEEE 802.3, 8 priority classes according to IEEE 802.1p, smart mode, port mirroring, multicast filtering, IGMP snooping, VLANs, Media Redundancy Protocol (MRP according to IEC 62439), Rapid Spanning Tree
-----------------	--

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

	(RSTP), Fast Ring Detection (FRD), Large Tree Support, IEEE 802.1X security, port security, SNMPv3, HTTPS, PROFINET device, GMRP, GVRP, SNTp, 2 digital inputs
--	--

System requirements

Supported browsers	Internet Explorer 5.5 or higher
--------------------	---------------------------------

Signaling

Status display	LEDs: US1, US2 (power supply), Fail (alarm contact), 2 LEDs per Ethernet port (Link and switchable Activity/Speed/Duplex), DI1, DI2 (Digital Input), UI (supply voltage for ext. sensor), and large operator display (display of IP address and other parameters)
----------------	---


FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2700786>



UL Listed

Approval ID: FILE E 140324



cUL Listed

Approval ID: FILE E 140324

cULus Listed

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

Classifications

ECLASS

ECLASS-11.0	19170401
ECLASS-12.0	19170401
ECLASS-13.0	19170401

ETIM

ETIM 9.0	EC000734
----------	----------

UNSPSC

UNSPSC 21.0	43222600
-------------	----------

2700786

<https://www.phoenixcontact.com/us/products/2700786>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(a)-I, 6(c), 7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	000dbfce-7643-42b8-ad64-03d846d17c0f

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

Accessories

FL FXT - Extension module

2989307

<https://www.phoenixcontact.com/us/products/2989307>



Extension module for the FL SWITCH GHS... Gigabit Modular Switch, extension by up to 8 Ethernet ports

FL IF 2TX VS-RJ-F - Media module

2832344

<https://www.phoenixcontact.com/us/products/2832344>



Interface module for connecting twisted pair cable, RJ45, connection direction forward

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

FL IF 2FX SC-F - Media module

2832412

<https://www.phoenixcontact.com/us/products/2832412>



Fiber optic interface module for connecting 100 Base-FX multi-mode glass fibers (1300 nm), SC, connection direction forward

FL IF 2FX SC-D - Media module

2832425

<https://www.phoenixcontact.com/us/products/2832425>



Fiber optic interface module for connecting 100 Base-FX multi-mode glass fibers (1300 nm), SC, connection direction downward

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

FL IF 2FX SM SC-D - Media module

2832205

<https://www.phoenixcontact.com/us/products/2832205>



FO interface module for connecting 100 Base-FX single mode glass fibers (1300 nm), SC, connection direction downward

FL IF 2FX ST-D - Media module

2884033

<https://www.phoenixcontact.com/us/products/2884033>



Fiber optic interface module for connecting 100 Base-FX multi-mode glass fibers (1300 nm), ST, connection direction downward

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

FL IF 2POF SCRJ-D - Media module

2891084

<https://www.phoenixcontact.com/us/products/2891084>



Fiber optic interface module for connecting 100 Base-FX POF/PCF fibers (650 nm), SC-RJ, connection direction downward

FL SFP SX - Media module

2891754

<https://www.phoenixcontact.com/us/products/2891754>



Gigabit SFP module for transmission up to 1 km with a wavelength of 850 nm.

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

FL SFP LX - Media module

2891767

<https://www.phoenixcontact.com/us/products/2891767>



Gigabit SFP module for transmission up to 30 km with a wavelength of 1310 nm.

FL SFP LH - Media module

2989912

<https://www.phoenixcontact.com/us/products/2989912>



Gigabit SFP module for transmission up to 80 km with a wavelength of 1,550 nm.

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

FL SD FLASH/MRM - Program / configuration memory

2700270

<https://www.phoenixcontact.com/us/products/2700270>


Configuration memory for FL-SWITCH-GHS products, plug-in



PSM-LWL-GDM-RUGGED- 50/125 - FO cable

2799322

<https://www.phoenixcontact.com/us/products/2799322>



Fiber glass cable, duplex 50 μm /125 μm , by the meter, without male connector, for installation in stationary systems and machines

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

PSM-LWL-GDO- 50/125 - FO cable

2799432

<https://www.phoenixcontact.com/us/products/2799432>



Fiberglass cable, duplex 50/125 µm, by the meter, without connector, for outdoor installation

FOC-GDM-RUGGED-1016/IP20/... - FO patch cable

2901558

<https://www.phoenixcontact.com/us/products/2901558>



Robust GOF installation cable for assembly (IP20 heads only) for installation in stationary systems and machines, aramid strain-relief elements, with individual elements made from FRNC material, halogen-free, ozone and UV resistant, with a polyurethane (PUR) outer sheath

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

FOC-GDO-1017/IP20/... - FO patch cable

2901559

<https://www.phoenixcontact.com/us/products/2901559>



Highly rugged GOF round cable (IP20 heads only) for assembly and for outdoor installation with integrated moisture barrier as well as rodent-proof scrim. Individual elements made from highly flexible FRNC material. The wire is ozone and UV resistant with a very rugged polyethylene outer sheath.

FL IF 2PSE-F - Media module

2832904

<https://www.phoenixcontact.com/us/products/2832904>



Interface module for connecting PoE twisted pair ports, RJ45, connection direction forward

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

COM CAB MINI DIN - Connecting cable

2400127

<https://www.phoenixcontact.com/us/products/2400127>



Connecting cable, for connecting the controller to a PC (RS-232) for PC WORX with flow control, 3 m in length

FL DIN RA - DIN rail adapter

2891053

<https://www.phoenixcontact.com/us/products/2891053>



The FL DIN RA is installed in a standard, 19-inch rack (EIA-310-D, IEC 60297-3-100) to allow DIN rail mounted equipment to be rack mounted.

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

FL CAT5 PATCH 0,5 - Patch cable

2832263

<https://www.phoenixcontact.com/us/products/2832263>



Patch cable, CAT5, assembled, 0.5 m

FL CAT5 PATCH 1,0 - Patch cable

2832276

<https://www.phoenixcontact.com/us/products/2832276>



Patch cable, CAT5, assembled, 1 m

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

FL CAT5 PATCH 2,0 - Patch cable

2832289

<https://www.phoenixcontact.com/us/products/2832289>




Patch cable, CAT5, assembled, 2 m

NBC-R4AC-R4AC-IE8A/.../... - Patch cable

1411854

<https://www.phoenixcontact.com/us/products/1411854>



Patch cable, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, cable outlet: straight, Ethernet

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch




2700786

<https://www.phoenixcontact.com/us/products/2700786>

NBC-R4AC/10G-R4AC/10G-94F/2,0 - Patch cable

1408360

<https://www.phoenixcontact.com/us/products/1408360>




Patch cable, CAT6_A, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 2.0 m

NBC-R4AC/10G-R4AC/10G-94F/3,0 - Patch cable

1408365

<https://www.phoenixcontact.com/us/products/1408365>



Patch cable, CAT6_A, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 3.0 m

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

NBC-R4AC/1,0-93B/R4AC - Patch cable

1408968

<https://www.phoenixcontact.com/us/products/1408968>



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

NBC-R4AC/2,0-93B/R4AC - Patch cable

1408969

<https://www.phoenixcontact.com/us/products/1408969>



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

FL SWITCH GHS 4G/12-L3 - Industrial Ethernet Switch



2700786

<https://www.phoenixcontact.com/us/products/2700786>

NBC-R4AC/5,0-93B/R4AC - Patch cable

1408970

<https://www.phoenixcontact.com/us/products/1408970>



Patch cable, degree of protection: IP20, cable length: 5 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com