

NLC-050-024X-08I-04QRX-05A - Base unit



2701056

<https://www.phoenixcontact.com/sk/products/2701056>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



24 V AC/DC Nanoline base unit. Equipped with 8 digital input and 4 relay output channels. Additional I/O channels can be added using a maximum of three I/O extension modules. Optional communication modules provide network or serial connectivity. Optional Operator Panel provides user interface. Programming is via nanoNavigator.

Your advantages

- An operating panel can be optionally integrated in the basic unit or installed on a wall in a decentralized manner
- Intuitive programming language with options for flowcharts and ladder diagrams
- Basic unit has integrated digital inputs, relay outputs, and analog inputs, including high-speed counters

Commercial data

Item number	2701056
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DRA
Product key	DRACAA
Catalog page	Page 463 (C-8-2015)
GTIN	4046356325356
Weight per piece (including packing)	320.4 g
Weight per piece (excluding packing)	320.4 g
Customs tariff number	85371098
Country of origin	IN

Technical data

Product properties

Product type	Base unit
Product family	Nanoline

System properties

INTERBUS-Master

Number of supported branch terminals with remote bus branch	3 (I/O modules)
---	-----------------

System requirements

Engineering tool	nanoNavigator 1 or 2
------------------	----------------------

Electrical properties

Supply

Supply voltage	24 V AC/DC (Power available to the I/O and Communications modules)
Supply voltage range	19 V DC ... 30 V DC
	19 V AC ... 26 V AC
Power supply connection	Screw connection
Max. current consumption	250 mA
Typical current consumption	150 mA (@ 24 V AC/DC)

Real-time clock

Realtime clock	Optional module
----------------	-----------------

Input data

Digital

Input name	Digital inputs
Description of the input	EN 61131-2 type 1 NPN/PNP
Number of inputs	8
Connection method	Screw connection
Input voltage range "0" signal	0 V AC/DC ... 5 V AC/DC
Input voltage range "1" signal	15 V AC/DC ... 30 V AC/DC
Nominal input voltage U_{IN}	24 V AC/DC
Nominal input current at U_{IN}	5 mA DC (On)
Typical response time	20 ms

Output data

Digital

Output name	Relay output
Output description	Relay output
Connection method	Screw connection

NLC-050-024X-08I-04QRX-05A - Base unit



2701056

<https://www.phoenixcontact.com/sk/products/2701056>

Number of outputs	4
Protective circuit	Short-circuit and overload protection
Maximum output current per channel	5 A
Maximum output current per module / terminal block	20 A
Maximum output current per module	5 A
Nominal load, ohmic	600 W (@ 24 ohms)
Maximum operating frequency with ohmic nominal load	0.5 Hz
Signal delay	10 ms (@ 20 °C (excludes bounce))
Output name	Relay output
Output description	Relay output
Connection method	Screw connection
Number of outputs	4
Protective circuit	Short-circuit and overload protection
Maximum output current per channel	5 A
Maximum output current per module / terminal block	20 A
Maximum output current per module	5 A
Nominal load, ohmic	600 W (@ 24 ohms)
Maximum operating frequency with ohmic nominal load	0.5 Hz
Signal delay	10 ms (@ 20 °C (excludes bounce))

Connection data

Connection method	Screw connection
-------------------	------------------

Interfaces

Operator Panel

Connection method	RJ45 / COMBICON
-------------------	-----------------

RS-232

Connection method	Slot 1
-------------------	--------


USB

Connection method	Slot 1
-------------------	--------

Realtime Clock

Connection method	Slot 2
-------------------	--------

Dimensions

Dimensional drawing	
Width	80.5 mm
Height	103.5 mm

NLC-050-024X-08I-04QRX-05A - Base unit



2701056

<https://www.phoenixcontact.com/sk/products/2701056>

Depth	60 mm
-------	-------

Material specifications

Color	black
-------	-------

Environmental and real-life conditions

Ambient conditions


Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	90 %
Permissible humidity (storage/transport)	90 %

Mounting


Mounting type	DIN rail mounting
---------------	-------------------

Drawings

Dimensional drawing



Connection diagram



NLC-050-024X-08I-04QRX-05A - Base unit



2701056

<https://www.phoenixcontact.com/sk/products/2701056>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sk/products/2701056>



UL Listed
Approval ID: FILE E 238705



cUL Listed
Approval ID: FILE E 238705

cULus Listed

NLC-050-024X-08I-04QRX-05A - Base unit



2701056

<https://www.phoenixcontact.com/sk/products/2701056>

Classifications

ECLASS

ECLASS-11.0	27242216
ECLASS-12.0	27242216
ECLASS-13.0	27242216

ETIM

ETIM 9.0	EC001417
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT s.r.o.
Námestie Mateja Korvína 1
811 07 Bratislava
+421 2 3210 1470
obchod.sk@phoenixcontact.com