

NLC-START-02 - Starter kit

2701425

<https://www.phoenixcontact.com/sk/products/2701425>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



24 V DC base unit with PNP transistor outputs, LCD display, USB module, serial cable, input and output simulators and Quick Start Guide

Product description

Kit containing items required to start programming and testing the Nanoline family of controllers.

Your advantages

- Basic unit
- USB cable
- Output simulator (available as 24 V AC or 24 V DC model)
- Input simulator (available as 24 V AC or 24 V DC model)
- Operating panel

Commercial data

Item number	2701425
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	DRA
Product key	DRACAZ
Catalog page	Page 473 (C-8-2015)
GTIN	4046356325530
Weight per piece (including packing)	808.3 g
Weight per piece (excluding packing)	771.1 g
Customs tariff number	85371098
Country of origin	US

NLC-START-02 - Starter kit

2701425

<https://www.phoenixcontact.com/sk/products/2701425>



Set consists of

NLC-050-024D-06I-04QTP-00A - Base unit

2701027

<https://www.phoenixcontact.com/sk/products/2701027>



24 V DC Nanoline base unit. Equipped with 6 digital input and 4 PNP digital output channels. Additional I/O channels can be added using a maximum of three I/O extension modules. Optional communication modules provide network or serial connectivity. Optional Operator Panel provides user interface. Programming is via nanoNavigator.

NLC-OP1-LCD-032-4X20 - Operator terminal

2701137

<https://www.phoenixcontact.com/sk/products/2701137>



User interface for Nanoline controllers. Mounts directly on the base unit. Can be mounted remotely using the mounting kit.

NLC-START-02 - Starter kit

2701425

<https://www.phoenixcontact.com/sk/products/2701425>



NLC-MOD-USB - nanoLC module

2701195

<https://www.phoenixcontact.com/sk/products/2701195>

Serial connection to PC's USB port for data transfer or software configuration



NLC-PC/USB-CBL 2M - Cable

2701247

<https://www.phoenixcontact.com/sk/products/2701247>

Cable, serial



NLC-START-02 - Starter kit

2701425

<https://www.phoenixcontact.com/sk/products/2701425>




NLC-050-24DC-IN-SIM - Simulator card

2701357

<https://www.phoenixcontact.com/sk/products/2701357>

Card to simulate inputs on an Nanoline base unit




NLC-050-24DC-OUT-SIM-T - Simulator card

2701360

<https://www.phoenixcontact.com/sk/products/2701360>

Card to simulate transistor outputs on a Nanoline base unit



NLC-START-02 - Starter kit

2701425

<https://www.phoenixcontact.com/sk/products/2701425>



Technical data

Product properties

Product type	Starter kit
--------------	-------------

NLC-START-02 - Starter kit



2701425

<https://www.phoenixcontact.com/sk/products/2701425>

Classifications

ECLASS

ECLASS-11.0	27242216
-------------	----------

ETIM

ETIM 8.0	EC001417
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT s.r.o.
Námestie Mateja Korvína 1
811 07 Bratislava
+421 2 3210 1470
obchod.sk@phoenixcontact.com