

# FL SWITCH SMCS 14TX/2FX-SM - Industrial Ethernet Switch



2701466

<https://www.phoenixcontact.com/us/products/2701466>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Ethernet Smart Managed Compact Switch with 14 10/100 Mbps RJ45 ports and two 100 Mbps FX-SC single mode ports



## Product description

The Smart Managed Compact Switch (SMCS) is an Ethernet switch suitable for industrial applications with 14 Fast Ethernet ports in RJ45 format and two fiber optic ports in SC single mode format.

## Your advantages

- RSTP
- SNMP
- VLANs
- MRP (client and manager)
- Web-based management, SNMP
- Extended temperature rating

## Commercial data

Item number	2701466
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	DN17
Product key	DNN122
Catalog page	Page 323 (C-6-2019)
GTIN	4046356759991
Weight per piece (including packing)	1,330 g
Weight per piece (excluding packing)	1,330 g
Customs tariff number	85176200
Country of origin	DE

# FL SWITCH SMCS 14TX/2FX-SM - Industrial Ethernet Switch



2701466

<https://www.phoenixcontact.com/us/products/2701466>

## Technical data

### Dimensions

Width	214 mm
Height	110 mm
Depth	69 mm

### Material specifications

Color	gray aluminum
-------	---------------

### Mounting

Mounting type	DIN rail mounting
---------------	-------------------

### Interfaces

#### Ethernet (RJ45)

Connection method	RJ45
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100 Mbps
Transmission physics	Copper
Transmission length	100 m (per segment)
Signal LEDs	Supply voltage, data transmission, error, link, activity
No. of channels	14 (RJ45 ports)

#### Ethernet FO

Connection method	SC
Transmission speed	100 Mbps (full duplex)
Transmission physics	Single-mode fiberglass
Transmission length	36000 m (fiberglass with F-G 9/125 0.36 dB/km) 32000 m (fiberglass with F-G 9/125 0.4 dB/km) 26000 m (fiberglass with F-G 9/125 0.5 dB/km)
Wavelength	1310 nm
No. of channels	2 (SC single mode)

#### Serial (RS-232)

Connection method	RS-232-C, 6-pos. MINI-DIN socket (PS/2)
-------------------	---

### Product properties

Type	Block design
Product type	Switch
Product family	Managed Switch SMCS
MTTF	286.27 Years (SN 29500 standard, temperature 25°C, operating cycle 21%) 149.5 Years (SN 29500 standard, temperature 40°C, operating cycle 34.25%)

# FL SWITCH SMCS 14TX/2FX-SM - Industrial Ethernet Switch



2701466

<https://www.phoenixcontact.com/us/products/2701466>

	21.69 Years (SN 29500 standard, temperature 70°C, operating cycle 100%)
<b>Insulation characteristics</b>	
Protection class	III (VDE 0106)
<b>Switch functions</b>	
Diagnostic functions	RMON History
	N:1-Portmirroring
	LLDP (Link Layer Discovery Protocol)
	SNMP-Traps
	ACD (Address Conflict Detection)
Basic functions	Store-and-forward switch complies with IEEE 802.3 4 priority classes in acc. with IEEE 802.1 P TCP/IP protocol, BootP-capable, port-mirroring, integrated web server function, multicast filtering, IGMP snooping, VLAN, Rapid Spanning Tree (RSTP), PROFINET Device, Media Redundancy Protocol (MRP).
Signal contact control voltage	24 V (typical)
Signal contact control current	260 mA (maximum)
PROFINET conformance class	Conformance-Class B
PROFINET device function	PROFINET device
	Fast Startup
Filter functions	Quality of Service (4 priority classes)
	Port-Priorisierung
	VLAN
	IGMP Snooping (128 groups)
	IGMP Query
	Auto-Query-Port
	Extended Multicast Filtering
	Static Multicast Filtering
MAC address table	16000
Management	Web-based management (HTTP)
	SNMP v1/v2
	Serial interface (V.24)
Redundancy	MRP (Media Redundancy Protocol)
	RSTP (Rapid Spanning Tree Protocol)
	FRD (Fast Ring Detection)
	Large Tree Support
Status and diagnostic indicators	LEDs: US1, US2 (power supply), Fail (alarm contact), 2 LEDs per Ethernet port (Link and switchable Activity/Speed/Duplex)
Supported browsers	Internet Explorer 5.5 or higher
Additional functions	BootP
	DHCP-Client
Time synchronization	SNTP
<b>Security functions</b>	
Basic functions	Store-and-forward switch complies with IEEE 802.3 4 priority

# FL SWITCH SMCS 14TX/2FX-SM - Industrial Ethernet Switch



2701466

<https://www.phoenixcontact.com/us/products/2701466>

	classes in acc. with IEEE 802.1 P TCP/IP protocol, BootP-capable, port-mirroring, integrated web server function, multicast filtering, IGMP snooping, VLAN, Rapid Spanning Tree (RSTP), PROFINET Device, Media Redundancy Protocol (MRP).
Link Layer Discovery Protocol (LLDP)	As per protocol 802.2

## Electrical properties

Maximum power dissipation for nominal condition	6.24 W
Test voltage	500 V DC
Test section	for one minute 500 V DC
Transmission medium	Copper FO

## Supply

Supply voltage (DC)	24 V DC (redundant)
Supply voltage range	18 V DC ... 32 V DC
Power supply connection	Via COMBICON, max. conductor cross section 2.5 mm <sup>2</sup>
Residual ripple	3.6 V <sub>pp</sub> (within the permitted voltage range)
Typical current consumption	290 mA (at U <sub>S</sub> = 24 V DC)
Current consumption	260 mA

## Function

Signal contact control voltage	24 V (typical)
Signal contact control current	260 mA (maximum)

## Connection data

Connection method	Screw connection
Conductor cross section, rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section, flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12
Stripping length	7 mm

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 70 °C (non-condensing)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Vibration (operation)	in acc. with IEC 60068-2-6: 5g, 150 Hz
Air pressure (operation)	86 kPa ... 108 kPa (2000 m above mean sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)

## Standards and regulations

Free from substances that could impair the application of coating	Yes
---	-----

# FL SWITCH SMCS 14TX/2FX-SM - Industrial Ethernet Switch



2701466

<https://www.phoenixcontact.com/us/products/2701466>

## EMC data

Conformance with EMC directives	IEC 61000-6-2 IEC 61000-4-2 (ESD) Criterion B
	IEC 61000-4-3 (electromagnetic fields) Criterion A
	IEC 61000-4-4 (burst) Criterion B
	IEC 61000-4-5 (surge) Criterion B
	IEC 61000-4-6 (immunity to conducted interference) Criterion A
Noise immunity	EN 61000-6-2:2005
Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
Noise emission	EN 61000-6-3

## System properties

### Functionality

Basic functions	Store-and-forward switch complies with IEEE 802.3 4 priority classes in acc. with IEEE 802.1 P TCP/IP protocol, BootP-capable, port-mirroring, integrated web server function, multicast filtering, IGMP snooping, VLAN, Rapid Spanning Tree (RSTP), PROFINET Device, Media Redundancy Protocol (MRP).
-----------------	--

### System requirements

Supported browsers	Internet Explorer 5.5 or higher
--------------------	---------------------------------

## Signaling

Status display	LEDs: US1, US2 (power supply), Fail (alarm contact), 2 LEDs per Ethernet port (Link and switchable Activity/Speed/Duplex)
----------------	---

# FL SWITCH SMCS 14TX/2FX-SM - Industrial Ethernet Switch



2701466

<https://www.phoenixcontact.com/us/products/2701466>

## Classifications

### UNSPSC

UNSPSC 21.0	43222612
-------------	----------

# FL SWITCH SMCS 14TX/2FX-SM - Industrial Ethernet Switch



2701466

<https://www.phoenixcontact.com/us/products/2701466>

## Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)