


IB IL RS 485-ECO - Communication module



2702141

<https://www.phoenixcontact.com/pc/products/2702141>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Inline, Communication terminal, interface RS-485: 1, Communication via process data, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector

Product description

The terminal is designed for use within an Inline station. The terminal is used to operate standard I/O devices with serial interfaces on a bus system. Inline ECO terminals are approved for the temperature range from 0°C to +55°C. The electronics base and Inline connector are supplied as standard.

Your advantages

- One serial input and output channel in RS-485 format
- Data is transmitted in transparent mode
- Transmission speed can be set up to 38400 bps
- Number of data bits, stop bits and parity can be set
- Parameterization and data exchange via process data

Commercial data

Item number	2702141
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DRI151
Catalog page	Page 121 (C-6-2019)
GTIN	4046356983235
Weight per piece (including packing)	84.1 g
Weight per piece (excluding packing)	84.1 g
Customs tariff number	85389099
Country of origin	DE

Technical data

Dimensions

Dimensional drawing	
Width	12.2 mm
Height	119.8 mm
Depth	71.5 mm

Interfaces

Inline local bus

Number of interfaces	2
Connection method	Inline data jumper
Transmission speed	500 kbps

RS-485

Number of interfaces	1
Connection method	Spring-cage connection
Note on the connection method	Use shielded cables.
Transmission speed	110 bps ... 38400 bps (can be parameterized)
Transmission physics	Copper
Protocols supported	Transparent
Termination resistor	typ. 120 Ω (active, integrated)
Data bits	6 ... 8
Stop bits	1 or 2
Input buffer	4 kByte
Output buffer	1 kByte

System properties

Module

ID code (dec.)	191
ID code (hex)	BF
Length code (hex)	07
Length code (dec)	07
Process data channel	112 bit
Input address area	14 Byte
Output address area	14 Byte
Register length	112 bit

IB IL RS 485-ECO - Communication module



2702141

<https://www.phoenixcontact.com/pc/products/2702141>

Required parameter data	16 Byte
Required configuration data	5 Byte

Product properties

Product type	I/O component
Product family	Inline
Type	modular
Scope of delivery	including Inline connector
Special properties	Communication via process data

Insulation characteristics

Overvoltage category	II (IEC 60664-1, EN 60664-1)
Pollution degree	2 (IEC 60664-1, EN 60664-1)

Electrical properties

Maximum power dissipation for nominal condition	max. 0.7 W
---	------------

Potentials

Power consumption	max. 0.7 W (at U_L , within the permissible operating temperature)
-------------------	--

Potentials: Communications power (U_L)

Supply voltage	7.5 V DC (via voltage jumper)
Current draw	max. 85 mA
	typ. 70 mA
Power consumption	typ. 525 mW

Electrical isolation/isolation of the voltage ranges

Test voltage: Serial interface/7.5 V supply (bus logic)	500 V AC, 50 Hz, 1 min.
Test voltage: Serial interface/24 V supply U_M	500 V AC, 50 Hz, 1 min.
Test voltage: Serial interface/functional ground	500 V AC, 50 Hz, 1 min.
Test voltage: 7.5 V supply (bus logic)/functional ground	500 V AC, 50 Hz, 1 min.
Test voltage: 24 V supply (U_M)/functional ground	500 V AC, 50 Hz, 1 min.

Connection data

Connection technology

Connection name	Inline connector
-----------------	------------------

Conductor connection

Connection method	Spring-cage connection
Conductor cross section rigid	0.08 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.08 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

Inline connector

Connection method	Spring-cage connection
Conductor cross section, rigid	0.08 mm ² ... 1.5 mm ²

IB IL RS 485-ECO - Communication module



2702141

<https://www.phoenixcontact.com/pc/products/2702141>

Conductor cross section, flexible	0.08 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	0 °C ... 55 °C
Degree of protection	IP20
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

Standards and regulations

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------


IB IL RS 485-ECO - Communication module

2702141

<https://www.phoenixcontact.com/pc/products/2702141>

Drawings

Dimensional drawing




Dimensions

IB IL RS 485-ECO - Communication module

2702141

<https://www.phoenixcontact.com/pc/products/2702141>

Block diagram




Internal wiring of the terminal points

IB IL RS 485-ECO - Communication module

2702141


<https://www.phoenixcontact.com/pc/products/2702141>

Connection diagram



Inline terminal as network end point

Connection diagram



Inline terminal in the network center

2702141

<https://www.phoenixcontact.com/pc/products/2702141>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2702141>



UL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705

UAE-RoHS

Approval ID: 22-04-13090

cULus Listed

2702141

<https://www.phoenixcontact.com/pc/products/2702141>

Classifications

ECLASS

ECLASS-11.0	27242605
ECLASS-12.0	27242605
ECLASS-13.0	27242608

ETIM

ETIM 9.0	EC001601
----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

IB IL RS 485-ECO - Communication module



2702141

<https://www.phoenixcontact.com/pc/products/2702141>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com