PLD E 400-DS-MS/1,0-FS/0,6 - Door position switch

2702337

https://www.phoenixcontact.com/us/products/2702337

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Door position switch with 1 m cable with M8 plug and 0.6 m cable with M8 socket (Snap-in), including mounting accessories

Product description

This door position switch is used to automatically switch the class 400 PLD enclosure lights on or off when opening or closing the control cabinet door. If the enclosure lights are connected in series, this door position switch is only to be used from the second light onward.

Commercial data

Item number	2702337
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	DRL23Z
Catalog page	Page 499 (C-6-2019)
GTIN	4055626127460
Weight per piece (including packing)	145.1 g
Weight per piece (excluding packing)	145.1 g
Customs tariff number	85365080
Country of origin	HU

# PLD E 400-DS-MS/1,0-FS/0,6 - Door position switch

2702337

https://www.phoenixcontact.com/us/products/2702337

Technical data

Product properties

Product type	Door position switch
Mounting position	any
Mechanical service life	10×10^6 cycles

Electrical properties

Rated voltage	24 V DC
Rated current	3 A

Dimensions

Dimensional drawing	
Width	31 mm
Height	30.5 mm
Depth	98.3 mm
Note on dimensions	Without connected cables

Material specifications

Color	black
Material	Thermoplastic, fiber-reinforced
	PUR

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP54
Ambient temperature (operation)	-30 °C ... 80 °C

Standards and regulations

Protection class	II

Mounting

Mounting position	any

PLD E 400-DS-MS/1,0-FS/0,6 - Door position switch

2702337

https://www.phoenixcontact.com/us/products/2702337