

# GW DEVICE SERVER 2E/4DB9 - Interface converters



2702763

<https://www.phoenixcontact.com/us/products/2702763>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Serial device server for converting serial data (RS-232/422/485) to Ethernet data (RJ45). Supports TCP and UDP protocols. COM port redirector software and Windows drivers are available for download. Includes two RJ45 ports and four D-SUB 9 ports.

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2702763             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | DN11                |
| Product key                          | DNC321              |
| Catalog page                         | Page 355 (C-6-2019) |
| GTIN                                 | 4055626339184       |
| Weight per piece (including packing) | 246 g               |
| Weight per piece (excluding packing) | 195 g               |
| Customs tariff number                | 85176200            |
| Country of origin                    | US                  |

## Technical data

### Notes

#### Utilization restriction

|          |                                                                           |
|----------|---------------------------------------------------------------------------|
| EMC note | EMC: class A product, see manufacturer's declaration in the download area |
|----------|---------------------------------------------------------------------------|

#### Utilization restriction

|            |                                                               |
|------------|---------------------------------------------------------------|
| CCCex note | Use in potentially explosive areas is not permitted in China. |
|------------|---------------------------------------------------------------|

### Product properties

|              |                                                                                           |
|--------------|-------------------------------------------------------------------------------------------|
| Product type | Interface converter                                                                       |
| MTBF         | 63.5 Years (Telcordia standard, 25°C temperature, 50% stress, Environmental Factor = 1.0) |
|              | 42.3 Years (Telcordia standard, 40°C temperature, 50% stress, Environmental Factor = 1.5) |

### Electrical properties

|                                            |                                       |
|--------------------------------------------|---------------------------------------|
| Electrical isolation                       | IEC UL 61010-1 (VCC // Ethernet)      |
| Test voltage data interface/data interface | 1.5 kV <sub>rms</sub> (50 Hz, 1 min.) |
| Test voltage data interface/power supply   | 1.5 kV <sub>rms</sub> (50 Hz, 1 min.) |
|                                            | 1.5 kV <sub>rms</sub>                 |

#### Supply

|                             |                                                                     |
|-----------------------------|---------------------------------------------------------------------|
| Supply voltage range        | 10.8 V DC ... 30 V DC (via pluggable COMBICON screw terminal block) |
| Typical current consumption | 110 mA (24 V DC)                                                    |
| Max. current consumption    | 120 mA (24 V DC)                                                    |

#### Function

|                                  |                                               |
|----------------------------------|-----------------------------------------------|
| Management                       | Web-based management                          |
| Status and diagnostic indicators | LEDs: Status, ACT/LNK (Ethernet data traffic) |

### Connection data

#### Supply

|                                   |                                               |
|-----------------------------------|-----------------------------------------------|
| Conductor cross section, flexible | 0.20 mm <sup>2</sup> ... 2.50 mm <sup>2</sup> |
| Conductor cross section AWG       | 24 ... 12                                     |
| Tightening torque                 | 0.5 Nm ... 0.6 Nm                             |

### Interfaces

|            |          |
|------------|----------|
| Signal     | Ethernet |
| Web server | yes      |

Data: Ethernet interface, 10/100Base-T(X) in accordance with IEEE 802.3

|                           |                               |
|---------------------------|-------------------------------|
| Serial transmission speed | 10/100 Mbps, auto negotiation |
| Connection method         | RJ45 jack, shielded           |

# GW DEVICE SERVER 2E/4DB9 - Interface converters



2702763

<https://www.phoenixcontact.com/us/products/2702763>

|                     |                                 |
|---------------------|---------------------------------|
| No. of channels     | 2                               |
| Transmission length | ≤ 100 m (shielded twisted pair) |
| Protocols supported | TCP/IP, UDP, ASCII              |
| Auxiliary protocols | ARP, DHCP (Client), PING        |

## Data: RS-232

|                             |                                                                   |
|-----------------------------|-------------------------------------------------------------------|
| Serial transmission speed   | 0.3; 0.6; 1.2; 2.4; 4.8; 9.6; 19.2; 38.4; 57.6; 115.2; 230.4 Kbps |
| Number of connections       | 4                                                                 |
| Connection method           | D-SUB 9 plug                                                      |
| Pin assignment              | DTE                                                               |
| Transmission length         | 15 m                                                              |
| File format/coding          | 5/6/7/8 Data bits, 1/2 Stop bits, None/Even/Odd/Mark/Space Parity |
| Data flow control/protocols | Software handshake, Xon/Xoff or hardware handshake RTS/CTS        |

## Data: RS-422

|                           |                                                                   |
|---------------------------|-------------------------------------------------------------------|
| Serial transmission speed | 0.3; 0.6; 1.2; 2.4; 4.8; 9.6; 19.2; 38.4; 57.6; 115.2; 230.4 Kbps |
| Number of connections     | 4                                                                 |
| Connection method         | D-SUB 9 plug                                                      |
| Pin assignment            | 2, 3, 5, 7, 8                                                     |
| Transmission length       | ≤ 1200 m                                                          |
| Termination resistor      | 120 Ω (configurable)                                              |
| File format/coding        | 5/6/7/8 Data bits, 1/2 Stop bits, None/Even/Odd/Mark/Space Parity |

## Data: RS-485

|                           |                                                                   |
|---------------------------|-------------------------------------------------------------------|
| Serial transmission speed | 0.3; 0.6; 1.2; 2.4; 4.8; 9.6; 19.2; 38.4; 57.6; 115.2; 230.4 Kbps |
| Number of connections     | 4                                                                 |
| Connection method         | D-SUB 9 plug                                                      |
| Pin assignment            | 3, 5, 7                                                           |
| Termination resistor      | 120 Ω (configurable)                                              |
| File format/coding        | 5/6/7/8 Data bits, 1/2 Stop bits, None/Even/Odd/Mark/Space Parity |

## Dimensions

|        |        |
|--------|--------|
| Width  | 45 mm  |
| Height | 99 mm  |
| Depth  | 115 mm |

## Material specifications

|                  |        |
|------------------|--------|
| Color            | gray   |
| Housing material | PA 6.6 |

## Environmental and real-life conditions

### Ambient conditions

|                      |      |
|----------------------|------|
| Degree of protection | IP20 |
|----------------------|------|

2702763

<https://www.phoenixcontact.com/us/products/2702763>

|                                          |                                |
|------------------------------------------|--------------------------------|
| Ambient temperature (operation)          | -40 °C ... 70 °C               |
| Ambient temperature (storage/transport)  | -40 °C ... 80 °C               |
| Altitude                                 | < 2000 m                       |
| Permissible humidity (operation)         | 10 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing)  |

## Approvals

### Conformity/Approvals

|                  |                                        |
|------------------|----------------------------------------|
| Conformance      | CE-compliant                           |
| UL, USA          | UL 61010-1                             |
| UL, USA / Canada | Class I, Div. 2, Groups A, B, C, D T4A |
| Noxious gas test | ISA-S71.04-1985 G3 Harsh Group A       |

### Ex data

|       |                                               |
|-------|-----------------------------------------------|
| ATEX  | DEMKO 18ATEX 2026X: II 3 G<br>Ex ec IIC T4 Gc |
| IECEX | IECEX UL 18.0023X<br>Ex ec IIC T4 Gc          |

## EMC data

|                               |                                           |
|-------------------------------|-------------------------------------------|
| Noise immunity                | EN 61000-6-2:2005                         |
| Electromagnetic compatibility | Conformance with EMC Directive 2014/30/EU |
| Noise emission                | EN 61000-6-4                              |

## Standards and regulations

|                       |                    |
|-----------------------|--------------------|
| Standards/regulations | EN 55022, EN 55024 |
|-----------------------|--------------------|

## Mounting

|               |                   |
|---------------|-------------------|
| Mounting type | DIN rail mounting |
|---------------|-------------------|

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)