

# Specifications



Photo is representative



## Eaton 271106

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 250A, N, frame2, A250-NA

### General specifications

|                             |                                                                                                                                                                                                                                                                                  |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller series NZM molded case circuit breaker thermo-magnetic                                                                                                                                                                                                             |
| <b>CATALOG NUMBER</b>       | 271106                                                                                                                                                                                                                                                                           |
| <b>MODEL CODE</b>           | NZMN2-A250-NA                                                                                                                                                                                                                                                                    |
| <b>EAN</b>                  | 4015082711061                                                                                                                                                                                                                                                                    |
| <b>PRODUCT LENGTH/DEPTH</b> | 149 mm                                                                                                                                                                                                                                                                           |
| <b>PRODUCT HEIGHT</b>       | 195 mm                                                                                                                                                                                                                                                                           |
| <b>PRODUCT WIDTH</b>        | 105 mm                                                                                                                                                                                                                                                                           |
| <b>PRODUCT WEIGHT</b>       | 2.438 kg                                                                                                                                                                                                                                                                         |
| <b>COMPLIANCES</b>          | RoHS conform                                                                                                                                                                                                                                                                     |
| <b>CERTIFICATIONS</b>       | IEC<br>UL listed<br>CSA certified<br>IEC/EN 60947<br>UL/CSA<br>UL (Category Control Number DIVQ)<br>IEC 60947-2<br>UL 489<br>CSA (File No. 22086)<br>CE marking<br>CSA (Class No. 1432-01)<br>Specially designed for North America<br>CSA-C22.2 No. 5-09<br>UL (File No. E31593) |

## Product specifications

|                                                                                         |                                                                                                                                  |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>AMPERAGE RATING</b>                                                                  | 250 A                                                                                                                            |
| <b>VOLTAGE RATING</b>                                                                   | 690 V - 690 V                                                                                                                    |
| <b>CIRCUIT BREAKER FRAME TYPE</b>                                                       | NZM2                                                                                                                             |
| <b>FEATURES</b>                                                                         | Protection unit<br>Motor drive optional                                                                                          |
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                                                       | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                                              | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>                                                        | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                                                                                       |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.                                                                                       |
| <b>10.2.5 LIFTING</b>                                                                   | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.6 MECHANICAL IMPACT</b>                                                         | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.7 INSCRIPTIONS</b>                                                              | Meets the product standard's requirements.                                                                                       |

## Resources

|                                   |                                                                                                                                                                                                                                                                                                                     |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>BROCHURES</b>                  | <a href="#">eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf</a><br><a href="#">eaton-digital-nzm-brochure-br013003en-en-us.pdf</a>                                                                                                                                                                    |
| <b>CATALOGUES</b>                 | <a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-039.eps</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-050.eps</a><br><a href="#">eaton-circuit-breaker-current-nzm-mccb-characteristic-curve-004.eps</a> |
| <b>CHARACTERISTIC CURVE</b>       | <a href="#">eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250290en.pdf</a>                                                                                                                                                                                                                          |
| <b>DECLARATIONS OF CONFORMITY</b> | <a href="#">eaton-circuit-breaker-switch-nzm-mccb-dimensions-017.eps</a>                                                                                                                                                                                                                                            |
| <b>DRAWINGS</b>                   | <a href="#">eaton-circuit-breaker-nzm-mccb-dimensions-019.eps</a><br><a href="#">eaton-circuit-breaker-switch-nzm-mccb-3d-drawing.eps</a>                                                                                                                                                                           |
| <b>ECAD MODEL</b>                 | <a href="#">ETN.271106.edz</a>                                                                                                                                                                                                                                                                                      |
| <b>INSTALLATION INSTRUCTIONS</b>  | <a href="#">eaton-circuit-breakers-basic-device-nzm2-il01206006z.pdf</a>                                                                                                                                                                                                                                            |
| <b>INSTALLATION VIDEOS</b>        | <a href="#">The new digital NZM Range</a><br><a href="#">Introduction of the new digital circuit breaker NZM</a>                                                                                                                                                                                                    |
| <b>MCAD MODEL</b>                 | <a href="#">DA-CD-nzm2_3p</a><br><a href="#">DA-CS-nzm2_3p</a>                                                                                                                                                                                                                                                      |
| <b>TECHNICAL DATA SHEETS</b>      | <a href="#">eaton-nzm-technical-information-sheet</a>                                                                                                                                                                                                                                                               |

|                                                                 |                                                                                                      |
|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                  | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                   | Meets the product standard's requirements.                                                           |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.                                                               |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.                                                               |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.                                                               |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.                                                               |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.                                                               |
| <b>POLLUTION DEGREE</b>                                         | 3                                                                                                    |
| <b>MOUNTING METHOD</b>                                          | Fixed<br>DIN rail (top hat rail)<br>mounting optional<br>Built-in device fixed built-in technique    |
| <b>CLIMATIC PROOFING</b>                                        | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30                       |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>            | 58.13 W                                                                                              |
| <b>UTILIZATION CATEGORY</b>                                     | A (IEC/EN 60947-2)                                                                                   |
| <b>ISOLATION</b>                                                | 500 V AC (between auxiliary contacts and main contacts)<br>300 V AC (between the auxiliary contacts) |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                      | 70 °C                                                                                                |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                      | -25 °C                                                                                               |
| <b>AMBIENT STORAGE TEMPERATURE - MAX</b>                        | 70 °C                                                                                                |
| <b>AMBIENT STORAGE TEMPERATURE - MIN</b>                        | 40 °C                                                                                                |
| <b>LOW-VOLTAGE HBC FUSE</b>                                     | 355 A gG/gL                                                                                          |

|                                                                |                                                                                                                                                                                                                      |
|----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>- MAX</b>                                                   |                                                                                                                                                                                                                      |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>     | 0                                                                                                                                                                                                                    |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b> | 0                                                                                                                                                                                                                    |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>   | 0                                                                                                                                                                                                                    |
| <b>PROTECTION AGAINST DIRECT CONTACT</b>                       | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110                                                                                                                                                      |
| <b>CONNECTION</b>                                              | Front screw                                                                                                                                                                                                          |
| <b>DEGREE OF PROTECTION</b>                                    | IP20<br>IP20 (basic degree of protection, in the operating controls area)                                                                                                                                            |
| <b>DIRECTION OF INCOMING SUPPLY</b>                            | As required                                                                                                                                                                                                          |
| <b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>              | Screw connection                                                                                                                                                                                                     |
| <b>LIFESPAN, MECHANICAL</b>                                    | 20000 operations                                                                                                                                                                                                     |
| <b>OVERVOLTAGE CATEGORY</b>                                    | III                                                                                                                                                                                                                  |
| <b>RATED OPERATIONAL CURRENT</b>                               | 300 A (415 V AC-1, making and breaking capacity)<br>250 A (660-690 V AC-3, making and breaking capacity)<br>250 A (690 V AC-1, making and breaking capacity)<br>300 A (380/400 V AC-1, making and breaking capacity) |
| <b>DEGREE OF PROTECTION (IP), FRONT SIDE</b>                   | IP40 (with insulating surround)<br>IP66 (with door coupling rotary handle)                                                                                                                                           |
| <b>DEGREE OF PROTECTION (TERMINATIONS)</b>                     | IP00 (terminations, phase isolator and strip terminal)<br>IP10 (tunnel terminal)                                                                                                                                     |
| <b>NUMBER OF POLES</b>                                         | Three-pole                                                                                                                                                                                                           |
| <b>TERMINAL CAPACITY (COPPER STRIP)</b>                        | Min. 2 segments of 9 mm x 0.8 mm at box terminal<br>Max. 10 segments of 16 mm x 0.8 mm at box terminal<br>Max. 10 segments of 16 mm x 0.8 mm at rear-side connection (punched)<br>Min. 2 segments of 16              |

|                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                        | mm x 0.8 mm at rear-side connection (punched)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>LIFESPAN, ELECTRICAL</b>                            | 10000 operations at 400 V AC-1<br>7500 operations at 690 V AC-1<br>5000 operations at 690 V AC-3<br>6500 operations at 415 V AC-3<br>6500 operations at 400 V AC-3                                                                                                                                                                                                                                                                                                                                                              |
| <b>FUNCTIONS</b>                                       | System and cable protection<br>Current limiting circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>TYPE</b>                                            | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>SPECIAL FEATURES</b>                                | <ul style="list-style-type: none"> <li>• Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity <math>I_{cn}</math>)</li> <li>• Rated current = rated uninterrupted current: 250 A</li> <li>• Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate.</li> <li>• Adjustable overload releases <math>I_r</math></li> </ul> |
| <b>APPLICATION</b>                                     | <ul style="list-style-type: none"> <li>• Branch circuits, feeder circuits</li> <li>• Use in unearthed supply systems at 690 V</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>SHOCK RESISTANCE</b>                                | 20 g (half-sinusoidal shock 20 ms)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT</b> | Front side                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

|                                                                              |                                                                                                                                                                                                                                   |
|------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>RATED OPERATIONAL<br/>CURRENT FOR SPECIFIED<br/>HEAT DISSIPATION (IN)</b> | 250 A                                                                                                                                                                                                                             |
| <b>POWER LOSS</b>                                                            | 58.1 W                                                                                                                                                                                                                            |
| <b>RELEASE SYSTEM</b>                                                        | Thermomagnetic release                                                                                                                                                                                                            |
| <b>SHORT-CIRCUIT TOTAL<br/>BREAKTIME</b>                                     | < 10 ms                                                                                                                                                                                                                           |
| <b>RATED SHORT-TIME<br/>WITHSTAND CURRENT (T<br/>= 0.3 S)</b>                | 1.9 kA                                                                                                                                                                                                                            |
| <b>RATED SHORT-TIME<br/>WITHSTAND CURRENT (T<br/>= 1 S)</b>                  | 1.9 kA                                                                                                                                                                                                                            |
| <b>SHORT-CIRCUIT RELEASE<br/>NON-DELAYED SETTING -<br/>MAX</b>               | 2500 A                                                                                                                                                                                                                            |
| <b>SHORT-CIRCUIT RELEASE<br/>NON-DELAYED SETTING -<br/>MIN</b>               | 1500 A                                                                                                                                                                                                                            |
| <b>TERMINAL CAPACITY<br/>(CONTROL CABLE)</b>                                 | 16 mm <sup>2</sup> - 18 mm <sup>2</sup> (2x)<br>14 mm <sup>2</sup> - 18 mm <sup>2</sup> (1x)                                                                                                                                      |
| <b>TERMINAL CAPACITY<br/>(COPPER BUSBAR)</b>                                 | Max. 20 mm x 5 mm direct<br>at switch rear-side<br>connection<br>Min. 16 mm x 5 mm direct<br>at switch rear-side<br>connection<br>M8 at rear-side screw<br>connection                                                             |
| <b>TERMINAL CAPACITY<br/>(COPPER SOLID<br/>CONDUCTOR/CABLE)</b>              | 16 mm <sup>2</sup> (1x) at tunnel<br>terminal<br>6 mm <sup>2</sup> - 11 mm <sup>2</sup> (1x) direct<br>at switch rear-side<br>connection<br>6 mm <sup>2</sup> - 12 mm <sup>2</sup> (1x) at<br>box terminal                        |
| <b>TERMINAL CAPACITY<br/>(ALUMINUM SOLID<br/>CONDUCTOR/CABLE)</b>            | 16 mm <sup>2</sup> (1x) at tunnel<br>terminal                                                                                                                                                                                     |
| <b>TERMINAL CAPACITY<br/>(COPPER STRANDED<br/>CONDUCTOR/CABLE)</b>           | 4 mm <sup>2</sup> - 350 mm <sup>2</sup> (1x) at<br>tunnel terminal<br>4 mm <sup>2</sup> - 350 mm <sup>2</sup> (1x) at<br>box terminal<br>4 mm <sup>2</sup> - 3/0 mm <sup>2</sup> (1x)<br>direct at switch rear-side<br>connection |
| <b>HANDLE TYPE</b>                                                           | Rocker lever                                                                                                                                                                                                                      |
| <b>SHORT DELAY CURRENT<br/>SETTING (ISD) - MAX</b>                           | 0 A                                                                                                                                                                                                                               |
| <b>SHORT DELAY CURRENT<br/>SETTING (ISD) - MIN</b>                           | 0 A                                                                                                                                                                                                                               |
| <b>INSTANTANEOUS<br/>CURRENT SETTING (II) -</b>                              | 2500 A                                                                                                                                                                                                                            |

|                                                                                                    |                   |
|----------------------------------------------------------------------------------------------------|-------------------|
| <b>MAX</b>                                                                                         |                   |
| <b>INSTANTANEOUS<br/>CURRENT SETTING (II) -<br/>MIN</b>                                            | 1500 A            |
| <b>NUMBER OF<br/>OPERATIONS PER HOUR -<br/>MAX</b>                                                 | 120               |
| <b>OVERLOAD CURRENT<br/>SETTING (IR) - MAX</b>                                                     | 250 A             |
| <b>OVERLOAD CURRENT<br/>SETTING (IR) - MIN</b>                                                     | 200 A             |
| <b>RATED SHORT-CIRCUIT<br/>BREAKING CAPACITY ICS<br/>(IEC/EN 60947) AT 230 V,<br/>50/60 HZ</b>     | 85 kA             |
| <b>RATED SHORT-CIRCUIT<br/>BREAKING CAPACITY ICS<br/>(IEC/EN 60947) AT<br/>400/415 V, 50/60 HZ</b> | 50 kA             |
| <b>RATED SHORT-CIRCUIT<br/>BREAKING CAPACITY ICS<br/>(IEC/EN 60947) AT 440 V,<br/>50/60 HZ</b>     | 35 kA             |
| <b>RATED SHORT-CIRCUIT<br/>BREAKING CAPACITY ICS<br/>(IEC/EN 60947) AT 525 V,<br/>50/60 HZ</b>     | 25 kA             |
| <b>RATED SHORT-CIRCUIT<br/>BREAKING CAPACITY ICS<br/>(IEC/EN 60947) AT 690 V,<br/>50/60 HZ</b>     | 5 kA              |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 400/415 V, 50/60 HZ</b>                      | 105 kA            |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 440 V, 50/60 HZ</b>                          | 74 kA             |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 525 V, 50/60 HZ</b>                          | 53 kA             |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 690 V, 50/60 HZ</b>                          | 40 kA             |
| <b>STANDARD TERMINALS</b>                                                                          | Screw terminal    |
| <b>RATED OPERATING<br/>VOLTAGE UE (UL) - MAX</b>                                                   | 600Y/347 V, 480 V |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 240 V, 50/60 HZ</b>                          | 187 kA            |
| <b>RATED IMPULSE<br/>WITHSTAND VOLTAGE<br/>(UIMP) AT AUXILIARY<br/>CONTACTS</b>                    | 6000 V            |

|                                                                            |           |
|----------------------------------------------------------------------------|-----------|
| <b>RATED IMPULSE<br/>WITHSTAND VOLTAGE<br/>(UIMP) AT MAIN<br/>CONTACTS</b> | 8000 V    |
| <b>RATED INSULATION<br/>VOLTAGE (UI)</b>                                   | 1000 V AC |

|                        |
|------------------------|
| <b>PROJECT NAME:</b>   |
| <b>PROJECT NUMBER:</b> |
| <b>PREPARED BY:</b>    |
| <b>DATE:</b>           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

