

Specifications



Photo is representative

Eaton 271447

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, black, lockable, size 3, NA type

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element NA
CATALOG NUMBER	271447
MODEL CODE	NZM3-XTVD-NA
EAN	4015082714475
PRODUCT LENGTH/DEPTH	100 mm
PRODUCT HEIGHT	230 mm
PRODUCT WIDTH	120 mm
PRODUCT WEIGHT	1.382 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	IEC60947 UL489 UL (Category Control Number DIHS) CSA-C22.2 No. 5-09 CSA (File No. 22086) UL (File No. E140305) CE marking CSA (Class No. 1437-01) UL listed CSA certified
GLOBAL CATALOG	271447

Product specifications

USED WITH	NZM3, N3
FEATURES	Lockable Standard: black / gray
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGS	eaton-digital-nzm-catalog-ca013003en-en-us.pdf eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-003.eps eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-006.eps eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-004.eps
DRAWINGS	
INSTALLATION INSTRUCTIONS	IL01208007Z
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
MCAD MODEL	DA-CD-nzm3_xtvd DA-CS-nzm3_xtvd
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Black
FITTED WITH:	Padlock
FRAME	NZM3
SUITABLE FOR	Switch disconnecter Power circuit breaker
COVER/DOOR TYPE	Door opens only with active rotation beyond the 0 position Door interlock not defeated in the locked OFF position.
LOCK NUMBER	Single lockable
LOCKING FACILITY	Lockable on the 0 position on the handle using up to 3 padlocks With door interlock
TYPE	• Accessory • Door coupling rotary handle
SPECIAL FEATURES	• Complete including rotary drive and coupling parts • Extension shaft

additionally
required.

- Cannot be combined with mechanical interlock
- External warning plate/designation label can be clipped on.
- Door coupling rotary handle for operating the switch through a closed control panel door

DEGREE OF PROTECTION	IP66
/ NEMA ENCLOSURE TYPE	4X, 12

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

