

Specifications



Photo is representative

Eaton 271515

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, red-yellow, max 60mm shaft, size 4

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	271515
MODEL CODE	NZM4-XTVDVR-60
EAN	4015082715151
PRODUCT LENGTH/DEPTH	230 mm
PRODUCT HEIGHT	130 mm
PRODUCT WIDTH	230 mm
PRODUCT WEIGHT	1.833 kg
COMPLIANCES	IEC UL/CSA RoHS conform
CERTIFICATIONS	IEC60947 CSA-C22.2 No. 5-09 UL listed CSA (Class No. 1437-01) UL (File No. E140305) CSA (File No. 22086) UL (Category Control Number DIHS) CE marking CSA certified UL489
GLOBAL CATALOG	271515

Product specifications

USED WITH	NZM4(-4), N(S)4(-4)
FEATURES	Lockable Red-yellow for emergency switching off
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product

Resources

BROCHURES

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

CATALOGS

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions.eps](#)

[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-007.eps](#)

DRAWINGS

[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-011.eps](#)

[eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps](#)

[eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-005.eps](#)

INSTALLATION INSTRUCTIONS

[IL01210003Z](#)

INSTALLATION VIDEOS

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

MCAD MODEL

[DA-CS-nzm4_xtvd_60](#)

[DA-CD-nzm4_xtvd_60](#)

TECHNICAL DATA SHEETS

[eaton-nzm-technical-information-sheet](#)

	standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Black
FITTED WITH:	Padlock
FRAME	NZM4
SUITABLE FOR	Emergency stop Switch disconnecter Power circuit breaker
COVER/DOOR TYPE	Door interlock can be modified in the unlocked ON position Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door can be opened in OFF Door interlock not defeated in the locked OFF position.
NUMBER OF POLES	Single-pole
LOCK NUMBER	Double lockable
LOCKING FACILITY	With door interlock Lockable on the handle on the switch using up to 3 padlocks

TYPE	• Accessory • Door coupling rotary handle
SPECIAL FEATURES	• Complete including rotary drive and coupling parts • Extension shaft additionally required. • For maximum shaft length 60 mm • Without shaft support • Cannot be combined with NZM...-XDZ additional handle • External warning plate/designation label can be clipped on. • Door coupling rotary handle for operating the switch through a closed control panel door
DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	IP66 4X. 12

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE: