

Specifications

Photo is representative

Eaton 272441

Eaton Moeller® series DILH Contactor, Ith =le: 1714 A, RAW 250: 230 - 250 V 50 - 60 Hz/230 - 350 V DC, AC and DC operation, Screw connection DILH1400/22(RAW250)

General specifications

PRODUCT NAME	Eaton Moeller® series DILH contactor
CATALOG NUMBER	272441
MODEL CODE	DILH1400/22(RAW250)
EAN	4015082724412
PRODUCT LENGTH/DEPTH	232 mm
PRODUCT HEIGHT	342 mm
PRODUCT WIDTH	260 mm
PRODUCT WEIGHT	14.4 kg
CERTIFICATIONS	UL File No.: E29096 UL Category Control No.: NLDX CSA File No.: 012528 IEC/EN 60947 CSA-C22.2 No. 60947-4-1-14 UL 60947-4-1 CSA UL CE IEC/EN 60947-4-1 VDE 0660 CSA Class No.: 3211-04 CCC
CATALOG NOTES	<ul style="list-style-type: none">• Contacts according to EN 50012• Conventional thermal current Ith of main contacts (1-pole, open) at 60°
GLOBAL CATALOG	272441

Product specifications

ACCESSORIES	Fitting options auxiliary contacts: on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SA
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

Resources

CATALOGS

[Product Range Catalog](#)
[Switching and protecting motors](#)

CHARACTERISTIC CURVE

[eaton-contactors-dilm-characteristic-curve.eps](#)
[eaton-contactors-short-time-loading-dilm-characteristic-curve-002.eps](#)

DECLARATIONS OF CONFORMITY

[DA-DC-00005052.pdf](#)
[DA-DC-00005043.pdf](#)

DRAWINGS

[eaton-contactors-dimensions-009.eps](#)

[eaton-contactors-mounting-dilm-dimensions.eps](#)

[eaton-contactors-mounting-dilm-dimensions-002.eps](#)

[eaton-contactors-dimensions-010.eps](#)

[eaton-contactors-mounting-dilm-3d-drawing-002.eps](#)

[eaton-contactors-3d-drawing.eps](#)

ECAD MODEL

[DA-CE-ETN.DILH1400_22\(RAW250\)](#)

INSTALLATION INSTRUCTIONS

[IL034039ZU2021_09.pdf](#)

MCAD MODEL

[eaton-iec-contactors-mcad-drawings-dilh1400.dwg](#)

[eaton-iec-contactors-mcad-3d-models-dilh1400.stp](#)

WIRING DIAGRAMS

[eaton-contactors-contact-dilm-wiring-diagram-004.eps](#)

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	Suppressor circuit in actuating electronics
OPERATING FREQUENCY	1000 mechanical Operations/h (AC operated) 1000 mechanical Operations/h (DC operated)
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	8000 V AC
UTILIZATION CATEGORY	AC-1: Non-inductive or slightly inductive loads, resistance furnaces
CONNECTION	Screw terminals
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE	80 °C

TEMPERATURE - MAX	
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CONVENTIONAL THERMAL CURRENT ITH AT 55°C (3-POLE, OPEN)	1462 A
CONVENTIONAL THERMAL CURRENT ITH OF MAIN CONTACTS (1-POLE, OPEN)	3500 A
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	63 W
APPLICATION	Mains contactors for resistive loads from 1000 A
PRODUCT CATEGORY	Contactors
ELECTRICAL	
CONNECTION TYPE OF MAIN CIRCUIT	Rail connection
SCREWDRIVER SIZE	2, Terminal screw, Control circuit cables, Pozidriv screwdriver 0.8 x 5.5/1 x 6 mm, Terminal screw, Control circuit cables, Standard screwdriver
VOLTAGE TYPE	AC/DC
DEGREE OF PROTECTION	IP00
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	2
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	2
NUMBER OF CONTACTS (NORMALLY CLOSED) AS MAIN CONTACT	0
NUMBER OF MAIN CONTACTS (NORMALLY OPEN CONTACT)	3
RATED BREAKING CAPACITY AT 1000 V	5800 A
RATED BREAKING	8200 A

CAPACITY AT 220/230 V**RATED BREAKING** 8200 A**CAPACITY AT 380/400 V****RATED BREAKING** 8200 A**CAPACITY AT 500 V****RATED BREAKING** 8200 A**CAPACITY AT 660/690 V****RATED CONTROL SUPPLY****VOLTAGE (US) AT AC, 50** 250 V**Hz - MAX****RATED CONTROL SUPPLY****VOLTAGE (US) AT AC, 50** 230 V**Hz - MIN****RATED CONTROL SUPPLY****VOLTAGE (US) AT AC, 60** 250 V**Hz - MAX****RATED CONTROL SUPPLY****VOLTAGE (US) AT AC, 60** 230 V**Hz - MIN**0.2 x US max - 0.6 x US
min, DC operated**DROP-OUT VOLTAGE** AC operated: 0.2 x US max
- 0.6 x US min, AC
operated**OVERVOLTAGE**

III

Sealing - Pick-up phase
(0.7 x Uc min - 1.15 x Uc
max): Contactor switches
on with certaintySealing - Pick-up phase (0 -
0.7 x Uc min: Contactor
does not switch onSealing - Voltage drops
(0.2 - 0.6 x Uc min \leq 12 ms:
Time is bridged
successfully

Sealing - Voltage drops

(0.6 - 0.7 x Uc min:

Contactor remains
switched onSealing - Voltage
interruptions (0 - 0.2 x Uc
min \leq 10 ms: Time is
bridged successfullySealing - Excess voltage
(1.15 - 1.3 x Uc max):Contactor remains
switched on

Sealing - Voltage drops

(0.2 - 0.6 x Uc min) $>$ 12
ms: Drop-out of the
contactor**BEHAVIOR IN MARGINAL
AND TRANSITIONAL
CONDITIONS**

	Sealing - Voltage interruptions 0 - 0.2 x Us min) > 10 ms: Drop-out of the contactor
DUTY FACTOR	100 %
ELECTROMAGNETIC COMPATIBILITY	Designed for operation in industrial environments. Its use in residential environments may cause radio-frequency interference, requiring additional noise suppression.
LIFESPAN, MECHANICAL	5,000,000 Operations (AC operated) 5,000,000 Operations (DC operated)
PICK-UP VOLTAGE	0.7 - 1.15 V DC x Us 0.7 - 1.15 V AC x Us
POWER CONSUMPTION, PICK-UP, 50 Hz	700 W, Pull-in power, Coil in a cold state and 1.0 x Us
	800 VA, Pull-in power, Coil in a cold state and 1.0 x Us
SAFE ISOLATION	1000 V AC, Between coil and contacts, According to EN 61140
POWER CONSUMPTION, PICK-UP, 60 Hz	800 VA, Pull-in power, Coil in a cold state and 1.0 x Us
	700 W, Pull-in power, Coil in a cold state and 1.0 x Us
SCREW SIZE	M3.5, Terminal screw, Control circuit cables M12, Terminal screw, Main connections
POWER CONSUMPTION, SEALING, 50 Hz	11.4 W, Coil in a cold state and 1.0 x Us 26.5 VA, Coil in a cold state and 1.0 x Us
POWER CONSUMPTION, SEALING, 60 Hz	26.5 VA, Coil in a cold state and 1.0 x Us 11.4 W, Coil in a cold state and 1.0 x Us
RESISTANCE	500 mΩ (Admissible transitional contact resistance - of the external control circuit device when actuating A11)
SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	15 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)

SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.75 - 2.5) mm ² , Control circuit cables 2 x (0.75 - 2.5) mm ² , Control circuit cables
SHOCK RESISTANCE	10 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 8 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms
TERMINAL CAPACITY (SOLID)	2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14, Control circuit cables
SIGNAL LEVEL	5 V - 15 V, PLC signal level (A3 - A4) to IEC/EN 61131-2 (type 2), Magnet systems
TERMINAL CAPACITY (BUSBAR)	80 mm width, Main connection
SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)	1600 A, Maximum motor rating (UL/CSA)
POWER CONSUMPTION	Control transformer with uk ≤ 7%
TIGHTENING TORQUE	35 Nm, Main cable connection screw/bolt 1.2 Nm, Screw terminals, Control circuit cables
WIDTH ACROSS FLATS	18 mm
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	250 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	230 V
RATED INSULATION VOLTAGE (UI)	1000 V
RATED MAKING CAPACITY (COS PHI TO	9840 A

IEC/EN 60947)

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V 0 A

RATED OPERATIONAL

CURRENT (IE) AT AC-4, 400 V 0 A

RATED OPERATIONAL

CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 1400 A

RATED OPERATIONAL

POWER AT AC-3, 380/400 V, 50 Hz 0 kW

RATED OPERATIONAL

POWER AT AC-4, 380/400 V, 50 Hz 0 kW

RATED OPERATIONAL

POWER (NEMA) 0 kW

RATED OPERATIONAL

VOLTAGE (UE) AT AC - MAX 1000 V

STATIC HEAT

DISSIPATION, NON-CURRENT-DEPENDENT PVS 6.5 W

STRIPPING LENGTH

(CONTROL CIRCUIT CABLE) 10 mm

SWITCHING TIME (AC

OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX 70 ms

SWITCHING TIME (AC

OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX 40 ms

1400 A, 600 V 60 Hz

3phase, 347 V 60 Hz

1phase, (UL/CSA)

1400 A, 480 V 60 Hz

3phase, 277 V 60 Hz

1phase, (UL/CSA)

CONVENTIONAL

THERMAL CURRENT ITH AT 40°C (3-POLE, OPEN) 1714 A

CONVENTIONAL

THERMAL CURRENT ITH AT 50°C (3-POLE, OPEN) 1533 A

CONVENTIONAL

THERMAL CURRENT ITH 1400 A

AT 60°C (3-POLE, OPEN)

ACTUATING VOLTAGE	RAW 250: 230 - 250 V 50 - 60 Hz/230 - 350 V DC
ALTITUDE	Max. 2000 m
OPERATING VOLTAGE AT AC, 50 HZ - MIN	230 V
OPERATING VOLTAGE AT AC, 50 HZ - MAX	250 V
OPERATING VOLTAGE AT AC, 60 HZ - MIN	230 V
OPERATING VOLTAGE AT AC, 60 HZ - MAX	250 V

PROJECT NAME:**PROJECT NUMBER:****PREPARED BY:****DATE:****Eaton Corporation plc**

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

