

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker for terminal blocks, Strip, white, labeled, horizontal: L1, L2, L3, N, GND, mounting type: latching, for terminal block width: 18 mm, Number of individual labels: 5, text field height: 5 mm, text field width: 18 mm

Your advantages

- Consists of five individual labels with 17.5 mm pitch
- Flat zack marker strips

Commercial data

|                                      |                    |
|--------------------------------------|--------------------|
| Item number                          | 2749576            |
| Packing unit                         | 10 pc              |
| Minimum order quantity               | 10 pc              |
| Sales key                            | BG05               |
| Product key                          | BG2122             |
| Catalog page                         | Page 63 (C-6-2013) |
| GTIN                                 | 4017918099237      |
| Weight per piece (including packing) | 0.83 g             |
| Weight per piece (excluding packing) | 0.56 g             |
| Customs tariff number                | 49119900           |
| Country of origin                    | PL                 |

# ZBN 18,LGS:L1-N,ERDE - Marker for terminal blocks



2749576

<https://www.phoenixcontact.com/us/products/2749576>

## Technical data

### Product properties

|              |                       |
|--------------|-----------------------|
| Product type | Labeled device marker |
| Pitch        | 18 mm                 |
| Type         | flat                  |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 02 |
|------------------|----|

### Marking

|                                     |                    |
|-------------------------------------|--------------------|
| Number of individual labels         | 5                  |
| Number of individual labels per row | 5                  |
| Number of marker strips             | 10                 |
| Printing direction                  | horizontal         |
| Printing                            | L1, L2, L3, N, GND |

## Environmental and real-life conditions

### UV resistance

|               |                                |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
|---------------|--------------------------------|

### Wipe resistance of inscriptions

|               |                                                |
|---------------|------------------------------------------------|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07            |
|               | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |

### Ambient conditions

|                                                     |                   |
|-----------------------------------------------------|-------------------|
| Ambient temperature (operation)                     | -40 °C ... 100 °C |
| Recommended ambient temperature (storage/transport) | 23 °C             |
| Recommended humidity (storage/transport)            | 50 %              |

## Mounting

|               |          |
|---------------|----------|
| Mounting type | latching |
|---------------|----------|

## Material specifications

|                                        |                                |
|----------------------------------------|--------------------------------|
| Color                                  | white (RAL 9010)               |
| Material                               | PA                             |
| Flammability rating according to UL 94 | V2                             |
| Components                             | free from silicone and halogen |

## Environmental and real-life conditions

### UV resistance

|               |                                |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
|---------------|--------------------------------|

### Wipe resistance of inscriptions

|               |                                     |
|---------------|-------------------------------------|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07 |
|---------------|-------------------------------------|

|  |                                                |
|--|------------------------------------------------|
|  | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
|--|------------------------------------------------|

Ambient conditions

|                                                     |                   |
|-----------------------------------------------------|-------------------|
| Ambient temperature (operation)                     | -40 °C ... 100 °C |
| Recommended ambient temperature (storage/transport) | 23 °C             |
| Recommended humidity (storage/transport)            | 50 %              |

Dimensions

|                   |          |
|-------------------|----------|
| Width             | 17.5 mm  |
| Text field width  | 18.00 mm |
| Text field height | 5.00 mm  |
| Pitch             | 18 mm    |

# ZBN 18,LGS:L1-N,ERDE - Marker for terminal blocks



2749576

<https://www.phoenixcontact.com/us/products/2749576>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27281101 |
| ECLASS-12.0 | 27281101 |
| ECLASS-13.0 | 27281101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000761 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

Environmental product compliance

|                                         |                            |
|-----------------------------------------|----------------------------|
| EU RoHS                                 |                            |
| Fulfills EU RoHS substance requirements | Yes, No exemptions         |
| EU REACH SVHC                           |                            |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt% |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)