Specifications







Eaton 276259

Main load disconnector Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 415 V, 20 A, 2P

| General specifications | | |
|-------------------------|---|--|
| PRODUCT NAME | Eaton Moeller series IS Disconnector | |
| CATALOG NUMBER | 276259 | |
| MODEL CODE | IS-20/2 | |
| EAN | 4015082762599 | |
| PRODUCT LENGTH/DEPTH | 60 mm | |
| PRODUCT HEIGHT | 80 mm | |
| PRODUCT WIDTH | 35.4 mm | |
| PRODUCT WEIGHT | 0.201 kg | |
| COMPLIANCES | RoHS conform | |
| CERTIFICATIONS | EN45545-2 IEC 61373 | |
| GLOBAL CATALOG | 276259 | |



| Product specification | |
|---|--|
| DEGREE OF PROTECTION | IP40 IP10 |
| TERMINALS | Lift terminal |
| EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT | 0.7 W |
| IMPRINT/INDICATION | Symbol "arrows" |
| LAMP SOCKET | Other |
| AMBIENT OPERATING TEMPERATURE - MAX | 40 °C |
| AMBIENT OPERATING TEMPERATURE - MIN | -5 °C |
| BUILT-IN DEPTH | 69.5 mm |
| HEAT DISSIPATION CAPACITY | 0 W |
| HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT | 0.6 W |
| LAMP POWER | 0 W |
| NUMBER OF CONTACTS (CHANGE-OVER CONTACTS) | 0 |
| NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS) | 2 |
| AMPERAGE RATING | 20 A |
| COLOR CALOTTE | Other |
| SWITCH TYPE | Other Off switch |
| RATED SHORT-TIME WITHSTAND CURRENT (ICW) | 1 kA |
| VOLTAGE TYPE | AC |
| LAMP TYPE | Other |
| ТҮРЕ | IS. Main load disconnector switch |
| APPLICATION | Switchgear for industrial and advanced commercial applications |
| NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS) | 2 |
| RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) | 20 A |

| Resources | |
|----------------------------|--|
| DECLARATIONS OF CONFORMITY | DA-DC-03 IS |
| DRAWINGS | <u>eaton-dimensions-mas-</u> <u>is.jpg</u> |
| ECAD MODEL | ETN.IS-20_2.edz |
| MCAD MODEL | eaton-main-load- disconnector-switch- mcad-3dmodels-is-2p.stp eaton-main-load- disconnector-switch- mcad-drawings-is-2p.dwg |
| WIRING DIAGRAMS | <u>IS_2P</u> |

| RATED OPERATIONAL VOLTAGE (UE) - MAX | 415 V |
|---|----------|
| RATED SWITCHING CAPACITY | 12.5 kA |
| STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT | 0 W |
| VOLTAGE RATING - MIN | 240 V |
| WIDTH IN NUMBER OF MODULAR SPACINGS | 2 |
| NUMBER OF POLES | Two-pole |

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









